



Clear Seam Sealer

General purpose, sealing butt joints and seams in window frame assembly

Uses

Clear Seam Sealer is specifically designed for sealing narrow joints and seams such as:

- Sealing butt joints and seams in window frame assembly
- Sealing screw heads in metal assembly
- General purpose sealant for small joints seams and cracks in most types of construction and metal assembly

Advantages

- Adheres to most metals and common building substrates
- Retains good flexibility with age
- Good flowability, can be applied by Plews Gun
- Translucent, unobtrusive after application

Description

Clear Seam Sealer is translucent sealant which provides a lasting weatherproof seal. Its ability to flow or be gunned into narrow joints and seams makes it ideal for use in metal fabrication, such as window frame assembly.

Properties

Form:	Colourless thixotropic liquid
Physical or chemical change:	Solvent loss
Chemical resistance:	Water and weather resistant. Not resistant to organic solvents.
Service temperature range:	Up to 70°C

Application Instructions

Surface preparation

All surfaces to which Clear Seam Sealer is to be applied must be clean, dry and free from contamination. Any traces of grease or oil should be removed using a solvent such as Solvent 10.

Application

For many applications, the use of a Plews Gun or similar is particularly convenient.

Note: Clear Seam Sealer is highly thixotropic to reduce slump after application, and thus may present a gelled appearance when the can is first opened. Stirring the material will simplify application or transfer to the Plews Gun. In cold weather, storage in a warm room prior to use will make application easier.

Clean up

Excess material, spillages and application equipment can be cleaned up using Solvent 10.

Limitations

Clear Seam Sealer should not be used in joints or cracks more than 3 mm in width. Whilst Clear Seam Sealer exhibits excellent adhesion to most metals and common building substrates, it is recommended that for new applications a preliminary adhesion test be carried out.

Supply

Clear Seam Sealer is supplied in 4 litre and 20 litre cans.

600512	Clear Seam Sealer 18.9 litre
600513	Clear Seam Sealer 3.75 litre

Storage

12 months in unopened original containers stored in a cool dry place.

Clear Seam Sealer

Important notice

A Safety Data Sheet (SDS) and Technical Data Sheet (TDS) are available from the Parchem website or upon request from the nearest Parchem sales office. Read the SDS and TDS carefully prior to use as application or performance data may change from time to time. In emergency, contact any Poisons Information Centre (phone 13 11 26 within Australia) or a doctor for advice.

Product disclaimer

This Technical Data Sheet (TDS) summarises our best knowledge of the product, including how to use and apply the product based on the information available at the time. You should read this TDS carefully and consider the information in the context of how the product will be used, including in conjunction with any other product and the type of surfaces to, and the manner in which, the product will be applied. Our responsibility for products sold is subject to our standard terms and conditions of sale. Parchem does not accept any liability either directly or indirectly for any losses suffered in connection with the use or application of the product whether or not in accordance with any advice, specification, recommendation or information given by it.