

## Water based, biodegradable seasoning compound for aluminium form

### Uses

Use to condition (season) new aluminium forms, forms that have been cleaned with acid or abrasive cleaners and forms that have been abrasive blasted or high pressure power washed.

### Advantages

- Superior alternative to the traditional and marginally effective liming process
- High viscosity ensures uniform conditioning when used in vertical or horizontal applications on both smooth or extruded surfaces
- 100% biodegradable
- Odourless
- Fast acting

### Description

Conlift Aluminium Seasoner combines a powerful detergent to help penetrate through residual processing oils left on the surface of the forms by the form manufacturer with a highly alkaline solution that oxidises the elemental aluminium on the surface of the forms to reduce the chemical bonding (sticking) that can take place between aluminium and fresh concrete.

### Properties

Density:	1,100 g/l
Colour:	Opaque
Odour:	None
Viscosity:	100 cps
Water soluble:	Yes
VOC Content:	None

### Application Instructions

Site environmental conditions, substrate conditions and construction have a major impact on product selection, application methods, procedures and rates, appearance and performance. Product literature provides general information applicable to some conditions. However, an adequate site test application by the purchaser or installer in advance of field scale use is mandatory (irrespective of any other verbal or written representations) to verify that product and quantities purchased can be satisfactorily applied and will achieve desired appearance and performance under intended use conditions.

Mix prior to each withdrawal from container.

Prior to application, verify that air temperature and aluminium

surface is no less than 10° C. Best results are achieved if air and form temperatures are above 21°C.

Before applying, verify that all surfaces are free of concrete buildup, coatings, form oil or other foreign materials that could interfere with the normal reaction process of Conlift Aluminium Seasoner. Power wash all new forms with warm water and a commercial grade detergent to remove excess mill oil/grease.

Typical application rate is 5 - 6.25 m<sup>2</sup>/l.

Apply product on side rails while the forms are still in stacks.

Roll Conlift Aluminium Seasoner onto the surface in a uniform manner using the appropriate nap roller: 12mm nap roller for smooth surfaces and a 20mm nap roller on extruded surfaces. A 450mm (18 inch) roller works best.

### Precautions

Do not use in temperatures below 10°C.

Do not use on aluminium forms that are not clean and free of concrete buildup, coatings, form oils or other foreign materials that could interfere with the normal reaction process.

While Conlift Aluminium Seasoner is reacting on the aluminium forms, highly flammable hydrogen gas is generated.

Therefore, do not use Conlift Aluminium Seasoner indoors unless the application area is well ventilated and free of any open flame or spark-generating devices.

Protect from freezing. Allowing product to freeze can cause the container to rupture as well as separation of the active components, resulting in poor product performance. Product which is suspected of freezing should not be used.

Verify that product is within the "use by" date stated on product packaging. Do not use expired product.

The use of expired product may result in poor product performance or failure.

### Supply

Product is packaged in 19 L pails.

ALSEA	Conlift Alumi Seasoner 19L
-------	----------------------------

### Storage

Store in a dry location within a temperature range between 4°C and 38°C.

### Shelf Life

Shelf life is 12 months. Use before the "use by" date stated on product packaging.

# Conlift Aluminium Seasoner

---

## Important notice

A Safety Data Sheet (SDS) and Technical Data Sheet (TDS) are available from the Parchem website or upon request from the nearest Parchem sales office. Read the SDS and TDS carefully prior to use as application or performance data may change from time to time. In emergency, contact any Poisons Information Centre (phone 13 11 26 within Australia) or a doctor for advice.

## Product disclaimer

This Technical Data Sheet (TDS) summarises our best knowledge of the product, including how to use and apply the product based on the information available at the time. You should read this TDS carefully and consider the information in the context of how the product will be used, including in conjunction with any other product and the type of surfaces to, and the manner in which, the product will be applied. Our responsibility for products sold is subject to our standard terms and conditions of sale. Parchem does not accept any liability either directly or indirectly for any losses suffered in connection with the use or application of the product whether or not in accordance with any advice, specification, recommendation or information given by it.

