

Infosafe No™ LPX27	Issue Date : November 2012	ISSUED by PARCHEMN
--------------------	----------------------------	--------------------

Product Name : **DURAFLOOR COLOUR PACK**

Classified as hazardous

1. Identification

GHS Product Identifier DURAFLOOR COLOUR PACK

Company Name Parchem Construction Supplies Pty Ltd (ABN 80 069 961 968)

Address 7 Lucca Road Wyong
NSW 2259 Australia

Telephone/Fax Number Tel: 02 4350 5000
Fax: 02 4351 2024

Emergency phone number 0800 154 666 (available 24/7)

Recommended use of the chemical and restrictions on use Pigmented paste in various colours used with epoxy flooring system.

Other Information Distributed in New Zealand by:
Concrete Plus
23 Watts Road
Sockburn
New Zealand
Tel: (03) 343 0090
Fax: (03) 343 0202

This MSDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since Parchem Construction Supplies Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this MSDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company. Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.

www.parchem.co.nz

2. Hazard Identification

GHS classification of the substance/mixture Classified as Hazardous according to the Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001, New Zealand.
Classified as Dangerous Goods for transport according to the New Zealand Standard NZS 5433:2012 Transport of Dangerous Goods on Land.
6.3A - Substance that is irritating to the skin.
6.4A - Substance that is irritating to the eye.
6.5B - Substance that is a contact sensitiser.
6.8B - Substance that is suspected to be a human reproductive or developmental toxicant.
6.9B - Substance that is harmful to human target organs or systems.
9.1B - Substance that is ecotoxic in the aquatic environment.

Signal Word (s) Warning

Hazard Statement (s) H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H361 Suspected of damaging fertility or the unborn child.
H371 May cause damage to organs through prolonged or repeated exposure (dermal).
H411 Toxic to aquatic life with long lasting effects.

Pictogram (s) Exclamation mark, Environment, Health hazard,

Infosafe No™ LPX27

Issue Date : November 2012

ISSUED by PARCHEMN

Product Name : DURAFLOOR COLOUR PACK

Classified as hazardous


Precautionary statement – Prevention

P103 Read label before use. -This statement applies only where the substance is available to the general public.
 P201 Obtain special instructions before use.
 P202 Do not handle until all safety precautions have been read and understood.
 P260 Do not breathe dust/fume/gas/mist/vapours/spray.
 P264 Wash skin thoroughly after handling.
 P272 Contaminated work clothing should not be allowed out of the workplace.
 P273 Avoid release to the environment. -This statement does not apply where this is the intended use.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statement – Response

GENERAL
 P308+P313 IF exposed or concerned: Get medical advice/ attention.
 P314 Get medical advice/attention if you feel unwell.
 P391 Collect spillage.
 EYES
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P337+P313 If eye irritation persists: Get medical advice/attention.
 SKIN
 P302+P352 IF ON SKIN: Wash with plenty of soap and water.
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
 P362 Take off contaminated clothing and wash before re-use.
 P405 Store locked up.

Precautionary statement – Storage
Precautionary statement – Disposal

P501 In the case of a substance that is in compliance with a HSNO approval other than a Part 6A (Group Standards) approval, a label must provide a description of one or more appropriate and achievable methods for the disposal of a substance in accordance with the Hazardous Substances (Disposal) Regulations 2001. This may also include any method of disposal that must be avoided. See Section 13 for disposal details.

3. Composition/information on ingredients

Ingredients	Name	CAS	Proportion
	Bisphenol A epoxy resin	25068-38-6	10-<40 %
	C12-C14 Glycidyl ether	68609-97-2	<20 %
	Formaldehyde, polymer with (chloromethyl)oxirane and phenol	9003-36-5	<20 %
	Xylene	1330-20-7	<1 %

4. First-aid measures

Inhalation	If inhaled, remove affected person from contaminated area. Keep at rest until recovered. If symptoms persist seek medical attention.
Ingestion	Do NOT induce vomiting. Wash out mouth with water. Seek medical attention.
Skin	Wash affected area thoroughly with soap and water. Remove contaminated clothing and wash before reuse or discard. Seek medical attention.
Eye contact	If in eyes, hold eyelids apart and flush the eyes continuously with running water. Continue flushing for several minutes until all contaminants are washed out completely. Seek medical attention.
First Aid Facilities	Eye wash, safety shower and normal washroom facilities.
Advice to Doctor	Treat symptomatically.
Other Information	For advice, contact a Poisons Information Centre (Phone eg Australia 131 126; New Zealand 0800 764 766) or a doctor (at once).

Infosafe No™ LPX27	Issue Date : November 2012	ISSUED by PARCHEMN
--------------------	----------------------------	--------------------

Product Name : DURAFLOOR COLOUR PACK

Classified as hazardous

5. Fire-fighting measures

Suitable extinguishing media	Use carbon dioxide, dry chemical, foam, water fog or water spray.
Hazards from Combustion Products	Under fire conditions this product may emit toxic and/or irritating fumes including carbon monoxide and carbon dioxide.
Specific hazards arising from the chemical	Combustible liquid. This product will readily burn under fire conditions.
Hazchem Code	•3Z
Decomposition Temp.	Not available
Precautions in connection with Fire	Fire-fighters should wear full protective clothing and self contained breathing apparatus (SCBA) operated in positive pressure mode. Water spray may be used to keep fire exposed containers cool.

6. Accidental release measures

Emergency Procedures	Wear appropriate personal protective equipment and clothing to prevent exposure. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unprotected personnel. If possible contain the spill. Place inert absorbent, non-combustible material onto spillage. Use clean non-sparking tools to collect the material and place into suitable labelled containers for subsequent recycling or disposal. Dispose of waste according to the applicable local and national regulations. If contamination of sewers or waterways occurs inform the local water and waste management authorities in accordance with local regulations.
-----------------------------	--

7. Handling and storage

Precautions for Safe Handling	Use only in a well ventilated area. Keep containers sealed when not in use. Prevent the build up of mists or vapours in the work atmosphere. Avoid inhalation of vapours and mists, and skin or eye contact. Do not use near ignition sources. Do not pressurise, cut, heat or weld containers as they may contain hazardous residues. Maintain high standards of personal hygiene i.e. Washing hands prior to eating, drinking, smoking or using toilet facilities.
Conditions for safe storage, including any incompatibilities	Store in a cool, dry well-ventilated area away from heat, sources of ignition, oxidising agents, foodstuffs, and clothing and out of direct sunlight. Keep containers closed when not in use and securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Do NOT pressurise, cut, heat or weld containers as they may contain hazardous residues. For information on the design of the storeroom, reference should be made to Australian Standard AS1940 - The storage and handling of flammable and combustible liquids. Reference should also be made to all State and Federal regulations.

8. Exposure controls/personal protection

Occupational exposure limit values	No exposure value assigned for this specific material by the New Zealand Department of Labour. However, the available exposure limits for ingredients are listed below:
---	---

New Zealand Occupational Safety and Health Service (OSH) Workplace Exposure Standards:

Substance	TWA		STEL		NOTICES
	ppm	mg/m ³	ppm	mg/m ³	
Xylene	50	217	-	-	-

TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eight-hour working day, for a five-day week.

STEL (Short Term Exposure Limit): The average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.

Biological Limit Values	Biological Exposure Indices (BEI) from American Conference of Industrial Hygienists (ACGIH) for ingredients are as follows:
--------------------------------	---

Infosafe No™ LPX27	Issue Date : November 2012	ISSUED by PARCHEMN
--------------------	----------------------------	--------------------

Product Name : **DURAFLOOR COLOUR PACK**

Classified as hazardous

	Determinant	Sampling Time	Biological Exposure
	Indice (BEI) XYLENE [1330-20-7] Methylhippuric acids in urine	End of shift shift of work week	1.5mg/g creatinine
Appropriate engineering controls	Use with good general ventilation. If mists or vapours are produced local exhaust ventilation should be used.		
Respiratory Protection	If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable organic vapour/mist filter should be used. Reference should be made to Australian Standards AS/NZS 1715, Selection, Use and maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.		
Eye Protection	Safety glasses with side shields or chemical goggles should be worn. Final choice of appropriate eye/face protection will vary according to individual circumstances. Eye protection devices should conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors for Industrial Applications.		
Hand Protection	Wear gloves of impervious material. Final choice of appropriate gloves will vary according to individual circumstances i.e. methods of handling or according to risk assessments undertaken. Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.		
Body Protection	Suitable workwear should be worn to protect personal clothing, eg cotton overalls buttoned at neck and wrist. When large quantities are handled the use of plastic aprons and rubber boots is recommended.		

9. Physical and chemical properties

Appearance	Pigmented paste in various colours (base white).
Odour	Epoxy resin
Decomposition	Not available
Temperature	
Melting Point	Not available
Boiling Point	>200°C (resin)
Solubility in Water	Insoluble
Specific Gravity	1.85 (23°C)
pH	Not available
Vapour Pressure	0.01 Pascals
Vapour Density (Air=1)	Not available
Odour Threshold	Not available
Viscosity	Not available
Partition Coefficient: n-octanol/water	Not available
Flash Point	>155°C (resin)
Flammability	Not flammable
Auto-Ignition	Not available
Temperature	
Flammable Limits - Lower	Not available
Flammable Limits - Upper	Not available

10. Stability and reactivity

Reactivity	Reacts with incompatibles
Chemical Stability	Stable under normal conditions of handling and storage.
Conditions to Avoid	Heat, flames and other ignition sources.

Infosafe No™ LPX27	Issue Date : November 2012	ISSUED by PARCHEMN
--------------------	----------------------------	--------------------

Product Name : **DURAFLOOR COLOUR PACK**

Classified as hazardous

Incompatible Materials	Strong acids, strong bases, strong oxidisers.
Hazardous Decomposition Products	Thermal decomposition may result in the release of toxic and/or irritating fumes including carbon monoxide and carbon dioxide.
Hazardous Polymerization	Will not occur.

11. Toxicological Information

Toxicology Information	No toxicity data available for this product.
Ingestion	Ingestion of this product may irritate the gastric tract causing nausea, vomiting and possible abdominal pain.
Inhalation	Inhalation of product vapours may cause irritation of the nose, throat and respiratory system. Symptoms of exposure can include sneezing and coughing.
Skin	Causes skin irritation. Skin contact will cause redness, itching and swelling. Repeated exposure may cause skin dryness and cracking and may lead to dermatitis.
Eye	Causes serious eye irritation. On eye contact this product will cause tearing, stinging, blurred vision, and redness.
Respiratory sensitisation	Not expected to be a respiratory sensitiser.
Skin Sensitisation	May cause an allergic skin reaction.
Germ cell mutagenicity	Not considered to be a mutagenic hazard.
Carcinogenicity	Not considered to be a carcinogenic hazard.
Reproductive Toxicity	Suspected of damaging fertility or the unborn child.
STOT-single exposure	Not expected to cause damage to organs.
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure by skin contact.
Aspiration Hazard	Not expected to be an aspiration hazard.

12. Ecological information

Ecotoxicity	Toxic to aquatic life with long lasting effects.
Persistence and degradability	Not available
Mobility	Not available
Bioaccumulative Potential	Not available
Environmental Protection	Do not discharge the product into drains, waterways or sewers.

13. Disposal considerations

Disposal Considerations	<p>Product Disposal: Product wastes are controlled wastes and should be disposed of in accordance with all applicable local and national regulations. This product can be disposed through a licensed commercial waste collection service. It can be disposed by burning in an approved high temperature incineration facility; or alternatively, it can be reacted with the catalyst/hardener component to enable it to cure to an inert solid that can be disposed in a licensed landfill facility.</p> <p>Personal protective clothing and equipment as specified in Section 8 of this SDS must be worn during handling and disposal of this product. The ventilation requirements as specified in the same section must also be followed, and the precautions given in Section 7 of this SDS regarding handling must also be followed.</p> <p>Do not dispose into the sewerage system. Do not discharge into drains or</p>
--------------------------------	---

Infosafe No™ LPX27	Issue Date : November 2012	ISSUED by PARCHEMN
--------------------	----------------------------	--------------------

Product Name : **DURAFLOOR COLOUR PACK**

Classified as hazardous

watercourses or dispose where ground or surface waters may be affected. In New Zealand, the disposal agency or contractor must comply with the New Zealand Hazardous Substances (Disposal) Regulations 2001. Further details regarding disposal can be obtained on the ERMA New Zealand website under specific group standards.

Container Disposal:
The container or packaging must be cleaned and rendered incapable of holding any substance. It can then be disposed of in a manner consistent with that of the substance it contained. In this instance the packaging can be disposed through a commercial waste collection service.
Alternatively, the container or packaging can be recycled if the hazardous residues have been thoroughly cleaned or rendered non-hazardous.
In New Zealand, the packaging (that may or may not hold any residual substance) that is lawfully disposed of by householders or other consumers through a public or commercial waste collection service is a means of compliance with regulations.

14. Transport information

Transport Information	<p>Road and Rail Transport: This material is classified as a Class 9 - Miscellaneous Substances according to NZS 5433:2012 Transport of Dangerous Goods on Land. Must not be loaded in the same freight container or on the same vehicle with: - Class 1, Explosives Class 9 dangerous goods that contain organic matter must not be loaded in the same bulk container or tankwagon with dangerous goods of Division 5.1 unless the Class 9 and Division 5.1 dangerous goods are in separate compartments of a bulk container or tankwagon. Goods of packing group II or III may be loaded in the same freight container or on the same vehicle if transported in segregation devices. Segregation devices may be used to segregate Dangerous goods of Class 9 when the nature of those dangerous goods requires them to be segregated from dangerous goods of Class 3, 4, 5, 6 or 8 or from food items.</p> <p>Marine Transport (IMO/IMDG): Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea. UN No.: 3082 Proper Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Contains Bisphenol A Epoxy Resin) DG Class: 9 Packaging Group: III EMS No.: F-A, S-F Special provisions: 274, 335</p> <p>Air Transport (ICAO/IATA): Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air. UN No: 3082 Proper Shipping Name: : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Contains Bisphenol A Epoxy Resin) Class: 9 Packing Group: III Label: Miscellaneous Packing Instruction: 964 (For passenger and cargo aircraft) Packing Instruction: 964 (For cargo aircraft only) Special provisions: A97, A158 3082</p>
U.N. Number	3082
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. - (CONTAINS BISPHENOL A EPOXY RESIN)
Transport hazard class(es)	9
Hazchem Code	•3Z
Packing Group	III

Infosafe No™ LPX27 Issue Date : November 2012 ISSUED by PARCHEMN

Product Name : **DURAFLOOR COLOUR PACK**

Classified as hazardous

EPG Number 9C1

IERG Number 47

IMDG Marine pollutant Yes

15. Regulatory information

Regulatory Information Classified as Hazardous according to the Hazardous Substances (Minimum degrees of hazard) Regulations 2001.
Group Standard: Additives, Process Chemicals and Raw Materials (Subsidiary Hazard) Group Standard 2006

HSNO Approval Number HSR002503

16. Other Information

Date of preparation or last revision of SDS SDS Reviewed: November 2012
Supersedes: January 2008

Contact Person/Point Technical Support: 1800 812 864
...End Of MSDS...

© Copyright ACOHS Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe MSDS displayed is the intellectual property of Acohs Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe MSDS displayed is the intellectual property of Acohs Pty Ltd.
The compilation of MSDS's displayed is the intellectual property of Acohs Pty Ltd.

Copying of any MSDS displayed is permitted for personal use only and otherwise is not permitted. In particular the MSDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of MSDS without the express written consent of Acohs Pty Ltd.