

Infosafe No™ LPT5F	Issue Date : September 2012	ISSUED by PARCHEMC
--------------------	-----------------------------	--------------------

Product Name : **DURAFLOOR M PRIMER**

Classified as hazardous

1. Identification

GHS Product Identifier	DURAFLOOR M PRIMER
Company Name	Parchem Construction Supplies Pty Ltd (ABN 80 069 961 968)
Address	7 Lucca Road Wyong NSW 2259 Australia
Telephone/Fax Number	Tel: 02 4350 5000 Fax: 02 4351 2024
Emergency phone number	1800 638 556 (available 24/7)
Recommended use of the chemical and restrictions on use	A primer to promote adhesion of some sealants to metals, glass and ceramics.
Other Information	<p>This MSDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since Parchem Construction Supplies Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this MSDS in the context of how the user intends to handle and use the product in the workplace.</p> <p>If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company. Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.</p> <p>www.parchem.com.au</p>

2. Hazard Identification

GHS classification of the substance/mixture	<p>Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia.</p> <p>Classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)</p> <p>Flammable Liquids: Category 2 Skin Corrosion/Irritation: Category 2 Eye Damage/Irritation: Category 2A Toxic to Reproduction: Category 2 STOT Single Exposure Category 3 (narcotic) STOT Repeated Exposure Category 2 Aspiration Hazard: Category 1</p>
Signal Word (s)	Danger
Hazard Statement (s)	<p>H225 Highly flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H361 Suspected of damaging fertility or the unborn child. H373 May cause damage to organs through prolonged or repeated exposure by inhalation.</p>
Pictogram (s)	Flame, Exclamation mark, Health hazard



Precautionary statement – Prevention	<p>P102 Keep out of reach of children. P103 Read label before use. P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and</p>
---	---

Infosafe No™ LPT5F

Issue Date : September 2012

ISSUED by PARCHEMC

Product Name : **DURAFLOOR M PRIMER**

Classified as hazardous

understood.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/eye protection/face protection.

Precautionary

statement – Response

GENERAL:

P101 If medical advice is needed, have product container or label at hand.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P391 Collect spillage.

SKIN:

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P362 Take off contaminated clothing and wash before reuse.

INHALATION:

P304+P340 IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

P314 Get medical advice/attention if you feel unwell.

INGESTION:

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P331 Do NOT induce vomiting.

EYES:

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

Precautionary

statement – Storage

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235: Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Precautionary

statement – Disposal

P501 Dispose of contents/container to an approved waste disposal plant.

3. Composition/information on ingredients

Ingredients	Name	CAS	Proportion
	Toluene	108-88-3	60-<100 %
	Ethyl acetate	141-78-6	10-30 %
	Ingredients determined not to be hazardous.		Balance

4. First-aid measures

Inhalation	If inhaled, remove from contaminated area. Apply artificial respiration if not breathing. Seek medical attention.
Ingestion	Do NOT induce vomiting. Wash out mouth and lips with water. Where vomiting occurs naturally have affected person place head below hip level in order to reduce risk of aspiration. Seek immediate medical attention.
Skin	Wash affected area thoroughly with soap and water. Remove contaminated clothing and wash before reuse or discard. Seek medical attention.
Eye contact	If in eyes, hold eyelids apart and flush the eyes continuously with running water. Continue flushing for several minutes until all contaminants are washed out completely. Seek medical attention.
First Aid Facilities	Eye wash, safety shower and normal washroom facilities.
Advice to Doctor	Treat symptomatically.

Infosafe No™ LPT5F

Issue Date : September 2012

ISSUED by PARCHEMC

Product Name : **DURAFLOOR M PRIMER**

Classified as hazardous

Other Information For advice, contact a Poisons Information Centre (Phone eg Australia 131 126; New Zealand 0800 764 766) or a doctor (at once).

5. Fire-fighting measures

Suitable extinguishing media Use carbon dioxide, dry chemical or foam. Alcohol resistant foam is preferred. If not available normal foam can be used.

Unsuitable Extinguishing Media DO NOT USE water jets.

Hazards from Combustion Products Under fire conditions this product may emit toxic and/or irritating fumes and gases including carbon monoxide, carbon dioxide, oxides of sulphur and trace amounts of hydrogen chloride.

Specific hazards arising from the chemical Highly flammable liquid and vapour. Vapour/air mixtures may ignite explosively. Flashback along the vapour trail may occur. Runoff to sewer may create fire or explosion hazard.

Hazchem Code •3YE

Decomposition Temp. Not available

Precautions in connection with Fire Fire fighters should wear Self-Contained Breathing Apparatus (SCBA) operated in positive pressure mode and full protective clothing to prevent exposure to vapours or fumes. Water spray may be used to cool down heat-exposed containers. Fight fire from safe location. This product should be prevented from entering drains and watercourses.

6. Accidental release measures

Emergency Procedures Wear appropriate personal protective equipment and clothing to prevent exposure. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unprotected personnel. If possible contain the spill. Place inert absorbent, non-combustible material onto spillage. Use clean non-sparking tools to collect the material and place into suitable labelled containers for subsequent recycling or disposal. Dispose of waste according to the applicable local and national regulations. If contamination of sewers or waterways occurs inform the local water and waste management authorities in accordance with local regulations.

7. Handling and storage

Precautions for Safe Handling Avoid contact with skin and eyes. Wear overalls, impervious gloves and safety glasses. Use in designated areas with adequate ventilation. Use approved flammable liquid storage containers in the work area. Prevent release of vapours and mists into workplace air. Keep containers closed when not in use. Take precautionary measures against static discharges. Keep material away from sparks, flames and other ignition sources. Do not empty into drains. Ensure a high level of personal hygiene is maintained when using this product, that is, always wash hands before eating, drinking, smoking or using the toilet facilities.

Conditions for safe storage, including any incompatibilities Store in a cool, dry, well-ventilated area away from sources of ignition, oxidising agents, strong acids, foodstuffs, and clothing. Keep containers closed when not in use and securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Have appropriate fire extinguishers available in and near the storage area. Take precautions against static electricity discharges. Use proper grounding procedures. For information on the design of the storeroom, reference should be made to Australian Standard AS1940 - The storage and handling of flammable and combustible liquids. Reference should also be made to all applicable local and national regulations.

8. Exposure controls/personal protection

Occupational exposure limit values No exposure value assigned for this material by Safe Work, Australia. However, the available exposure limits for ingredients are listed below:
Safe Work, Australia Exposure Standards:

Substance	TWA		STEL		NOTICES
	ppm	mg/m ³	ppm	mg/m ³	
Toluene	50	191	150	574	Sk
Ethyl Acetate	200	720	400	1440	-

Infosafe No™ LPT5F	Issue Date : September 2012	ISSUED by PARCHEMC
--------------------	-----------------------------	--------------------

Product Name : **DURAFLOOR M PRIMER**

Classified as hazardous

Biological Limit Values	<p>TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eight-hour working day, for a five-day week.</p> <p>STEL (Short Term Exposure Limit): The average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.</p> <p>Biological Exposure Indices (BEI) from American Conference of Industrial Hygienists (ACGIH) for ingredients are as follows:</p> <table border="0" style="width:100%;"> <thead> <tr> <th style="text-align: left;">Determinant Indices (BEI)</th> <th style="text-align: left;">Sampling Time</th> <th style="text-align: left;">Biological Exposure</th> </tr> </thead> <tbody> <tr> <td colspan="3">TOLUENE [108-88-3]</td> </tr> <tr> <td>o-Cresol in urine</td> <td>End of shift</td> <td>0.3mg/g creatinine</td> </tr> <tr> <td>Toluene in urine</td> <td>End of shift</td> <td>0.03 mg/L</td> </tr> <tr> <td>Toluene in blood</td> <td>Prior to last shift of work week</td> <td>0.02 mg/L</td> </tr> </tbody> </table>	Determinant Indices (BEI)	Sampling Time	Biological Exposure	TOLUENE [108-88-3]			o-Cresol in urine	End of shift	0.3mg/g creatinine	Toluene in urine	End of shift	0.03 mg/L	Toluene in blood	Prior to last shift of work week	0.02 mg/L
Determinant Indices (BEI)	Sampling Time	Biological Exposure														
TOLUENE [108-88-3]																
o-Cresol in urine	End of shift	0.3mg/g creatinine														
Toluene in urine	End of shift	0.03 mg/L														
Toluene in blood	Prior to last shift of work week	0.02 mg/L														
Appropriate engineering controls	<p>Provide sufficient ventilation to keep airborne levels below the exposure limits. Where vapours or mists are generated, particularly in enclosed areas, and natural ventilation is inadequate, a flameproof exhaust ventilation system is required. Refer to AS 1940 - The storage and handling of flammable and combustible liquids and AS/NZS 60079.10.1:2009 Explosive atmospheres - Classification of areas - Explosive gas atmospheres, for further information concerning ventilation requirements.</p>															
Respiratory Protection	<p>If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable organic vapour filter should be used. Reference should be made to Australian/New Zealand Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.</p>															
Eye Protection	<p>Safety glasses with side shields or chemical goggles should be worn. Final choice of appropriate eye/face protection will vary according to individual circumstances. Eye protection devices should conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors for Industrial Applications.</p>															
Hand Protection	<p>Wear gloves of impervious material. Final choice of appropriate gloves will vary according to individual circumstances i.e. methods of handling or according to risk assessments undertaken. Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.</p>															
Body Protection	<p>Suitable protective work wear, e.g. cotton overalls buttoned at neck and wrist is recommended. Chemical resistant apron is recommended where large quantities are handled.</p>															

9. Physical and chemical properties

Appearance	Transparent, slightly coloured liquid
Odour	Aromatic
Decomposition Temperature	Not available
Melting Point	Not available
Boiling Point	Not available
Solubility in Water	Insoluble
Specific Gravity	0.87 (23°C)
pH	Not available
Vapour Pressure	44 mmHg (25°C)
Vapour Density (Air=1)	Not available
Evaporation Rate	Not available
Odour Threshold	Not available
Viscosity	Not available
Volatile Component	95% w/w

Infosafe No™ LPT5F	Issue Date : September 2012	ISSUED by PARCHEMC
--------------------	-----------------------------	--------------------

Product Name : **DURAFLOOR M PRIMER**

Classified as hazardous

Partition Coefficient: n-octanol/water	Not available
Flash Point	-4°C (Ethyl acetate) 4.4°C (Toluene)
Flammability	Highly flammable
Auto-Ignition Temperature	Not available
Flammable Limits - Lower	1.3% (Toluene)
Flammable Limits - Upper	7.0% (Toluene)
Initial boiling point and boiling range	77°C (Toluene)

10. Stability and reactivity

Reactivity	Reacts with incompatibles.
Chemical Stability	Stable under normal conditions of storage and handling.
Conditions to Avoid	Heat, flames and other ignition sources.
Incompatible Materials	Strong oxidising agents, acids and organic peroxides.
Hazardous Decomposition Products	Thermal decomposition may result in the release of toxic and/or irritating fumes and gases including carbon monoxide, carbon dioxide, oxides of sulphur and trace amounts of hydrogen chloride.
Possibility of hazardous reactions	May react with incompatible materials.
Hazardous Polymerization	Will not occur.

11. Toxicological Information

Toxicology Information	No toxicity data available for this material.
Acute Toxicity - Inhalation Ingestion	LC50 (Mouse): 400ppm/24hr (Toluene)
Inhalation	May be fatal if swallowed and enters airways. Small amounts of liquid aspirated into the respiratory system during ingestion or from vomiting may cause severe pulmonary injury that may lead to death. May cause irritation to the mouth, throat, esophagus and stomach with symptoms of nausea, abdominal discomfort, vomiting and diarrhoea.
Skin	May cause drowsiness or dizziness. May cause irritation to the mucous membrane and upper airways, especially where vapours or mists are generated. Symptoms include sneezing, coughing, wheezing, shortness of breath, headache, dizziness, drowsiness nausea and vomiting.
Eye	Causes skin irritation. Skin contact will cause redness, itching and swelling. Repeated exposure may cause skin dryness and cracking and may lead to dermatitis.
Respiratory sensitisation	Causes serious eye irritation. On eye contact this product will cause tearing, stinging, blurred vision, and redness.
Skin Sensitisation	Not expected to be a respiratory sensitiser.
Germ cell mutagenicity	Not expected to be a skin sensitiser.
Carcinogenicity	Not considered to be a mutagenic hazard.
Reproductive Toxicity	Not considered to be a carcinogenic hazard.
STOT-single exposure	Suspected of damaging fertility or the unborn child.
	May cause drowsiness or dizziness.

Infosafe No™ LPT5F

Issue Date : September 2012

ISSUED by PARCHEMC

Product Name : **DURAFLOOR M PRIMER**

Classified as hazardous

STOT-repeated exposure May cause damage to organs through prolonged exposure if inhaled. Inhalation can cause irritation of the nose, throat and respiratory system.
Aspiration Hazard May be fatal if swallowed and enters airways.

12. Ecological information

Ecotoxicity No ecological data are available for this material.
Persistence and degradability Not available
Mobility Not available
Bioaccumulative Potential Not available
Environmental Protection Do not discharge this material into waterways, drains and sewers.

13. Disposal considerations

Disposal Considerations Dispose of waste according to applicable local and national regulations. Labels should not be removed from containers until they have been cleaned. Do not cut, puncture or weld on or near containers. Empty containers may contain hazardous residues. Contaminated containers must not be treated as household waste. Containers should be cleaned by appropriate methods and then re-used or disposed of by landfill or incineration as appropriate. Do not incinerate closed containers. Advise flammable nature.

14. Transport information

Transport Information Road and Rail Transport (ADG Code):
This material is Dangerous Goods Class 3 - Flammable Liquid according to The Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)
Class 3 - Flammable Liquids are incompatible in a placard load with any of the following:
- Class 1, Explosives
- Division 2.1, Flammable Gases, (Division 2.1 and Class 3 are incompatible in transport if both are in tanks or other receptacles with a capacity individually exceeding 500 L.)
- Division 2.3, Toxic Gases
- Division 4.2 Spontaneously Combustible Substances
- Division 5.1 Oxidising substances and Division 5.2, Organic Peroxides
- Class 6 Toxic or Infectious Substances (where the flammable liquid is nitromethane)
- Class 7 Radioactive Substances.

Marine Transport (IMO/IMDG):
Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.
UN No.: 1263
Proper Shipping Name: PAINT RELATED MATERIAL
DG Class: 3
Packaging Group: II
EMS No.: F-E, S-E
Special provisions: 163

Air Transport (ICAO/IATA):
Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.
UN No: 1263
Proper Shipping Name: Paint related material
Class: 3
Packing Group: II
Label: Miscellaneous
Packing Instruction: 353 (For passenger and cargo aircraft)
Packing Instruction: 364 (For cargo aircraft only)
Special provisions: A3, A72

Infosafe No™ LPT5F	Issue Date : September 2012	ISSUED by PARCHEMC
--------------------	-----------------------------	--------------------

Product Name : **DURAFLOOR M PRIMER**

Classified as hazardous

U.N. Number	1263
UN proper shipping name	PAINT RELATED MATERIAL
Transport hazard class(es)	3
Hazchem Code	•3YE
Packing Group	II
EPG Number	3C1
IERG Number	14
IMDG Marine pollutant	No

15. Regulatory information

Regulatory Information	Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia. Classified as a Scheduled Poison according to the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).
Poisons Schedule	S6

16. Other Information

Date of preparation or last revision of SDS	SDS Reviewed: September 2012 Supersedes: September 2007
Contact Person/Point	Technical Support: 1800 812 864 ...End Of MSDS...

© Copyright ACOHS Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe MSDS displayed is the intellectual property of Acohs Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe MSDS displayed is the intellectual property of Acohs Pty Ltd.
The compilation of MSDS's displayed is the intellectual property of Acohs Pty Ltd.

Copying of any MSDS displayed is permitted for personal use only and otherwise is not permitted. In particular the MSDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of MSDS without the express written consent of Acohs Pty Ltd.