

Infosafe No™ LPT68 Issue Date : July 2013 ISSUED by PARCHEMC

Product Name : DURAFLOOR SLX HARDENER

Classified as hazardous

1. Identification

GHS Product Identifier	DURAFLOOR SLX HARDENER
Company Name	Parchem Construction Supplies Pty Ltd (ABN 80 069 961 968)
Address	7 Lucca Road Wyong NSW 2259 Australia
Telephone/Fax Number	Tel: 02 4350 5000 Fax: 02 4351 2024
Emergency phone number	1800 638 556 (available 24/7)
Recommended use of the chemical and restrictions on use	Used in conjunction with base, two colour packs and fillers to form a self-levelling epoxy floor.
Other Information	<p>This SDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since Parchem Construction Supplies Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this MSDS in the context of how the user intends to handle and use the product in the workplace.</p> <p>If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company. Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.</p> <p>www.parchem.com.au</p>

2. Hazard Identification

GHS classification of the substance/mixture	<p>Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia.</p> <p>Classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)</p> <p>Acute Toxicity - Dermal: Category 5 Eye Damage/Irritation: Category 1 Acute Toxicity - Inhalation: Category 4 Acute Toxicity - Oral: Category 4 Skin Corrosion/Irritation: Category 1A Sensitization - Skin: Category 1 Hazardous to the Aquatic Environment - Acute Hazard: Category 3 Hazardous to the Aquatic Environment - Long-Term Hazard: Category 3</p>
Signal Word (s)	Danger
Hazard Statement (s)	H302 Harmful if swallowed. H313 May be harmful in contact with skin. H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H332 Harmful if inhaled. H402 Harmful to aquatic life. H412 Harmful to aquatic life with long lasting effects. P102 Keep out of reach of children. P103 Read label before use.
General Precautionary Statement (s)	
Pictogram (s)	Corrosion, Exclamation mark

Infosafe No™ LPT68

Issue Date : July 2013

ISSUED by PARCHEMC

 Product Name : **DURAFLOOR SLX HARDENER**

Classified as hazardous


Precautionary statement – Prevention

P260 Do not breathe fume/mist/vapours.
 P264 Wash contaminated skin thoroughly after handling.
 P270 Do not eat, drink or smoke when using this product.
 P271 Use only outdoors or in a well-ventilated area.
 P272 Contaminated work clothing should not be allowed out of the workplace.
 P273 Avoid release to the environment.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statement – Response

P301+P312 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
 P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P310 Immediately call a POISON CENTER or doctor/physician.
 P330 Rinse mouth.
 P331 Do NOT induce vomiting.
 P332+P313 If skin irritation occurs: Get medical advice/attention.
 P363 Wash contaminated clothing before reuse.
 P405 Store locked up.

Precautionary statement – Storage
Precautionary statement – Disposal

P501 Dispose of contents/container to an approved waste disposal plant.

3. Composition/information on ingredients

Ingredients	Name	CAS	Proportion
	Benzyl alcohol	100-51-6	30-60 %
	Isophoronediamine	2855-13-2	30-60 %
	m-Xylene à,à'-diamine	1477-55-0	1-10 %
	Salicylic acid	69-72-7	1-10 %
	1-Methoxy-2-propyl acetate	108-65-6	0-1 %
	Nonylphenol	25154-52-3	0-1 %
	Ingredients determined not to be hazardous		Balance

4. First-aid measures

Inhalation	If inhaled, remove affected person from contaminated area. Apply artificial respiration if not breathing. Seek medical attention.
Ingestion	Do not induce vomiting. Wash out mouth thoroughly with water. Seek immediate medical attention.
Skin	Remove all contaminated clothing immediately. Wash gently and thoroughly with water and non-abrasive soap for 15 minutes. Ensure contaminated clothing is washed before re-use or discard. Seek immediate medical attention.
Eye contact	If in eyes, hold eyelids apart and flush the eyes continuously with running water. Remove contact lenses. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Seek immediate medical attention.
First Aid Facilities	Eyewash, safety shower and normal washroom facilities.
Advice to Doctor	Treat symptomatically.
Other Information	For advice in an emergency, contact a Poisons Information Centre (Phone Australia 13 1126) or a doctor at once.

5. Fire-fighting measures

Infosafe No™ LPT68	Issue Date : July 2013	ISSUED by PARCHEMC
--------------------	------------------------	--------------------

Product Name : **DURAFLOOR SLX HARDENER**

Classified as hazardous

Suitable extinguishing media	Carbon dioxide, dry chemical, foam, water fog or water mist.
Unsuitable Extinguishing Media	Do not use water jet.
Hazards from Combustion Products	Under fire conditions this product may emit toxic and/or irritating fumes, smoke and gases including carbon monoxide, carbon dioxide, oxides of nitrogen and ammonia.
Specific hazards arising from the chemical	Combustible liquid. This product will burn if exposed to fire.
Hazchem Code	2X
Decomposition Temp.	>200°C
Precautions in connection with Fire	Fire fighters should wear Self-Contained Breathing Apparatus (SCBA) operated in positive pressure mode and full protective clothing to prevent exposure to vapours or fumes. Water spray may be used to cool down heat-exposed containers. Fight fire from safe location. This product should be prevented from entering drains and watercourses.

6. Accidental release measures

Emergency Procedures	Wear appropriate personal protective equipment and clothing to prevent exposure. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unprotected personnel. If possible contain the spill. Place inert absorbent, non-combustible material onto spillage. Use clean non-sparking tools to collect the material and place into suitable labelled containers for subsequent recycling or disposal. Dispose of waste according to the applicable local and national regulations. If contamination of sewers or waterways occurs inform the local water and waste management authorities in accordance with local regulations.
-----------------------------	--

7. Handling and storage

Precautions for Safe Handling	Corrosive and combustible liquid. Attacks skin and eyes. May produce severe burns. Wear suitable protective clothing, gloves and eye/face protection when mixing and using. Use in designated areas with adequate ventilation. Avoid breathing in vapours, mist or fumes. Keep containers closed when not in use. Ensure a high level of personal hygiene is maintained when using this product, that is, always wash hands after handling, and before eating, drinking, smoking or using the toilet facilities. Do not use near ignition sources. Do not pressurise, cut, heat or weld containers as they may contain hazardous. Prevent the build up of mists or vapours in the work atmosphere. Keep containers sealed when not in use.
Conditions for safe storage, including any incompatibilities	Corrosive and combustible liquid for storage and handling purposes. Keep tightly closed in a dry, cool, well-ventilated area, out of direct sunlight. Provide a catch-tank in a bunded area. Avoid sparks, flames and other ignition sources. Store away from incompatible materials. Do NOT pressurise, cut, heat or weld containers as they may contain hazardous residues. Keep containers closed when not in use and securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Have appropriate fire extinguishers available in and near the storage area. Take precautions against static electricity discharges. Use proper grounding procedures. For information on the design of the store-room reference should be made to Australian Standard AS1940 - The storage and handling of flammable and combustible liquids and AS 3780-2008 The storage and handling of corrosive substances. Reference should also be made to all Local, State and Federal regulations.

8. Exposure controls/personal protection

Occupational exposure limit values	No exposure value assigned for this material by Safe Work, Australia. However, the available exposure limits for ingredients are listed below:
---	--

Safe Work, Australia Exposure Standards:

Substance	TWA	STEL	NOTICES
	ppm	mg/m ³	
		ppm	mg/m ³

Infosafe No™ LPT68	Issue Date : July 2013	ISSUED by PARCHEMC
--------------------	------------------------	--------------------

Product Name : **DURAFLOOR SLX HARDENER**

Classified as hazardous

1-Methoxy-2-propyl acetate	50	274	100	548	-
m-Xylene à,à'-diamine	-	0.1	-	-	Peak Limitation

TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eight-hour working day, for a five-day week.

STEL (Short Term Exposure Limit): The average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.

Peak Limitation: A ceiling concentration which should not be exceeded over a measurement period which should be as short as possible but not exceeding 15 minutes.

Biological Limit Values No biological limit allocated.

Appropriate engineering controls Provide sufficient ventilation to keep airborne levels below the exposure limits. Where vapours or mists are generated, particularly in enclosed areas, and natural ventilation is inadequate, a local exhaust ventilation system is required.

Respiratory Protection If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable organic vapour filter should be used. Reference should be made to Australian/New Zealand Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.

Eye Protection Safety glasses with side shields, goggles or full-face shield as appropriate should be used. Final choice of appropriate eye/face protection will vary according to individual circumstances i.e. methods of handling or engineering controls and according to risk assessments undertaken. Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors for Industrial Applications.

Hand Protection Wear gloves of impervious material e.g. Laminated film, nitrile or neoprene. Final choice of appropriate gloves will vary according to individual circumstances i.e. methods of handling or according to risk assessments undertaken. Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.

Footwear Wear safety footwear. Final choice will vary according to individual circumstances. Reference should be made to AS/NZS 2210.1: 2010 Safety, protective and occupational footwear-Guide to selection, care and use.

Body Protection Suitable protective work wear, e.g. cotton overalls buttoned at neck and wrist is recommended. Chemical resistant apron is recommended where large quantities are handled.

9. Physical and chemical properties

Appearance	Liquid
Colour	Milky
Odour	Characteristic amine odour.
Decomposition Temperature	>200°C
Melting Point	<10°C
Boiling Point	247°C
Solubility in Water	Insoluble
Specific Gravity	1.02
pH	Not available
Vapour Pressure	0.15 mmHg (for Benzyl alcohol)
Vapour Density (Air=1)	Not available
Evaporation Rate	Not available

Infosafe No™ LPT68	Issue Date : July 2013	ISSUED by PARCHEMC
--------------------	------------------------	--------------------

Product Name : **DURAFLOOR SLX HARDENER**

Classified as hazardous

Odour Threshold	Not available
Viscosity	Not available
Partition Coefficient: n-octanol/water	Not available
Flash Point	>100°C (Pensky Martens Closed Cup)
Flammability	Combustible liquid
Auto-Ignition Temperature	Not available
Flammable Limits - Lower	Not available
Flammable Limits - Upper	Not available

10. Stability and reactivity

Reactivity	Reacts with incompatibles
Chemical Stability	Stable under normal conditions of storage and handling.
Conditions to Avoid	Heat, flames and other sources of ignition.
Incompatible Materials	Strong oxidizing agents, strong acids and strong bases.
Hazardous Decomposition Products	Thermal decomposition may result in the release of toxic and/or irritating fumes and gases including carbon monoxide, carbon dioxide, oxides of nitrogen and ammonia.
Hazardous Polymerization	Will not occur.

11. Toxicological Information

Toxicology Information	No toxicity data available for this material. The available acute toxicity data for the ingredients is given below:
Acute Toxicity - Oral	Isophoronediamine: LD50 (Rat): >1,030 mg/kg
Ingestion	Harmful if swallowed. Ingestion of this product will cause nausea, vomiting, abdominal pain and chemical burns to the mouth, throat and stomach.
Inhalation	Harmful if inhaled. Inhalation of mist or vapour will result in respiratory irritation and possible harmful corrosive effects including burns, lesions of the nasal septum, pulmonary edema, and scarring of tissue.
Skin	May be harmful in contact with skin. Causes burns. Corrosive to the skin. Skin contact can cause redness, itching, irritation, severe pain and chemical burns with resultant tissue destruction. May cause an allergic skin reaction
Eye	Causes eye damage. Eye contact will cause stinging, blurring, tearing, severe pain and possible burns, necrosis, permanent damage and blindness.
Respiratory sensitisation	Not expected to be a respiratory sensitiser.
Skin Sensitisation	May cause an allergic skin reaction
Germ cell mutagenicity	Not considered to be a mutagenic hazard.
Carcinogenicity	Not considered to be a carcinogenic hazard.
Reproductive Toxicity	Not considered to be toxic to reproduction.
STOT-single exposure	Not expected to cause toxicity to a specific target organ.
STOT-repeated exposure	Not expected to cause toxicity to a specific target organ.
Aspiration Hazard	Not expected to be an aspiration hazard.
Skin corrosion/irritation	Isophoronediamine: Testing demonstrated that isophorone diamine is a strong skin sensitiser (15

Infosafe No™ LPT68 Issue Date : July 2013 ISSUED by PARCHEMC

Product Name : DURAFLOOR SLX HARDENER

Classified as hazardous

out of 15 test rabbit were sensitised).

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Persistence and degradability Not available

Mobility Not available

Bioaccumulative Potential Not available

Other Adverse Effects Not available

Environmental Protection Do not discharge this material into waterways, drains and sewers.

13. Disposal considerations

Disposal Considerations Do not allow into drains or watercourses or dispose of where ground or surface waters may be affected. Wastes including emptied containers are controlled wastes and should be disposed of in accordance with all applicable national and local regulations.

14. Transport information

Transport Information Road and Rail Transport (ADG Code):
This material is classified as Dangerous Goods Class 8 Corrosive Substances according to the Australian Code for the Transport of Dangerous Goods by Road and Rail (7th edition).
Class 8 Dangerous Goods are incompatible in a placard load with any of the following:
- Class 1, Explosives
- Division 4.3, Dangerous When Wet Substances
- Division 5.1, Oxidising substances
- Division 5.2, Organic Peroxides
- Class 6, Toxic or Infectious Substances, if the Class 6 dangerous goods are cyanides and the Class 8 dangerous goods are acids
- Class 7, Radioactive Substances
and are incompatible with food and food packaging in any quantity.
Strong acids must not be loaded in the same freight container or on the same vehicle with strong alkalis. Packing Group I and II acids and alkalis should be considered as strong.

Marine Transport (IMO/IMDG):
Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.
UN No.: 2735
Proper Shipping Name: AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS ISOPHORONEDIAMINE)
Class: 8
Packaging Group: III
EMS No.: F-A, S-B
Special Provision(s): 223 274

Air Transport (ICAO/IATA):
Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.
UN No.: 2735
Proper Shipping Name: AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS ISOPHORONEDIAMINE)
Class: 8
Packaging Group: III
Label: Corrosive
Packaging Instructions (passenger & cargo): 852
Packaging Instructions (cargo only): 856
Special Provision(s): A3 A803

Infosafe No™ LPT68 Issue Date : July 2013 ISSUED by PARCHEMC

Product Name : DURAFLOOR SLX HARDENER

Classified as hazardous

U.N. Number	2735
UN proper shipping name	AMINES, LIQUID, CORROSIVE, N.O.S. - (CONTAINS ISOPHORONEDIAMINE)
Transport hazard class(es)	8
Hazchem Code	2X
Packing Group	III
EPG Number	8A1
IERG Number	36

15. Regulatory information

Regulatory Information	Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia
Poisons Schedule	Classified as a Scheduled Poison according to the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP). S5
AICS (Australia)	The listed chemicals are included in Australian Inventory of Chemical Substances (AICS) or otherwise notified under NICNAS.

16. Other Information

Date of preparation or last revision of SDS	SDS Reviewed: July 2013 Supersedes: June 2009
Literature References	-Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice. -Standard for the Uniform Scheduling of Medicines and Poisons. -Australian Code for the Transport of Dangerous Goods by Road & Rail. -Model Work Health and Safety Regulations, Schedule 10: Prohibited carcinogens, restricted carcinogens and restricted hazardous chemicals. -Workplace exposure standards for airborne contaminants, Safe work Australia. -American Conference of Industrial Hygienists (ACGIH). -Globally Harmonised System of classification and labelling of chemicals.
Contact Person/Point	Technical Support: 1800 812 864 ...End Of MSDS...

© Copyright ACOHS Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe MSDS displayed is the intellectual property of Acohs Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe MSDS displayed is the intellectual property of Acohs Pty Ltd. The compilation of MSDS's displayed is the intellectual property of Acohs Pty Ltd.

Copying of any MSDS displayed is permitted for personal use only and otherwise is not permitted. In particular the MSDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of MSDS without the express written consent of Acohs Pty Ltd.