

Infosafe No™ LPT67	Issue Date : September 2013	ISSUED by PARCHEMC
--------------------	-----------------------------	--------------------

Product Name : **DURAFLOOR TF HARDENER**

Classified as hazardous

## 1. Identification

<b>GHS Product Identifier</b>	DURAFLOOR TF HARDENER
<b>Company Name</b>	Parchem Construction Supplies Pty Ltd (ABN 80 069 961 968)
<b>Address</b>	7 Lucca Road Wyong NSW 2259 Australia
<b>Telephone/Fax Number</b>	Tel: 02 4350 5000 Fax: 02 4351 2024
<b>Emergency phone number</b>	1800 638 556 (available 24/7)
<b>Recommended use of the chemical and restrictions on use</b>	Hardener component of epoxy flooring system.
<b>Other Information</b>	<p>This SDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since Parchem Construction Supplies Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this MSDS in the context of how the user intends to handle and use the product in the workplace.</p> <p>If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company. Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.</p> <p>www.parchem.com.au</p>

## 2. Hazard Identification

<b>Classification of the substance or mixture</b>	<p>Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia.</p> <p>Classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)</p>
<b>Signal Word (s)</b>	<p>Acute Toxicity - Dermal: Category 4          Acute Toxicity - Oral: Category 4          Acute Toxicity - Inhalation: Category 5          Eye Damage/Irritation: Category 1          Skin Corrosion/Irritation: Category 1A          Sensitization - Skin: Category 1          Hazardous to the Aquatic Environment - Long-Term Hazard: Category 3          Danger</p>
<b>Hazard Statement (s)</b>	<p>H302 Harmful if swallowed.          H312 Harmful in contact with skin.          H314 Causes severe skin burns and eye damage.          H317 May cause an allergic skin reaction.          H333 May be harmful if inhaled.          H402 Harmful to aquatic life.</p>
<b>General Precautionary Statement (s)</b>	<p>P101 If medical advice is needed, have product container or label at hand.          P102 Keep out of reach of children.          P103 Read label before use.</p>
<b>Pictogram (s)</b>	<p>Corrosion, Exclamation mark</p>



Infosafe No™ LPT67	Issue Date : September 2013	ISSUED by PARCHEMC
--------------------	-----------------------------	--------------------

Product Name : **DURAFLOOR TF HARDENER**

Classified as hazardous

<b>Precautionary statement – Prevention</b>	<p>P260 Do not breathe fume/mist/vapours.  P264 Wash contaminated skin thoroughly after handling.  P270 Do not eat, drink or smoke when using this product.  P272 Contaminated work clothing should not be allowed out of the workplace.  P273 Avoid release to the environment.  P280 Wear protective gloves/protective clothing/eye protection/face protection.</p>
<b>Precautionary statement – Response</b>	<p>P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.  P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  P310 Immediately call a POISON CENTER or doctor/physician.  P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  P363 Wash contaminated clothing before reuse.  P405 Store locked up.</p>
<b>Precautionary statement – Storage</b>	
<b>Precautionary statement – Disposal</b>	<p>P501 Dispose of contents/container to an approved waste disposal plant.</p>

### 3. Composition/information on ingredients

Ingredients	Name	CAS	Proportion
	Isophoronediamine	2855-13-2	30-70 %
	Benzyl alcohol	100-51-6	10-30 %
	Ethanol	64-17-5	0-10 %
	Calcium nitrate	10124-37-5	0-10 %
	Ingredients determined not to be hazardous		Balance

### 4. First-aid measures

<b>Inhalation</b>	If inhaled, remove affected person from contaminated area. Apply artificial respiration if not breathing. Seek medical attention.
<b>Ingestion</b>	Do not induce vomiting. Wash out mouth thoroughly with water. Seek immediate medical attention.
<b>Skin</b>	Remove all contaminated clothing immediately. Wash gently and thoroughly with water and non-abrasive soap for 15 minutes. Ensure contaminated clothing is washed before re-use or discard. Seek immediate medical attention.
<b>Eye contact</b>	If in eyes, hold eyelids apart and flush the eyes continuously with running water. Remove contact lenses. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Seek immediate medical attention.
<b>First Aid Facilities</b>	Eyewash, safety shower and normal washroom facilities.
<b>Advice to Doctor</b>	Treat symptomatically.
<b>Other Information</b>	For advice in an emergency, contact a Poisons Information Centre (Phone Australia 13 1126) or a doctor at once.

### 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Carbon dioxide, dry chemical, foam, water fog or water mist.
<b>Unsuitable Extinguishing Media</b>	Do not use water jet.
<b>Hazards from Combustion Products</b>	Under fire conditions this product may emit toxic and/or irritating fumes, smoke and gases including carbon monoxide, carbon dioxide, oxides of nitrogen and ammonia.
<b>Specific hazards arising from the chemical</b>	Combustible liquid. This product will burn if exposed to fire.
<b>Hazchem Code</b>	2X
<b>Decomposition Temp.</b>	Not available

Infosafe No™ LPT67	Issue Date : September 2013	ISSUED by PARCHEMC
--------------------	-----------------------------	--------------------

Product Name : **DURAFLOOR TF HARDENER**

Classified as hazardous

**Precautions in connection with Fire** Fire fighters should wear Self-Contained Breathing Apparatus (SCBA) operated in positive pressure mode and full protective clothing to prevent exposure to vapours or fumes. Water spray may be used to cool down heat-exposed containers. Fight fire from safe location. This product should be prevented from entering drains and watercourses.

## 6. Accidental release measures

**Personal precautions, protective equipment and emergency procedures** Wear appropriate personal protective equipment and clothing to prevent exposure. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unprotected personnel. If possible contain the spill. Place inert absorbent, non-combustible material onto spillage. Use clean non-sparking tools to collect the material and place into suitable labelled containers for subsequent recycling or disposal. Dispose of waste according to the applicable local and national regulations. If contamination of sewers or waterways occurs inform the local water and waste management authorities in accordance with local regulations.

## 7. Handling and storage

**Precautions for Safe Handling** Corrosive and combustible liquid. Attacks skin and eyes. May produce severe burns. Wear suitable protective clothing, gloves and eye/face protection when mixing and using. Use in designated areas with adequate ventilation. Avoid breathing in vapours, mist or fumes. Keep containers closed when not in use. Ensure a high level of personal hygiene is maintained when using this product, that is, always wash hands after handling, and before eating, drinking, smoking or using the toilet facilities. Do not use near ignition sources. Do not pressurise, cut, heat or weld containers as they may contain hazardous. Prevent the build up of mists or vapours in the work atmosphere. Keep containers sealed when not in use.

**Conditions for safe storage, including any incompatibilities** Corrosive and combustible liquid for storage and handling purposes. Keep tightly closed in a dry, cool, well-ventilated area, out of direct sunlight. Provide a catch-tank in a bunded area. Avoid sparks, flames and other ignition sources. Store away from incompatible materials. Do NOT pressurise, cut, heat or weld containers as they may contain hazardous residues. Keep containers closed when not in use and securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Have appropriate fire extinguishers available in and near the storage area. Take precautions against static electricity discharges. Use proper grounding procedures. For information on the design of the store-room reference should be made to Australian Standard AS1940 - The storage and handling of flammable and combustible liquids and AS 3780-2008 The storage and handling of corrosive substances. Reference should also be made to all Local, State and Federal regulations.

**Corrosiveness** Not corrosive to aluminium

**Storage Regulations** Classified as a Class C1 (COMBUSTIBLE LIQUID) for the purpose of storage and handling, in accordance with the requirements of AS1940.

## 8. Exposure controls/personal protection

**Occupational exposure limit values** No exposure value assigned for this material by Safe Work, Australia. However, the available exposure limits for ingredients are listed below:

Safe Work, Australia Exposure Standards:

Substance	TWA		STEL	
	ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
Ethanol	1000	1880	-	-

TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eight-hour working day, for a five-day week.

STEL (Short Term Exposure Limit): The average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.

**Biological Limit Values** No biological limit allocated.

Infosafe No™ LPT67

Issue Date : September 2013

ISSUED by PARCHEMC

Product Name : **DURAFLOOR TF HARDENER**

Classified as hazardous

<b>Appropriate engineering controls</b>	This substance is hazardous and should be used with a local exhaust ventilation system, drawing vapours away from workers' breathing zone. A flame-proof exhaust ventilation system is required. If the engineering controls are not sufficient to maintain concentrations of vapours/mists below the exposure standards, suitable respiratory protection must be worn. Refer to AS 1940 - The storage and handling of flammable and combustible liquids and AS/NZS 60079.10.1:2009 Explosive atmospheres - Classification of areas - Explosive gas atmospheres, for further information concerning ventilation requirements.
<b>Respiratory Protection</b>	If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable organic vapour filter should be used. Reference should be made to Australian/New Zealand Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.
<b>Eye Protection</b>	Safety glasses with side shields, goggles or full-face shield as appropriate should be used. Final choice of appropriate eye/face protection will vary according to individual circumstances i.e. methods of handling or engineering controls and according to risk assessments undertaken. Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors for Industrial Applications.
<b>Hand Protection</b>	Wear gloves of impervious material. Final choice of appropriate gloves will vary according to individual circumstances i.e. methods of handling or according to risk assessments undertaken. Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.
<b>Footwear</b>	Wear safety footwear. Final choice will vary according to individual circumstances. Reference should be made to AS/NZS 2210.1: 2010 Safety, protective and occupational footwear-Guide to selection, care and use.
<b>Body Protection</b>	Suitable protective work wear, e.g. cotton overalls buttoned at neck and wrist is recommended. Chemical resistant apron is recommended where large quantities are handled.

## 9. Physical and chemical properties

<b>Appearance</b>	Low viscosity liquid.
<b>Odour</b>	Characteristic amine odour.
<b>Decomposition Temperature</b>	Not available
<b>Melting Point</b>	<10°C
<b>Boiling Point</b>	>200°C
<b>Solubility in Water</b>	Insoluble
<b>Specific Gravity</b>	1.00 (at 23°C)
<b>pH</b>	Not available
<b>Vapour Pressure</b>	0.15 mmHg (for Benzyl alcohol)
<b>Vapour Density (Air=1)</b>	Not available
<b>Evaporation Rate</b>	Not available
<b>Odour Threshold</b>	Not available
<b>Viscosity</b>	Not available
<b>Partition Coefficient: n-octanol/water</b>	Not available
<b>Flash Point</b>	>100°C
<b>Flammability</b>	Not flammable
<b>Auto-Ignition Temperature</b>	Not available
<b>Flammable Limits - Lower</b>	Not available

Infosafe No™ LPT67	Issue Date : September 2013	ISSUED by PARCHEMC
--------------------	-----------------------------	--------------------

Product Name : **DURAFLOOR TF HARDENER**

Classified as hazardous

**Flammable Limits - Upper** Not available

## 10. Stability and reactivity

<b>Reactivity</b>	Reacts with incompatibles
<b>Chemical Stability</b>	Stable under normal conditions of storage and handling.
<b>Conditions to Avoid</b>	Heat, flames and other sources of ignition.
<b>Incompatible Materials</b>	Strong oxidizing agents, strong acids and strong bases.
<b>Hazardous Decomposition Products</b>	Thermal decomposition may result in the release of toxic and/or irritating fumes and gases including carbon monoxide, carbon dioxide, oxides of nitrogen and ammonia.
<b>Hazardous Polymerization</b>	Will not occur.

## 11. Toxicological Information

<b>Toxicology Information</b>	No toxicity data available for this material. The available acute toxicity data for the ingredients is given below:
<b>Acute Toxicity - Oral</b>	Benzyl alcohol: LD50 (rat): 1,230 mg/kg
<b>Acute Toxicity - Dermal Ingestion</b>	Benzyl alcohol: LD50 (rabbit): 2000mg/kg
<b>Inhalation</b>	Harmful if swallowed. Ingestion of this product will cause nausea, vomiting, abdominal pain and chemical burns to the mouth, throat and stomach. Inhalation of mist or vapour will result in respiratory irritation and possible harmful corrosive effects including burns, lesions of the nasal septum, pulmonary edema, and scarring of tissue. May be harmful if inhaled.
<b>Skin</b>	Harmful in contact with skin. Causes burns. Corrosive to the skin. Skin contact can cause redness, itching, irritation, severe pain and chemical burns with resultant tissue destruction. May cause an allergic skin reaction. Benzyl alcohol:- Standard Draize Test: 100mg/24h moderate reaction
<b>Eye</b>	Causes eye damage. Eye contact will cause stinging, blurring, tearing, severe pain and possible burns, necrosis, permanent damage and blindness.
<b>Respiratory sensitisation</b>	Not expected to be a respiratory sensitiser.
<b>Skin Sensitisation</b>	May cause an allergic skin reaction
<b>Germ cell mutagenicity</b>	Not considered to be a mutagenic hazard.
<b>Carcinogenicity</b>	Not considered to be a carcinogenic hazard.
<b>Reproductive Toxicity</b>	Not considered to be toxic to reproduction.
<b>STOT-single exposure</b>	Not expected to cause toxicity to a specific target organ.
<b>STOT-repeated exposure</b>	Not expected to cause toxicity to a specific target organ.
<b>Aspiration Hazard</b>	Not expected to be an aspiration hazard.

## 12. Ecological information

<b>Ecotoxicity</b>	Harmful to aquatic life with long lasting effects.
<b>Persistence and degradability</b>	Not available
<b>Mobility</b>	Not available
<b>Bioaccumulative Potential</b>	Not available

Infosafe No™ LPT67	Issue Date : September 2013	ISSUED by PARCHEMC
--------------------	-----------------------------	--------------------

Product Name : **DURAFLOOR TF HARDENER**

Classified as hazardous

**Other Adverse Effects** Not available

**Environmental Protection** Do not discharge this material into waterways, drains and sewers.

### 13. Disposal considerations

**Disposal Considerations** Do not allow into drains or watercourses or dispose of where ground or surface waters may be affected. Wastes including emptied containers are controlled wastes and should be disposed of in accordance with all applicable national and local regulations.

### 14. Transport information

**Transport Information** Road and Rail Transport (ADG Code):  
This material is classified as Dangerous Goods Class 8 Corrosive Substances according to the Australian Code for the Transport of Dangerous Goods by Road and Rail (7th edition).  
Class 8 Dangerous Goods are incompatible in a placard load with any of the following:  
- Class 1, Explosives  
- Division 4.3, Dangerous When Wet Substances  
- Division 5.1, Oxidising substances  
- Division 5.2, Organic Peroxides  
- Class 6, Toxic or Infectious Substances, if the Class 6 dangerous goods are cyanides and the Class 8 dangerous goods are acids  
- Class 7, Radioactive Substances  
and are incompatible with food and food packaging in any quantity.  
Strong acids must not be loaded in the same freight container or on the same vehicle with strong alkalis. Packing Group I and II acids and alkalis should be considered as strong.

Marine Transport (IMO/IMDG):  
Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.  
UN No.: 2735  
Proper Shipping Name: AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS ISOPHORONEDIAMINE)  
Class: 8  
Packaging Group: III  
EMS No.: F-A, S-B  
Special Provision(s): 223 274

Air Transport (ICAO/IATA):  
Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.  
UN No.: 2735  
Proper Shipping Name: AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS ISOPHORONEDIAMINE)  
Class: 8  
Packaging Group: III  
Label: Corrosive  
Packaging Instructions (passenger & cargo): 852  
Packaging Instructions (cargo only): 856  
Special Provision(s): A3 A803  
2735

**U.N. Number**

**UN proper shipping name** AMINES, LIQUID, CORROSIVE, N.O.S. - (CONTAINS ISOPHORONEDIAMINE)

**Transport hazard class(es)** 8

**Hazchem Code** 2X

**Packing Group** III

**EPG Number** 8A1

Infosafe No™ LPT67	Issue Date : September 2013	ISSUED by PARCHEMC
--------------------	-----------------------------	--------------------

Product Name : **DURAFLOOR TF HARDENER**

Classified as hazardous

**IERG Number** 36**IMDG Marine pollutant** No**15. Regulatory information****Regulatory Information** Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia

Classified as a Scheduled Poison according to the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

**Poisons Schedule** S5**AICS (Australia)** All components of this product are listed on the Australian Inventory of Chemical Substances (AICS) or exempted.**16. Other Information****Date of preparation or last revision of SDS** SDS Reviewed: September 2013  
Supersedes: June 2009**Literature References** Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice.  
Standard for the Uniform Scheduling of Medicines and Poisons.  
Australian Code for the Transport of Dangerous Goods by Road & Rail.  
Model Work Health and Safety Regulations, Schedule 10: Prohibited carcinogens, restricted carcinogens and restricted hazardous chemicals.  
Workplace exposure standards for airborne contaminants, Safe work Australia.  
American Conference of Industrial Hygienists (ACGIH).  
Globally Harmonised System of classification and labelling of chemicals.**Contact Person/Point** Technical Support: 1800 812 864

...End Of MSDS...

© Copyright ACOHS Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe MSDS displayed is the intellectual property of Acohs Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe MSDS displayed is the intellectual property of Acohs Pty Ltd.  
The compilation of MSDS's displayed is the intellectual property of Acohs Pty Ltd.

Copying of any MSDS displayed is permitted for personal use only and otherwise is not permitted. In particular the MSDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of MSDS without the express written consent of Acohs Pty Ltd.