

Infosafe No™ LPXB4	Issue Date : March 2013	ISSUED by PARCHEMN
--------------------	-------------------------	--------------------

Product Name : **DURAFLOOR V ANTI-SKID HARDENER**

Classified as hazardous

1. Identification

GHS Product Identifier	DURAFLOOR V ANTI-SKID HARDENER
Company Name	Parchem Construction Supplies Pty Ltd (ABN 80 069 961 968)
Address	7 Lucca Road Wyong NSW 2259 Australia
Telephone/Fax Number	Tel: 02 4350 5000 Fax: 02 4351 2024
Emergency phone number	0800 154 666 (available 24/7)
Recommended use of the chemical and restrictions on use	Hardener component for heavy-duty, flow applied anti-skid surface dressing.
Other Information	Distributed in New Zealand by: Concrete Plus 23 Watts Road Sockburn New Zealand Tel: (03) 343 0090 Fax: (03) 343 0202

This SDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since Parchem Construction Supplies Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this MSDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company. Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.

www.parchem.co.nz

2. Hazard Identification

GHS classification of the substance/mixture	Classified as Hazardous according to the Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001, New Zealand. Classified as Dangerous Goods for transport according to the New Zealand Standard NZS 5433:2012 Transport of Dangerous Goods on Land. HSNO Classification: 6.1D - Substance that is acutely toxic (Dermal) 6.1D - Substance that is acutely toxic (Oral) 6.5B - Substance that is a contact sensitiser 6.8B - Substance that is suspected to be a human reproductive or developmental toxicant 8.2C - Substance that is corrosive to dermal tissue 8.3A - Substance that is corrosive to ocular tissue 9.1C - Substance that is harmful in the aquatic environment 9.3C - Substance that is harmful to terrestrial vertebrates
Signal Word (s)	Danger
Hazard Statement (s)	H302 Harmful if swallowed. H312 Harmful in contact with skin. H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction. H361 Suspected of damaging fertility or the unborn child. H412 Harmful to aquatic life with long lasting effects. H433 Harmful to terrestrial vertebrates.
Pictogram (s)	Corrosion, Exclamation mark, Health hazard

Infosafe No™ LPXB4 Issue Date : March 2013 ISSUED by PARCHEMN

Product Name : DURAFLOOR V ANTI-SKID HARDENER

Classified as hazardous



Precautionary statement – Prevention

P102 Keep out of reach of children.
 P103 Read label before use.
 P201 Obtain special instructions before use.
 P202 Do not handle until all safety precautions have been read and understood.
 P260 Do not breathe dust/fume/gas/mist/vapours/spray.
 P264 Wash skin thoroughly after handling.
 P270 Do not eat, drink or smoke when using this product.
 P272 Contaminated work clothing should not be allowed out of the workplace.
 P273 Avoid release to the environment. -This statement does not apply where this is the intended use.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statement – Response

GENERAL:
 P101 If medical advice is needed, have product container or label at hand. -This statement applies only where the substance is available to the general public.
 P310 Immediately call a POISON CENTER or doctor/physician.
 INGESTION:
 P301+P312 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
 P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting
 INHALATION:
 P304+P340 IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
 EYES:
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 SKIN:
 P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
 P363 Wash contaminated clothing before reuse.
 P405 Store locked up.

Precautionary statement – Storage
Precautionary statement – Disposal

P501 In the case of a substance that is in compliance with a HSN0 approval other than a Part 6A (Group Standards) approval, a label must provide a description of one or more appropriate and achievable methods for the disposal of a substance in accordance with the Hazardous Substances (Disposal) Regulations 2001. This may also include any method of disposal that must be avoided. See Section 13 for disposal details.

3. Composition/information on ingredients

Ingredients	Name	CAS	Proportion
	Isophorone diamine	2855-13-2	20-<60 %
	Anthracene oil	90640-80-5	30-<60 %
	Polyoxypropylene diamine	9046-10-0	0-<20 %
	Trimethylhexamethylenediamine	25620-58-0	0-<10 %
	Ingredients determined not to be hazardous.		Balance

4. First-aid measures

Inhalation

If inhaled, remove affected person from contaminated area. Apply artificial respiration if not breathing. Seek medical attention.

Ingestion

Do not induce vomiting. Wash out mouth thoroughly with water. Seek immediate medical attention.

Infosafe No™ LPXB4

Issue Date : March 2013

ISSUED by PARCHEMN

Product Name : **DURAFLOOR V ANTI-SKID HARDENER**

Classified as hazardous

Skin	If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Ensure contaminated clothing is washed before re-use or discard. Seek immediate medical attention.
Eye contact	If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Seek immediate medical attention.
First Aid Facilities	Eye wash, safety shower and normal washroom facilities.
Advice to Doctor	Treat symptomatically.
Other Information	For advice, contact a Poisons Information Centre (Phone eg Australia 131 126; New Zealand 0800 764 766) or a doctor (at once).

5. Fire-fighting measures

Suitable extinguishing media	Use carbon dioxide, dry chemical, foam or water mist.
Hazards from Combustion Products	Under fire conditions this product may emit toxic and/or irritating fumes and gases including carbon monoxide, carbon dioxide, oxides of nitrogen and ammonia gas.
Specific hazards arising from the chemical	Combustible liquid. This product will burn if exposed to fire.
Hazchem Code	2X
Decomposition Temp.	>200°C
Precautions in connection with Fire	Fire-fighters should wear full protective clothing and self contained breathing apparatus (SCBA) operated in positive pressure mode. Water spray may be used to keep fire exposed containers cool.

6. Accidental release measures

Emergency Procedures	Wear appropriate personal protective equipment and clothing to prevent exposure. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unprotected personnel. If possible contain the spill. Place inert absorbent, non-combustible material onto spillage. Use clean non-sparking tools to collect the material and place into suitable labelled containers for subsequent recycling or disposal. Dispose of waste according to the applicable local and national regulations. If contamination of sewers or waterways occurs inform the local water and waste management authorities in accordance with local regulations.
-----------------------------	--

7. Handling and storage

Precautions for Safe Handling	Corrosive and combustible liquid. Attacks skin and eyes. May produce severe burns. Wear suitable protective clothing, gloves and eye/face protection when mixing and using. Use in designated areas with adequate ventilation. Avoid breathing in vapours, mist or fumes. Keep containers closed when not in use. Ensure a high level of personal hygiene is maintained when using this product, that is, always wash hands after handling, and before eating, drinking, smoking or using the toilet facilities. Do not use near ignition sources. Do not pressurise, cut, heat or weld containers as they may contain hazardous. Prevent the build up of mists or vapours in the work atmosphere. Keep containers sealed when not in use.
Conditions for safe storage, including any incompatibilities	Corrosive and combustible liquid for storage and handling purposes. Keep tightly closed in a dry, cool, well-ventilated area, out of direct sunlight. Provide a catch-tank in a bunded area. Avoid sparks, flames and other ignition sources. Store away from incompatible materials. Do NOT pressurise, cut, heat or weld containers as they may contain hazardous residues. Keep containers closed when not in use and securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Have appropriate fire extinguishers available in and near the storage area. Take precautions against static electricity discharges. Use proper grounding procedures. For information on the design of the store-room reference should be made to Australian Standard AS1940 - The storage and handling of flammable and combustible liquids and AS 3780-2008 The storage and handling of corrosive

Infosafe No™ LPXB4	Issue Date : March 2013	ISSUED by PARCHEMN
--------------------	-------------------------	--------------------

Product Name : **DURAFLOOR V ANTI-SKID HARDENER**

Classified as hazardous

substances. Reference should also be made to all Local, State and Federal regulations.

8. Exposure controls/personal protection

Occupational exposure limit values	No exposure standards have been established for this material by the Occupational Safety and Health Service (OSH) of the New Zealand Department of Labour. However, over-exposure to some chemicals may result in enhancement of pre-existing adverse medical conditions and/or allergic reactions and should be kept to the least possible levels.
Biological Limit Values	No biological limit allocated.
Appropriate engineering controls	Provide sufficient ventilation to keep airborne levels below the exposure limits. Where vapours or mists are generated, particularly in enclosed areas, and natural ventilation is inadequate, a local exhaust ventilation system is required.
Respiratory Protection	If engineering controls are not effective in controlling airborne exposure then respiratory protective equipment should be used suitable for protecting against airborne contaminants. Final choice of appropriate breathing protection is dependent upon actual airborne concentrations and the type of breathing protection required will vary according to individual circumstances. Expert advice may be required to make this decision. Reference should be made to Australian Standards AS/NZS 1715, Selection, Use and maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices.
Eye Protection	Safety glasses with side shields, goggles or full-face shield as appropriate recommended. Final choice of appropriate eye/face protection will vary according to individual circumstances i.e. methods of handling or engineering controls and according to risk assessments undertaken. Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors for Industrial Applications.
Hand Protection	Wear gloves of impervious material, such as laminated film. Final choice of appropriate gloves will vary according to individual circumstances i.e. methods of handling or according to risk assessments undertaken. Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.
Body Protection	Suitable workwear should be worn to protect personal clothing, eg cotton overalls buttoned at neck and wrist. When large quantities are handled the use of plastic aprons and rubber boots is recommended.

9. Physical and chemical properties

Appearance	Dark coloured liquid
Odour	Amine odour
Decomposition Temperature	>200°C
Melting Point	10°C (Isophorone diamine)
Boiling Point	>200°C
Solubility in Water	Negligible
Specific Gravity	1.02 (23°C)
pH	Not available
Vapour Pressure	0.15 mmHg (Isophorone diamine)
Vapour Density (Air=1)	Not available
Evaporation Rate	Not available
Odour Threshold	Not available
Viscosity	Not available
Partition Coefficient: n-octanol/water	Not available

Infosafe No™ LPXB4	Issue Date : March 2013	ISSUED by PARCHEMN
--------------------	-------------------------	--------------------

Product Name : **DURAFLOOR V ANTI-SKID HARDENER**

Classified as hazardous

Flash Point	>110°C
Flammability	Non flammable
Auto-Ignition Temperature	Not available
Flammable Limits - Lower	Not available
Flammable Limits - Upper	Not available

10. Stability and reactivity

Reactivity	Reacts with incompatibles.
Chemical Stability	Stable under normal conditions of storage and handling.
Conditions to Avoid	Heat, flames and other sources of ignition.
Incompatible Materials	Strong oxidising agents, strong acids, halogens and halogenated organic compounds.
Hazardous Decomposition Products	Thermal decomposition may result in the release of toxic and/or irritating fumes and gases including carbon monoxide, carbon dioxide, oxides of nitrogen and ammonia gas.
Hazardous Polymerization	Will not occur.

11. Toxicological Information

Toxicology Information	No toxicity data available for this material.
Ingestion	Harmful if swallowed. Ingestion of this product may cause nausea, vomiting, abdominal pain and chemical burns to the mouth, throat and stomach.
Inhalation	Inhalation of mist or vapour will result in respiratory irritation and possible harmful corrosive effects including burns, lesions of the nasal septum, pulmonary edema, and scarring of tissue.
Skin	Causes severe skin burns. Corrosive to the skin. Skin contact can cause redness, itching, irritation, severe pain and chemical burns with resultant tissue destruction. Skin contact will cause redness, itching, irritation, severe pain and chemical burns with resultant tissue destruction. Harmful in contact with skin. Prolonged or repeated skin contact may cause defatting leading to skin burns and skin sensitisation.
Eye	Causes eye damage. Eye contact will cause stinging, blurring, tearing, severe pain and possible burns, necrosis, permanent damage and blindness.
Respiratory sensitisation	May act as a sensitiser producing asthma-like (by inhalation) in sensitised individuals. Those sensitised may react to concentration levels that do not affect other, non sensitised, people.
Skin Sensitisation	May cause an allergic skin reaction.
Germ cell mutagenicity	Not considered to be a mutagenic hazard.
Carcinogenicity	Not considered to be a carcinogenic hazard.
Reproductive Toxicity	Suspected of damaging fertility or the unborn child. Classified as a suspected human reproductive or developmental toxicant.
STOT-single exposure	Not expected to cause damage to organs.
STOT-repeated exposure	Not expected to cause damage to organs through repeated or prolonged exposure.
Aspiration Hazard	Not expected to be an aspiration hazard.

12. Ecological information

Ecotoxicity	Harmful to aquatic life with long lasting effects. Harmful to terrestrial vertebrates.
Persistence and degradability	Not available

Infosafe No™ LPXB4

Issue Date : March 2013

ISSUED by PARCHEMN

Product Name : **DURAFLOOR V ANTI-SKID HARDENER**

Classified as hazardous

Mobility	Not available
Bioaccumulative Potential	Not available
Environmental Protection	Prevent this material entering waterways, drains and sewers.

13. Disposal considerations

Disposal Considerations	<p>Product Disposal: Product wastes are controlled wastes and should be disposed of in accordance with all applicable local and national regulations. This product can be disposed through a licensed commercial waste collection service. It can be disposed by burning in an approved high temperature incineration facility; or alternatively, it can be reacted with the base component to enable it to cure to an inert solid that can be disposed in a licensed landfill facility. Personal protective clothing and equipment as specified in Section 8 of this SDS must be worn during handling and disposal of this product. The ventilation requirements as specified in the same section must also be followed, and the precautions given in Section 7 of this SDS regarding handling must also be followed.</p> <p>Do not dispose into the sewerage system. Do not discharge into drains or watercourses or dispose where ground or surface waters may be affected. In New Zealand, the disposal agency or contractor must comply with the New Zealand Hazardous Substances (Disposal) Regulations 2001. Further details regarding disposal can be obtained on the ERMA New Zealand website under specific group standards.</p> <p>Container Disposal: The container or packaging must be cleaned and rendered incapable of holding any substance. It can then be disposed of in a manner consistent with that of the substance it contained. In this instance the packaging can be disposed through a commercial waste collection service. Alternatively, the container or packaging can be recycled if the hazardous residues have been thoroughly cleaned or rendered non-hazardous. In New Zealand, the packaging (that may or may not hold any residual substance) that is lawfully disposed of by householders or other consumers through a public or commercial waste collection service is a means of compliance with regulations.</p>
--------------------------------	---

14. Transport information

Transport Information	<p>Road and Rail Transport: This material is classified as Dangerous Goods Class 8 Corrosive Substances according to NZS 5433:2012 Transport of Dangerous Goods on Land. Must not be loaded in the same freight container or on the same vehicle with:</p> <ul style="list-style-type: none">- Class 1, Explosives- Division 5.1, Oxidising substances- Division 5.2, Organic peroxides- Class 7, Radioactive materials unless specifically exempted- Food items. <p>Note 1: Cyanides (Division 6.1) must not be loaded in the same freight container or on the same vehicle with acids (Class 8).</p> <p>Note 2: Strong acids must not be loaded in the same freight container or on the same vehicle with strong alkalis. Packing Group I and II acids and alkalis should be considered as strong.</p> <p>Must not be loaded with in the same freight container; and on the same vehicle must be separated horizontally by at least 3 metres unless all but one are packed in separate freight containers with:</p> <ul style="list-style-type: none">- Division 4.3, Dangerous when wet substances <p>Goods of packing group II or III may be loaded in the same freight container or on the same vehicle if transported in segregation devices with:</p> <ul style="list-style-type: none">- Division 4.3, Dangerous when wet substances- Division 5.1, Oxidising substances- Division 5.2, Organic peroxides- Food items.
------------------------------	--

Infosafe No™ LPXB4	Issue Date : March 2013	ISSUED by PARCHEMN
--------------------	-------------------------	--------------------

Product Name : **DURAFLOOR V ANTI-SKID HARDENER**

Classified as hazardous

Marine Transport (IMO/IMDG):
 Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.
 UN No.: 2735
 Proper Shipping Name: POLYAMINES, LIQUID, CORROSIVE, N.O.S. (Contains Isophorone diamine and Polyoxypropylene diamine)
 Class: 8
 Packaging Group: III
 EMS No.: F-A, S-B
 Special provisions: 223, 274

Air Transport (ICAO/IATA):
 Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.
 UN No: 2735
 Proper Shipping Name: Polyamines, liquid, corrosive, n.o.s. (Contains Isophorone diamine and Polyoxypropylene diamine)
 Class: 8
 Packing Group: III
 Label: Corrosive
 Packing Instruction: 852 (For passenger and cargo aircraft)
 Packing Instruction: 856 (For cargo aircraft only)
 Special provisions: A3, A803
 2735

U.N. Number

UN proper shipping name AMINES, LIQUID, CORROSIVE, N.O.S. - (Contains Isophorone diamine and Polyoxypropylene diamine)

Transport hazard class(es) 8

Hazchem Code 2X

Packing Group III

EPG Number 8A1

IERG Number 36

IMDG Marine pollutant No

15. Regulatory information

Regulatory Information Classified as Hazardous according to the New Zealand Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001.
 Group Standard: Additives, Process Chemicals and Raw Materials (Corrosive)
 Group Standard 2006

HSNO Approval Number HSR002491

16. Other Information

Date of preparation or last revision of SDS SDS Reviewed: March 2013
 Supersedes: May 2008

Literature References Workplace Exposure Standards and Biological Exposure Indices , Department of Labour, Health & Safety.
 Transport of Dangerous goods on land NZS 5433.
 Preparation of Safety Data Sheets - Approved Code of Practice Under the HSNO Act 1996 (HSNO CoP 8-1 09-06).
 Assigning a hazardous substance to a group standard.
 American Conference of Industrial Hygienists (ACGIH).

Contact Person/Point Technical Support: 1800 812 864

...End Of MSDS...



Safety Data Sheet

infosafe
CS: 1.7.7

Page: 8 of 8

Infosafe No™ LPXB4

Issue Date : March 2013

ISSUED by PARCHEMN

Product Name : **DURAFLOOR V ANTI-SKID HARDENER**

Classified as hazardous

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe MSDS displayed is the intellectual property of Acohs Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe MSDS displayed is the intellectual property of Acohs Pty Ltd. The compilation of MSDS's displayed is the intellectual property of Acohs Pty Ltd.

Copying of any MSDS displayed is permitted for personal use only and otherwise is not permitted. In particular the MSDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of MSDS without the express written consent of Acohs Pty Ltd.