

Safety Data Sheet



Hazardous Substance, Dangerous Goods

1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

Product name: **DURAFLOOR X PRIMER HARDENER**

Recommended use: Aliphatic amine component of a two pack epoxy floor coating. Applied by brush and/or roller.

Supplier: Parchem Construction Suppliers Pty Ltd

ABN: 80 069 961 968

Street Address: 7 Lucca Road
Wyong NSW 2259
Australia

Telephone: (02) 4350 5000

Emergency telephone number: Australia – 1800 033 111 New Zealand – 0800 734 607

2. HAZARDS IDENTIFICATION

This material is hazardous according to health criteria of Safe Work Australia.



Signal Word

Danger

Hazard Classification

Acute Toxicity – Oral – Category 4

Acute Toxicity – Inhalation – Category 3

Skin Corrosion/Irritation – Category 1B

Sensitisation – Skin – Category 1A

Serious Eye Damage/Irritation – Category 1

Hazard Statement(s)

H302 Harmful if swallowed

H314 Causes severe skin burns and eye damage

H317 May cause an allergic skin reaction

H318 Causes serious eye damage

H331 Toxic if inhaled

Prevention Precautionary Statement(s)

P102 Keep out of reach of children

P103 Read label before use

P260 Do not breathe mist, vapours or spray

P264 Wash hands, face and all exposed skin thoroughly after handling

P270 Do not eat, drink or smoke when using this product

P271 Use only outdoors or in a well-ventilated area

P272 Contaminated work clothing should not be allowed out of the workplace

P273 Avoid release to the environment

P280 Wear protective clothing, gloves, eye/face protection and suitable respirator as required

Product name: DURAFLOOR X PRIMER HARDENER

SDS No: PARGHSEN000044

Issued: 31 March 2015

Version: 1.0

Page: 1 of 9

Safety Data Sheet



Response Precautionary Statement(s)

- P101 If medical advice is needed, have product container or label at hand
P301+310 IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician
P301+330+331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting
P302+352 IF ON SKIN: Wash with soap and water
P303+361+353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P363 Wash contaminated clothing before reuse
P333+313 If skin irritation or rash occurs: Get medical advice/attention
P304+340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
P342+311 Call a POISON CENTRE or doctor/physician
P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing
P310 Immediately call a POISON CENTRE or doctor/physician

Storage Precautionary Statement(s)

- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up

Disposal Precautionary Statement(s)

- P501 Dispose of contents/container in accordance with regional and national regulations

Poisons Schedule (Aust): S5

DANGEROUS GOODS CLASSIFICATION

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

Class: 8 Corrosive

3. COMPOSITION INFORMATION

CHEMICAL ENTITY	CAS NO.	PROPORTION
Benzyl alcohol	100-51-6	30 – 60%
Isophorone diamine	2855-13-2	30 – 60%
m-Xylenediamine	1477-55-0	1 – 10%
Polypropylene diamine	9046-10-0	1 – 10%
2-Hydroxybenzoic acid	69-72-7	1 – 10%
Ingredients determined to be non-hazardous	-	Balance
		100%

4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

Inhalation: Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at

Safety Data Sheet



rest until fully recovered. If breathing laboured and patient cyanotic (blue), ensure airways are clear and have a qualified person give oxygen through a facemask. If breathing has stopped apply artificial respiration at once. In the event of cardiac arrest, apply external cardiac massage. Seek immediate medical advice.

Skin contact: For gross contamination, immediately drench with water and remove clothing. Continue to flush skin and hair with plenty of water (and soap if material is insoluble). For skin burns, cover with a clean, dry dressing until medical help is available. If blistering occurs, do NOT break blisters. If swelling, redness, blistering, or irritation occurs seek medical assistance.

Eye contact: Immediately irrigate with copious quantities of water for 15 minutes. Eyelids to be held open. Remove clothing if contaminated and wash skin. Urgently seek medical assistance. Transport to hospital or medical centre.

Ingestion: Immediately rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water. Get to a doctor or hospital quickly.

PPE for First Aiders: Wear overalls, chemical goggles and impervious gloves. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Notes to physician: Treat symptomatically. Can cause corneal burns.

5. FIRE-FIGHTING MEASURES

Hazchem Code: 2X

Suitable extinguishing media: If material is involved in a fire use water fog (or if unavailable fine water spray), foam, dry agent (carbon dioxide, dry chemical powder).

Specific hazards: Combustible material. Corrosive substance.

Fire fighting further advice: On burning may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to products of decomposition.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILLS

Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of vapours. Wipe up with absorbent (clean rag or paper towels). Allow absorbent to dry before disposing with normal household garbage.

LARGE SPILLS

Shut off all possible sources of ignition. Clear area of all unprotected personnel. Prevent further leakage or spillage if safe to do so. Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination and the inhalation of vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal. If contamination of sewers or waterways has occurred advise local emergency services.

Dangerous Goods – Initial Emergency Response Guide No: 36

Safety Data Sheet



7. HANDLING AND STORAGE

Handling: Avoid skin and eye contact and inhalation of vapour, mist or aerosols.

Storage: Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from foodstuffs. Store away from incompatible materials described in Section 10. Store away from sources of heat or ignition. Keep containers closed when not in use - check regularly for leaks.

This material is classified as a Dangerous Good Class 8 Corrosive as per the criteria of the Australian Dangerous Goods Code and must be stored in accordance with the relevant regulations.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

National occupational exposure limits: No value assigned for this specific material by Safe Work Australia.

However for:

	TWA		STEL		CARCINOGEN	NOTICES
	ppm	mg/m ³	ppm	mg/m ³	CATEGORY	
m-Xylenediamine	-	0.1	-	-	-	Sk

As published by Safe Work Australia.

TWA - The time-weighted average airborne concentration over an eight-hour working day, for a five-day working week over an entire working life.

Peak Limitation - a ceiling concentration that should not be exceeded over a measurement period, which should be as short as possible, but not exceeding 15 minutes.

No Exposure Standards assigned to other constituents.

`Sk' Notice - absorption through the skin may be a significant source of exposure. The exposure standard is invalidated if such contact should occur.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept too as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

If the directions for use on the product label are followed, exposure of individuals using the product should not exceed the above standard. The standard was created for workers who are routinely, potentially exposed during product manufacture.

Biological Limit Values: As per the "National Model Regulations for the Control of Workplace Hazardous Substances (Safe Work Australia)" the ingredients in this material do not have a Biological Limit Allocated.

Engineering measures: Use with local exhaust ventilation or while wearing appropriate respirator. Keep containers closed when not in use.

Safety Data Sheet



Personal protection equipment: H: OVERALLS, SAFETY SHOES, CHEMICAL GOGGLES, GLOVES, RESPIRATOR.

Wear overalls, chemical goggles and impervious gloves. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

If risk of inhalation of exists, wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

Hygiene measures: Keep away from food, drink and animal feeding stuffs. When using do not eat, drink or smoke. Wash hands prior to eating, drinking or smoking. Avoid contact with clothing. Avoid skin and eye contact and inhalation of vapour, mist or aerosols. Ensure that eyewash stations and safety showers are close to the workstation location.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form / Colour / Odour: Pale yellow liquid with an ammoniacal odour.

Solubility:	Partly soluble in water.
Specific Gravity:	1.04
Relative Vapour Density (air=1):	N Av
Vapour Pressure (20 °C):	N Av
Flash Point (°C):	>100
Flammability Limits (%):	N Av
Autoignition Temperature (°C):	N Av
% Volatile by Volume:	N Av
Melting Point/Range (°C):	N Av
Boiling Point/Range (°C):	>100
Decomposition Point (°C):	N Av
pH:	N Av
Total VOC (g/Litre):	N Av

(Typical values only - consult specification sheet)

N Av = Not available

N App = Not applicable

10. STABILITY AND REACTIVITY

Reactivity: No reactivity hazards are known for the material.

Chemical stability: This material is thermally stable when stored and used as directed.

Hazardous reactions: No known hazardous reactions.

Conditions to avoid: Avoid temperatures above 40°C. Protect from freezing.

Incompatible materials: Strong acids and strong oxidising agents. Reaction with peroxides may result in violent decomposition of peroxide, possibly creating an explosion. Slowly corrodes copper, aluminium and zinc (includes galvanised surfaces).

Hazardous decomposition products: Ammonia produced when heated. Irritating and toxic fumes at

Safety Data Sheet



elevated temperatures. Burning produces noxious and toxic fumes of nitrogen oxides, carbon monoxide and carbon dioxide.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Acute Effects

Inhalation: Material may be an irritant to mucous membranes and respiratory tract.

Skin contact: Contact with skin will result in severe irritation. Corrosive to skin - may cause skin burns.

Ingestion: Swallowing can result in nausea, vomiting, diarrhoea, abdominal pain and chemical burns to the gastrointestinal tract.

Eye contact: A severe eye irritant. Corrosive to eyes: contact can cause corneal burns. Contamination of eyes can result in permanent injury.

Acute toxicity

Inhalation: This material has been classified as a Category 3 Hazard.
Acute toxicity estimate (based on ingredients): 2 – 10 mg/L/4hr

Skin contact: This material has been classified as non-hazardous.

Ingestion: This material has been classified as a Category 4 Hazard.
Acute toxicity estimate (based on ingredients): 300 - 2,000 mg/Kg

Corrosion/Irritancy: Eye: this material has been classified as a Category 1 Hazard (irreversible effects to eyes). Skin: this material has been classified as a Category 1B Hazard (corrosive to skin).

Sensitisation: Inhalation: this material has been classified as not a respiratory sensitiser.
Skin: this material has been classified as a Category 1A Hazard (skin sensitiser).

Aspiration hazard: This material has been classified as non-hazardous.

Specific target organ toxicity (single exposure): This material has been classified as non-hazardous.

Chronic Toxicity

Mutagenicity: This material has been classified as non-hazardous.

Carcinogenicity: This material has been classified as non-hazardous.

Reproductive toxicity (including via lactation): This material has been classified as non-hazardous.

Specific target organ toxicity (repeat exposure): This material has been classified as non-hazardous.

12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

Safety Data Sheet



Acute aquatic hazard: No information is available to complete an assessment.

Long-term aquatic hazard: This material has been classified as a Category Chronic 3 Hazard.
Acute toxicity estimate (based on ingredients): 10 - 100 mg/L

Ecotoxicity: No information available.

Persistence and degradability: No information available.

Bioaccumulative potential: No information available.

Mobility: No information available.

13. DISPOSAL CONSIDERATIONS

Persons conducting disposal, recycling or reclamation activities should ensure that appropriate personal protection equipment is used, see "Section 8. Exposure Controls and Personal Protection" of this SDS.

If possible material and its container should be recycled. If material or container cannot be recycled, dispose in accordance with local, regional, national and international Regulations.

14. TRANSPORT INFORMATION

ROAD AND RAIL TRANSPORT

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

UN No: 2735
Dangerous Goods Class: 8 Corrosive
Packing Group: II
Hazchem Code: 2X
Emergency Response Guide No: 36

Proper Shipping Name: AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS ISOPHORONE DIAMINE AND XYLENEDIAMINE)

Segregation Dangerous Goods: Not to be loaded with explosives (Class 1), dangerous when wet substances (Class 4.3), oxidising agents (Class 5.1), organic peroxides (Class 5.2), radioactive substances (Class 7) or food and food packaging in any quantity, however exemptions may apply. Note that concentrated strong alkalis are incompatible with concentrated strong acids.

MARINE TRANSPORT

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

UN No: 2735
Dangerous Goods Class: 8 Corrosive
Packing Group: II

Proper Shipping Name: AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS ISOPHORONE DIAMINE AND XYLENEDIAMINE)

Safety Data Sheet



AIR TRANSPORT

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

UN No: 2735
Dangerous Goods Class: 8 Corrosive
Packing Group: II

Proper Shipping Name: AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS ISOPHORONE DIAMINE AND XYLENEDIAMINE)

15. REGULATORY INFORMATION

This material is not subject to the following international agreements:

Montreal Protocol (Ozone depleting substances)
The Stockholm Convention (Persistent Organic Pollutants)
The Rotterdam Convention (Prior Informed Consent)

This material is subject to the following international agreements:

Basel Convention (Hazardous Waste)

- Wastes from production, formulation and use of resins, latex, plasticizers, glues/adhesives

International Convention for the Prevention of Pollution from Ships (MARPOL)

- Annex III - Harmful Substances carried in Packaged Form

This material/constituent(s) is covered by the following requirements:

- The Standard for the *Uniform Scheduling of Medicines and Poisons (SUSMP)* established under the *Therapeutic Goods Act (Commonwealth)*.
- All the constituents of this material are listed on the *Australian Inventory of Chemical Substances (AICS)*.

16. OTHER INFORMATION

Literary reference

This Safety Data Sheet has been prepared by Chemical Data Services Pty Ltd (chemdata.com.au) on behalf of its client.

Supersedes: July 2010

Reason(s) For Issue: 5 Yearly Revision. Change to Transport Information. Format change. Change in Hazardous Substance Classification.

Technical Support: Australia - 1300 737 787, New Zealand – 0800 657 156

Safety Data Sheets are updated frequently. Please ensure that you have a current copy.

This SDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since Parchem Construction Supplies Pty Ltd and Concrete Plus cannot anticipate or control the conditions under which the

Product name: DURAFLOOR X PRIMER HARDENER

SDS No: PARGHSEN000044

Issued: 31 March 2015

Version: 1.0

Page: 8 of 9

Safety Data Sheet



product may be used, each user must, prior to usage, review this SDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company.

Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.