

Infosafe No™ LQ1TK	Issue Date : November 2012	ISSUED by PARCHEMN
--------------------	----------------------------	--------------------

Product Name : **EMER-SEAL CONSTRUCTION SILICONE HM**

Classified as hazardous

1. Identification


GHS Product Identifier	EMER-SEAL CONSTRUCTION SILICONE HM
Company Name	Parchem Construction Supplies Pty Ltd (ABN 80 069 961 968)
Address	7 Lucca Road Wyong NSW 2259 Australia
Telephone/Fax Number	Tel: 02 4350 5000 Fax: 02 4351 2024
Emergency phone number	0800 154 666 (available 24/7)
Recommended use of the chemical and restrictions on use	High modulus silicone sealant.
Other Information	Distributed in New Zealand by: Concrete Plus 23 Watts Road Sockburn New Zealand Tel: (03) 343 0090 Fax: (03) 343 0202

This MSDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since Parchem Construction Supplies Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this MSDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company. Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.

www.parchem.co.nz

2. Hazard Identification

GHS classification of the substance/mixture	Classified as Hazardous according to the Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001, New Zealand. Not Classified as Dangerous Goods for transport according to the New Zealand Standard NZS 5433:2012 Transport of Dangerous Goods on Land. HSNO Classification: 6.3B - Substance that is mildly irritating to the skin 6.5B - Substance that is a contact sensitiser
Signal Word (s)	Warning
Hazard Statement (s)	H316 Causes mild skin irritation. H317 May cause an allergic skin reaction.
Pictogram (s)	Exclamation mark
	
Precautionary statement – Prevention	P103 Read label before use. P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P272 Contaminated work clothing should not be allowed out of the workplace. P280 Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary statement – Response	SKIN: P302+P352 IF ON SKIN: Wash with plenty of soap and water.

Infosafe No™ LQ1TK

Issue Date : November 2012

ISSUED by PARCHEMN

Product Name : **EMER-SEAL CONSTRUCTION SILICONE HM**

Classified as hazardous

Precautionary statement – Disposal

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
 P363 Wash contaminated clothing before reuse.
 P501 In the case of a substance that is in compliance with a HSNO approval other than a Part 6A (Group Standards) approval, a label must provide a description of one or more appropriate and achievable methods for the disposal of a substance in accordance with the Hazardous Substances (Disposal) Regulations 2001. This may also include any method of disposal that must be avoided. See Section 13 for disposal details.

3. Composition/information on ingredients

Ingredients	Name	CAS	Proportion
	2-Butanone, O,O',O''-(methylsilylydyne)trioxime	22984-54-9	<5 %
	Ingredients determined not to be hazardous.		Balance

4. First-aid measures

Inhalation	If inhaled, remove affected person from contaminated area. Keep at rest until recovered. If symptoms persist seek medical attention.
Ingestion	Do not induce vomiting. Wash out mouth thoroughly with water. Seek medical attention.
Skin	Wash affected area thoroughly with soap and water. If symptoms develop seek medical attention.
Eye contact	If in eyes, hold eyelids apart and flush the eyes continuously with running water. Continue flushing for several minutes until all contaminants are washed out completely. If symptoms develop and persist seek medical attention.
First Aid Facilities	Eyewash and normal washroom facilities.
Advice to Doctor	Treat symptomatically.
Other Information	For advice in an emergency, contact a Poisons Information Centre (Phone Australia 13 1126; New Zealand 0800 POISON / 0800 764 766) or a doctor at once.

5. Fire-fighting measures

Suitable extinguishing media	Use carbon dioxide, dry chemical, foam, water mist or water spray.
Hazards from Combustion Products	Under fire conditions this product may emit toxic and/or irritating fumes including carbon monoxide, carbon dioxide and metal oxides.
Specific hazards arising from the chemical	Combustible material. This product will readily burn under fire conditions.
Decomposition Temp.	>200°C
Precautions in connection with Fire	Fire fighters should wear Self-Contained Breathing Apparatus (SCBA) operated in positive pressure mode and full protective clothing to prevent exposure to vapours or fumes. Water spray may be used to cool down heat-exposed containers.

6. Accidental release measures

Emergency Procedures	Wear appropriate personal protective equipment and clothing to prevent exposure. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unprotected personnel. If possible contain the spill. Place inert absorbent, non-combustible material onto spillage. Use clean non-sparking tools to collect the material and place into suitable labelled containers for subsequent recycling or disposal. Dispose of waste according to the applicable local and national regulations. If contamination of sewers or waterways occurs inform the local water and waste management authorities in accordance with local regulations.
-----------------------------	--

7. Handling and storage

Infosafe No™ LQ1TK	Issue Date : November 2012	ISSUED by PARCHEMN
--------------------	----------------------------	--------------------

Product Name : **EMER-SEAL CONSTRUCTION SILICONE HM**

Classified as hazardous

Precautions for Safe Handling	Use only in a well ventilated area. Keep containers sealed when not in use. Prevent the build up of mists or vapours in the work atmosphere. Avoid inhalation of vapours and mists, and skin or eye contact. Do not use near ignition sources. Do not pressurise, cut, heat or weld containers as they may contain hazardous residues. Maintain high standards of personal hygiene i.e. Washing hands prior to eating, drinking, smoking or using toilet facilities.
Conditions for safe storage, including any incompatibilities	Store in a cool, dry, well-ventilated area away from sources of ignition, oxidising agents, strong acids, foodstuffs, and clothing. Keep containers closed when not in use and securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Have appropriate fire extinguishers available in and near the storage area. Take precautions against static electricity discharges. Use proper grounding procedures. For information on the design of the storeroom, reference should be made to Australian Standard AS1940 - The storage and handling of flammable and combustible liquids. Reference should also be made to all applicable local and national regulations.

8. Exposure controls/personal protection

Occupational exposure limit values	No exposure standards have been established for this material by the Occupational Safety and Health Service (OSH) of the New Zealand Department of Labour. However, over-exposure to some chemicals may result in enhancement of pre-existing adverse medical conditions and/or allergic reactions and should be kept to the least possible levels.
Biological Limit Values	No biological limit allocated.
Appropriate engineering controls	Provide sufficient ventilation to keep airborne levels below the exposure limits. Where vapours or mists are generated, particularly in enclosed areas, and natural ventilation is inadequate, a local exhaust ventilation system is required.
Respiratory Protection	If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable mist/dust filter should be used. Reference should be made to Australian/New Zealand Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.
Eye Protection	Safety glasses with side shields or chemical goggles should be worn. Final choice of appropriate eye/face protection will vary according to individual circumstances. Eye protection devices should conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors for Industrial Applications.
Hand Protection	Wear gloves of impervious material, such as laminate film, nitrile or PVC. Final choice of appropriate gloves will vary according to individual circumstances i.e. methods of handling or according to risk assessments undertaken. Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.
Body Protection	Suitable protective work wear, e.g. cotton overalls buttoned at neck and wrist is recommended. Chemical resistant apron is recommended where large quantities are handled.

9. Physical and chemical properties

Appearance	Thixotropic grey paste
Odour	Characteristic oxime odour
Decomposition Temperature	>200°C
Melting Point	Not available
Boiling Point	Not available
Solubility in Water	Insoluble
Specific Gravity	1.25 (23°C)
pH	Not available
Vapour Pressure	Not available

Infosafe No™ LQ1TK	Issue Date : November 2012	ISSUED by PARCHEMN
--------------------	----------------------------	--------------------

Product Name : **EMER-SEAL CONSTRUCTION SILICONE HM**

Classified as hazardous

Vapour Density (Air=1)	Not available
Evaporation Rate	Not available
Odour Threshold	Not available
Viscosity	Not available
Partition Coefficient: n-octanol/water	Not available
Flash Point	Not available
Flammability	Not flammable
Auto-Ignition Temperature	Not available
Flammable Limits - Lower	Not available
Flammable Limits - Upper	Not available

10. Stability and reactivity

Reactivity	Reacts with incompatibles.
Chemical Stability	Stable under normal conditions of storage and handling.
Conditions to Avoid	Heat, flames and other sources of ignition. Keep away from water.
Incompatible Materials	Strong oxidizing agents. Water, moisture.
Hazardous Decomposition Products	Thermal decomposition may result in the release of toxic and/or irritating fumes and gases including carbon monoxide, carbon dioxide, oxime compounds and metal oxides.
Possibility of hazardous reactions	Water, moisture or humid air can cause hazardous vapours to form.
Hazardous Polymerization	Will not occur.

11. Toxicological Information

Toxicology Information	No toxicology data available for this product.
Ingestion	Ingestion of this product may irritate the gastric tract causing nausea and vomiting.
Inhalation	Inhalation of product vapours may cause irritation of the nose, throat and respiratory system.
Skin	Causes mild skin irritation. Skin contact will cause redness, itching and swelling. Repeated exposure may cause skin dryness and cracking and may lead to dermatitis.
Eye	May be irritating to eyes. The symptoms may include redness, itching and tearing.
Respiratory sensitisation	Not expected to be a respiratory sensitiser.
Skin Sensitisation	May cause an allergic skin reaction.
Germ cell mutagenicity	Not considered to be a mutagenic hazard.
Carcinogenicity	Not considered to be a carcinogenic hazard.
Reproductive Toxicity	Not considered to be toxic to reproduction.
STOT-single exposure	Not expected to cause toxicity to a specific target organ.
STOT-repeated exposure	Not expected to cause toxicity to a specific target organ.
Aspiration Hazard	Not expected to be an aspiration hazard.

Infosafe No™ LQ1TK	Issue Date : November 2012	ISSUED by PARCHEMN
--------------------	----------------------------	--------------------

Product Name : **EMER-SEAL CONSTRUCTION SILICONE HM**

Classified as hazardous

12. Ecological information

Ecotoxicity	No ecological data are available for this material.
Persistence and degradability	Not available
Mobility	Not available
Bioaccumulative Potential	Not available
Environmental Protection	Prevent this material entering waterways, drains and sewers.

13. Disposal considerations

Disposal Considerations	<p>Product Disposal: Product wastes are controlled wastes and should be disposed of in accordance with all applicable local and national regulations. This product can be disposed through a licensed commercial waste collection service. The product should be rendered non-hazardous before being sent to a licensed landfill facility. Alternatively, as the product is combustible, it can be sent to an approved high temperature incineration plant for disposal. Personal protective clothing and equipment as specified in Section 8 of this SDS must be worn during handling and disposal of this product. The ventilation requirements as specified in the same section must also be followed, and the precautions given in Section 7 of this SDS regarding handling must also be followed. Do not dispose into the sewerage system. Do not discharge into drains or watercourses or dispose where ground or surface waters may be affected. In New Zealand, the disposal agency or contractor must comply with the New Zealand Hazardous Substances (Disposal) Regulations 2001. Further details regarding disposal can be obtained on the EPA New Zealand website under specific group standards.</p> <p>Container Disposal: The container or packaging must be cleaned and rendered incapable of holding any substance. It can then be disposed of in a manner consistent with that of the substance it contained. In this instance the packaging can be disposed through a commercial waste collection service. Alternatively, the container or packaging can be recycled if the hazardous residues have been thoroughly cleaned or rendered non-hazardous. In New Zealand, the packaging (that may or may not hold any residual substance) that is lawfully disposed of by householders or other consumers through a public or commercial waste collection service is a means of compliance with regulations.</p>
--------------------------------	---

14. Transport information

Transport Information	<p>Road and Rail Transport: Not classified as Dangerous Goods for transport according to the NZS 5433:2012 Transport of Dangerous Goods on Land.</p> <p>Marine Transport (IMO/IMDG): Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.</p> <p>Air Transport (ICAO/IATA): Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.</p>
IMDG Marine pollutant	No

15. Regulatory information

Regulatory Information	<p>Classified as Hazardous according to the New Zealand Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001. Group Standard: Surface Coatings and Colourants (Subsidiary Hazard) Group Standard 2006</p>
-------------------------------	--



Safety Data Sheet

Infosafe No™ LQ1TK	Issue Date : November 2012	ISSUED by PARCHEMN
--------------------	----------------------------	--------------------

Product Name : **EMER-SEAL CONSTRUCTION SILICONE HM**

Classified as hazardous

HSNO Approval Number HSR002670

16. Other Information

Date of preparation or last revision of SDS SDS Created: November 2012

Contact Person/Point Technical Support: 1800 812 864

...End Of MSDS...

© Copyright ACOHS Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe MSDS displayed is the intellectual property of Acohs Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe MSDS displayed is the intellectual property of Acohs Pty Ltd. The compilation of MSDS's displayed is the intellectual property of Acohs Pty Ltd.

Copying of any MSDS displayed is permitted for personal use only and otherwise is not permitted. In particular the MSDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of MSDS without the express written consent of Acohs Pty Ltd.