

Infosafe No™ LPT5P	Issue Date : August 2012	ISSUED by PARCHEMC
--------------------	--------------------------	--------------------

Product Name : **FOSROC NITOFLOOR FC100 CLEAR**

Classified as hazardous

1. Identification

GHS Product Identifier	FOSROC NITOFLOOR FC100 CLEAR
Company Name	Parchem Construction Supplies Pty Ltd (ABN 80 069 961 968)
Address	7 Lucca Road Wyong NSW 2259 Australia
Telephone/Fax Number	Tel: 02 4350 5000 Fax: 02 4351 2024
Emergency phone number	1800 638 556 (available 24/7)
Recommended use of the chemical and restrictions on use	Sealer for cementitious floors
Other Information	<p>This MSDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since Parchem Construction Supplies Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this MSDS in the context of how the user intends to handle and use the product in the workplace.</p> <p>If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company. Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.</p> <p>www.parchem.com.au</p>

2. Hazard Identification

GHS classification of the substance/mixture	<p>Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia.</p> <p>Classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)</p> <p>Flammable Liquids: Category 3 Acute Toxicity - Dermal: Category 4 Acute Toxicity - Inhalation: Category 4 Skin Corrosion/Irritation: Category 2 Toxic to Reproduction: Category 1 Hazardous to the Aquatic Environment - Acute Hazard: Category 3 Hazardous to the Aquatic Environment - Long-Term Hazard: Category 3</p>
Signal Word (s)	Danger
Hazard Statement (s)	<p>H226 Flammable liquid and vapour.</p> <p>H302 Harmful if swallowed.</p> <p>H315 Causes skin irritation.</p> <p>H332 Harmful if inhaled.</p> <p>H360 May damage fertility or the unborn child.</p> <p>H412 Harmful to aquatic life with long lasting effects.</p>
Pictogram (s)	Flame, Exclamation mark, Health hazard



Precautionary statement – Prevention	<p>P103 Read label before use</p> <p>P201 Obtain special instructions before use.</p> <p>P202 Do not handle until all safety precautions have been read and understood.</p> <p>P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.</p> <p>P233 Keep container tightly closed.</p>
---	---

Infosafe No™ LPT5P

Issue Date : August 2012

ISSUED by PARCHEMC

 Product Name : **FOSROC NITOFLOOR FC100 CLEAR**

Classified as hazardous

Precautionary statement – Response

P240 Ground/bond container and receiving equipment.
 P241 Use explosion-proof electrical/ventilating/lighting/.../equipment.
 P242 Use only non-sparking tools.
 P243 Take precautionary measures against static discharge.
 P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 P264 Wash skin thoroughly after handling.
 P270 Do not eat, drink or smoke when using this product.
 P271 Use only outdoors or in a well-ventilated area.
 P273 Avoid release to the environment.
 P280 Wear protective gloves/eye protection/face protection.
GENERAL:
 P370+P378: In case of fire: Use foam, carbon dioxide or dry chemical powder to extinguish.
 P312 Call a POISON CENTER or doctor/physician if you feel unwell.
SKIN:
 P302+P352: IF ON SKIN: Wash with plenty of water.
 P332+P313: If skin irritation occurs: Get medical advice/attention.
 P362+P364: Take off contaminated clothing and wash it before reuse.
EYES:
 P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing.
 P337+P313: If eye irritation persists: Get medical advice/attention.
INHALATION
 P304+P340 IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
INGESTION
 P330 Rinse mouth.
 P331 Do NOT induce vomiting.
Precautionary statement – Storage
 P403+P235: Store in a well-ventilated place. Keep cool.
Precautionary statement – Disposal
 P405 Store locked up.
 P501 Dispose of contents/container to an approved waste disposal plant.

3. Composition/information on ingredients

Ingredients	Name	CAS	Proportion
	Xylene	1330-20-7	60-100 %
	Ethylbenzene	100-41-4	0-<25 %
	Benzyl butyl phthalate	85-68-7	0-<1 %
	Ingredients determined not to be hazardous.		Balance

4. First-aid measures

Inhalation	If inhaled, remove from contaminated area. Apply artificial respiration if not breathing. Seek medical attention.
Ingestion	Do not induce vomiting. Wash out mouth thoroughly with water. Seek immediate medical attention.
Skin	Wash affected area thoroughly with soap and water. Remove contaminated clothing and wash before reuse or discard. Seek medical attention.
Eye contact	If in eyes, hold eyelids apart and flush the eyes continuously with running water. Continue flushing for several minutes until all contaminants are washed out completely. Seek medical attention.
First Aid Facilities	Eye wash, safety shower and normal washroom facilities.
Advice to Doctor	Treat symptomatically.
Other Information	For advice, contact a Poisons Information Centre (Phone eg Australia 131 126; New Zealand 0800 764 766) or a doctor (at once).

5. Fire-fighting measures

Suitable extinguishing media	Use carbon dioxide, dry chemical, foam or water mist.
Unsuitable Extinguishing Media	DO NOT USE water jets.

Infosafe No™ LPT5P	Issue Date : August 2012	ISSUED by PARCHEMC
--------------------	--------------------------	--------------------

Product Name : **FOSROC NITOFLOOR FC100 CLEAR**

Classified as hazardous

Hazards from Combustion	Under fire conditions this product may emit toxic and/or irritating fumes including carbon monoxide and carbon dioxide.
Products	
Specific hazards arising from the chemical	Flammable liquid and vapour. Vapour/air mixtures may ignite explosively. Flashback along the vapour trail may occur. Runoff to sewer may create fire or explosion hazard.
Hazchem Code	•3Y
Precautions in connection with Fire	Fire fighters should wear Self-Contained Breathing Apparatus (SCBA) operated in positive pressure mode and full protective clothing to prevent exposure to vapours or fumes. Water spray may be used to cool down heat-exposed containers. Fight fire from safe location. This product should be prevented from entering drains and watercourses.

6. Accidental release measures

Emergency Procedures	Wear appropriate personal protective equipment and clothing to prevent exposure. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unprotected personnel. If possible contain the spill. Place inert absorbent, non-combustible material onto spillage. Use clean non-sparking tools to collect the material and place into suitable labelled containers for subsequent recycling or disposal. Dispose of waste according to the applicable local and national regulations. If contamination of sewers or waterways occurs inform the local water and waste management authorities in accordance with local regulations.
-----------------------------	--

7. Handling and storage

Precautions for Safe Handling	Avoid contact with skin and eyes. Wear overalls, impervious gloves and safety glasses. Use in designated areas with adequate ventilation. Use approved flammable liquid storage containers in the work area. Prevent release of vapours and mists into workplace air. Keep containers closed when not in use. Take precautionary measures against static discharges. Keep material away from sparks, flames and other ignition sources. Do not empty into drains. Ensure a high level of personal hygiene is maintained when using this product, that is, always wash hands before eating, drinking, smoking or using the toilet facilities.
Conditions for safe storage, including any incompatibilities	Store in a cool, dry, well-ventilated area away from sources of ignition, oxidising agents, strong acids, foodstuffs, and clothing. Keep containers closed when not in use and securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Have appropriate fire extinguishers available in and near the storage area. Take precautions against static electricity discharges. Use proper grounding procedures. For information on the design of the storeroom, reference should be made to Australian Standard AS1940 - The storage and handling of flammable and combustible liquids. Reference should also be made to all applicable local and national regulations.

8. Exposure controls/personal protection

Occupational exposure limit values	No exposure value assigned for this specific material by the Safe Work, Australia. However, the available exposure limits for ingredients are listed below:
---	---

Safe Work, Australia Exposure Standards:

Substance	TWA		STEL		NOTICES
	ppm	mg/m ³	ppm	mg/m ³	
Xylene	80	350	150	655	-
Ethylbenzene	100	434	125	543	-

TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eight-hour working day, for a five-day week.

STEL (Short Term Exposure Limit): The average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.

Biological Limit Values

Biological Exposure Indices (BEI) from American Conference of Industrial Hygienists (ACGIH) for ingredients are as follows:

Determinant	Sampling Time	Biological Exposure
-------------	---------------	---------------------

Infosafe No™ LPT5P	Issue Date : August 2012	ISSUED by PARCHEMC
--------------------	--------------------------	--------------------

Product Name : **FOSROC NITOFLOOR FC100 CLEAR**

Classified as hazardous

Appropriate engineering controls	<p>Indices (BEI) XYLENE [1330-20-7] Methylhippuric acids in urine End of shift 1.5mg/g creatinine Ethylbenzene (100-41-4) Sum of mandelic acid End of shift 0.7g/g creatinine and phenylglyoxylic at end of work week acid in urine</p> <p>Provide sufficient ventilation to keep airborne levels below the exposure limits. Where vapours or mists are generated, particularly in enclosed areas, and natural ventilation is inadequate, a flameproof exhaust ventilation system is required. Refer to AS 1940 - The storage and handling of flammable and combustible liquids and AS/NZS 60079.10.1:2009 Explosive atmospheres - Classification of areas - Explosive gas atmospheres, for further information concerning ventilation requirements.</p>
Respiratory Protection	<p>If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable organic vapour filter should be used. Reference should be made to Australian/New Zealand Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.</p>
Eye Protection	<p>Safety glasses with side shields or chemical goggles should be worn. Final choice of appropriate eye/face protection will vary according to individual circumstances. Eye protection devices should conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors for Industrial Applications.</p>
Hand Protection	<p>Wear gloves of impervious material. Final choice of appropriate gloves will vary according to individual circumstances i.e. methods of handling or according to risk assessments undertaken. Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.</p>
Body Protection	<p>Suitable protective work wear, e.g. cotton overalls buttoned at neck and wrist is recommended. Chemical resistant apron is recommended where large quantities are handled.</p>

9. Physical and chemical properties

Appearance	Clear liquid
Odour	Aromatic solvent
Melting Point	Not available
Boiling Point	139°C (Xylene)
Solubility in Water	Not available
Specific Gravity	0.91 @ 25°C
pH	Not available
Vapour Pressure	8-12 hPa at 20°C (xylene)
Vapour Density (Air=1)	Not available
Evaporation Rate	Not available
Odour Threshold	Not available
Viscosity	Not available
Volatile Component	80% (approximate)
Partition Coefficient: n-octanol/water	Not available
Flash Point	27°C (xylene)
Flammability	Flammable
Auto-Ignition Temperature	Not available
Flammable Limits - Lower	Not available

Infosafe No™ LPT5P	Issue Date : August 2012	ISSUED by PARCHEMC
--------------------	--------------------------	--------------------

Product Name : **FOSROC NITOFLOOR FC100 CLEAR**

Classified as hazardous

Flammable Limits - Upper Not available

10. Stability and reactivity

Reactivity	Reacts with incompatibles
Chemical Stability	Stable under normal conditions of storage and handling.
Conditions to Avoid	Heat, flames and other ignition sources.
Incompatible Materials	Strong oxidising agents.
Hazardous Decomposition Products	Thermal decomposition may result in the release of toxic and/or irritating fumes including carbon monoxide and carbon dioxide.
Hazardous Polymerization	Will not occur.

11. Toxicological Information

Toxicology Information	No toxicology data available for this product.
Ingestion	Harmful if swallowed. May cause irritation to the mouth, throat, esophagus and stomach with symptoms of nausea, pain and vomiting.
Inhalation	Harmful if inhaled. May cause irritation to the mucous membrane and upper airways, especially where vapours or mists are generated. Symptoms include sneezing, coughing, wheezing, shortness of breath, headache, dizziness, nausea, vomiting, incoordination and narcosis.
Skin	Irritating to skin. Skin contact will cause redness, itching and swelling. Repeated exposure may cause skin dryness and cracking and may lead to dermatitis.
Eye	May be irritating to eyes. On eye contact this product may cause tearing, stinging, blurred vision, and redness.
Respiratory sensitisation	Not expected to be a respiratory sensitiser.
Skin Sensitisation	Not expected to be a skin sensitiser.
Germ cell mutagenicity	Not considered to be a mutagenic hazard.
Carcinogenicity	Ethylbenzene is listed as a Group 2B: Possibly carcinogenic to humans according to International Agency for Research on Cancer (IARC).
Reproductive Toxicity	May damage fertility or the unborn child.
STOT-single exposure	Not expected to cause damage to organs.
STOT-repeated exposure	Not expected to cause damage to organs.
Aspiration Hazard	Not expected to be an aspiration hazard.

12. Ecological information

Ecotoxicity	Harmful to aquatic life with long lasting effects.
Persistence and degradability	Not available
Mobility	Not available
Bioaccumulative Potential	Not available
Environmental Protection	Do not discharge this material into waterways, drains and sewers.
Acute Toxicity - Fish	Xylene (mixed isomers): LC50 (Fathead minnow): 13.4 mg/L/96h

13. Disposal considerations

Infosafe No™ LPT5P	Issue Date : August 2012	ISSUED by PARCHEMC
--------------------	--------------------------	--------------------

Product Name : **FOSROC NITOFLOOR FC100 CLEAR**

Classified as hazardous

Disposal Considerations Disposal of spilled or waste material must be carried out in accordance with the relevant local and national government regulations. Advise flammable nature. Empty containers may contain flammable residues. Do not puncture, cut or weld empty containers.

14. Transport information

Transport Information Road and Rail Transport (ADG Code):
This material is a Class 3 - Flammable Liquid according to The Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)
Class 3 - Flammable Liquids are incompatible in a placard load with any of the following:
- Class 1, Explosives
- Division 2.1, Flammable Gases, (Division 2.1 and Class 3 are incompatible in transport if both are in tanks or other receptacles with a capacity individually exceeding 500 L.)
- Division 2.3, Toxic Gases
- Division 4.2 Spontaneously Combustible Substances
- Division 5.1 Oxidising Agents and Division 5.2, Organic Peroxides
- Class 6 Toxic or Infectious Substances (where the flammable liquid is nitromethane)
- Class 7 Radioactive Substances.

Marine Transport (IMO/IMDG):
Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.
UN No.: 1866
Proper Shipping Name: RESIN SOLUTION
DG Class: 3
Packaging Group: III
EMS No.: F-E, S-E
Special provisions: 223, 955

Air Transport (ICAO/IATA):
Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.
UN No: 1866
Proper Shipping Name: : Resin solution
Class: 3
Packing Group: III
Label: Miscellaneous
Packing Instruction: 355 (For passenger and cargo aircraft)
Packing Instruction: 366 (For cargo aircraft only)
Special provisions: A3

U.N. Number 1866
UN proper shipping name RESIN SOLUTION
Transport hazard class(es) 3
Hazchem Code •3Y
Packing Group III
EPG Number 3A1
IERG Number 14
IMDG Marine pollutant No

15. Regulatory information

Regulatory Information Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia
Classified as a Scheduled Poison according to the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

Infosafe No™ LPT5P	Issue Date : August 2012	ISSUED by PARCHEMC
--------------------	--------------------------	--------------------

Product Name : **FOSROC NITOFLOOR FC100 CLEAR**

Classified as hazardous

Poisons Schedule S6

AICS (Australia) All components of this product are listed on the Australian Inventory of Chemical Substances (AICS) or exempted.

16. Other Information

Date of preparation or last revision of SDS SDS Reviewed: August 2012, Supersedes: September 2007

Contact Person/Point Technical Support: 1800 812 864

...End Of MSDS...

© Copyright ACOHS Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe MSDS displayed is the intellectual property of Acohs Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe MSDS displayed is the intellectual property of Acohs Pty Ltd. The compilation of MSDS's displayed is the intellectual property of Acohs Pty Ltd.

Copying of any MSDS displayed is permitted for personal use only and otherwise is not permitted. In particular the MSDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of MSDS without the express written consent of Acohs Pty Ltd.