

Infosafe No™ LQ36D Issue Date : April 2014 ISSUED by PARCHEMN

Product Name : FOSROC NITOFLOL FC130 HARDENER COLOURED

Classified as hazardous

1. Identification

GHS Product Identifier FOSROC NITOFLOL FC130 HARDENER COLOURED

Company Name Parchem Construction Supplies Pty Ltd (ABN 80 069 961 968)

Address 7 Lucca Road Wyong
NSW 2259 Australia

Telephone/Fax Number Tel: 02 4350 5000
Fax: 02 4351 2024

Emergency phone number 0800 154 666 (available 24/7)

Recommended use of the chemical and restrictions on use Hardener component of water based epoxy flooring system.

Other Information Distributed in New Zealand by:
Concrete Plus
23 Watts Road
Sockburn
New Zealand
Tel: (03) 343 0090
Fax: (03) 343 0202

This SDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since Parchem Construction Supplies Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this MSDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company. Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.

www.parchem.co.nz

2. Hazard Identification

Classification of the substance or mixture Classified as Hazardous according to the Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001, New Zealand.
Not classified as Dangerous Goods for transport according to the New Zealand Standard NZS 5433:2012 Transport of Dangerous Goods on Land.

HSNO Classification:

6.3A - Substance that is irritating to the skin
6.5B - Substance that is a contact sensitiser
6.8B - Substance that is suspected to be a human reproductive or developmental toxicant
8.3A - Substance that is corrosive to ocular tissue
9.1C - Substance that is harmful in the aquatic environment

Signal Word (s)

Danger

Hazard Statement (s)

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H361 Suspected of damaging fertility or the unborn child.
H412 Harmful to aquatic life with long lasting effects.

Pictogram (s)

Exclamation mark, Corrosion, Health hazard

Infosafe No™ LQ36D

Issue Date : April 2014

ISSUED by PARCHEMN

 Product Name : **FOSROC NITOFLOL FC130 HARDENER COLOURED**

Classified as hazardous


Precautionary statement – Prevention

P102 Keep out of reach of children.
 P103 Read label before use.
 P201 Obtain special instructions before use.
 P202 Do not handle until all safety precautions have been read and understood.
 P261 Avoid breathing mist/vapours/spray.
 P264 Wash skin thoroughly after handling.
 P272 Contaminated work clothing should not be allowed out of the workplace.
 P273 Avoid release to the environment.
 P280 Wear protective gloves/eye protection/face protection.
 P281 Use personal protective equipment as required.

Precautionary statement – Response

GENERAL
 P101 If medical advice is needed, have product container or label at hand.
 P308+P313 IF exposed or concerned: Get medical advice/ attention.
 EYE
 P310 Immediately call a POISON CENTER or doctor/physician.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 SKIN
 P302+P352 IF ON SKIN: Wash with plenty of soap and water.
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
 P362 Take off contaminated clothing and wash before re-use.
 P405 Store locked up.

Precautionary statement – Storage
Precautionary statement – Disposal

P501 In the case of a substance that is in compliance with a HSNO approval other than a Part 6A (Group Standards) approval, a label must provide a description of one or more appropriate and achievable methods for the disposal of a substance in accordance with the Hazardous Substances (Disposal) Regulations 2001. This may also include any method of disposal that must be avoided. See Section 13 for disposal details.

3. Composition/information on ingredients

Ingredients	Name	CAS	Proportion
	Polyamide resin	Proprietary	5-<15 %
	Dipropylene glycol monomethyl ether	34590-94-8	<1 %
	Xylene	1330-20-7	<1 %
	Pentaethylenhexamine	4067-16-7	<1 %
	Other ingredients determined not to be hazardous including water		To 100%

4. First-aid measures

Inhalation	If inhaled, remove affected person from contaminated area. Keep at rest until recovered. If symptoms develop and/or persist seek medical attention.
Ingestion	Do not induce vomiting. Wash out mouth thoroughly with water. Seek medical attention.
Skin	Remove all contaminated clothing immediately. Wash affected area thoroughly with soap and water. Wash contaminated clothing before reuse or discard. Seek medical attention.
Eye contact	If in eyes, hold eyelids apart and flush the eyes continuously with running water. Remove contact lenses. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Seek immediate medical attention.
First Aid Facilities	Eyewash, safety shower and normal washroom facilities.
Advice to Doctor	Treat symptomatically.

Infosafe No™ LQ36D Issue Date : April 2014 ISSUED by PARCHEMN

Product Name : **FOSROC NITOFLOL FC130 HARDENER COLOURED**

Classified as hazardous

Other Information For advice in an emergency, contact a Poisons Information Centre or a doctor at once. (0800 764 766)

5. Fire-fighting measures

Suitable extinguishing media Use appropriate fire extinguisher for surrounding environment.

Hazards from Combustion Products Under fire conditions this product may emit toxic and/or irritating fumes, smoke and gases including carbon monoxide, carbon dioxide and oxides of nitrogen.

Specific hazards arising from the chemical The product is not combustible, but under fire conditions, the non-aqueous components may decompose and/or burn after the water component evaporates.

Decomposition Temp. Not available

Precautions in connection with Fire Fire fighters should wear Self-Contained Breathing Apparatus (SCBA) operated in positive pressure mode and full protective clothing to prevent exposure to vapours or fumes. Water spray may be used to cool down heat-exposed containers.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Wear appropriate personal protective equipment and clothing to prevent exposure. Increase ventilation. If possible contain the spill. Place inert absorbent material onto spillage. Collect the material and place into a suitable labelled container. Do not dilute material but contain. Dispose of waste according to the applicable local and national regulations. If contamination of sewers or waterways occurs inform the local water and waste management authorities in accordance with local regulations.

7. Handling and storage

Precautions for Safe Handling Avoid inhalation of vapours and mists, and skin or eye contact. Use only in a well ventilated area. Keep containers sealed when not in use. Prevent the build up of mists or vapours in the work atmosphere. Maintain high standards of personal hygiene i.e. Washing hands prior to eating, drinking, smoking or using toilet facilities.

Conditions for safe storage, including any incompatibilities Store in a cool, dry, well-ventilated area, out of direct sunlight. Store in suitable, labelled containers. Keep containers tightly closed. Store away from incompatible materials. Ensure that storage conditions comply with applicable local and national regulations.

8. Exposure controls/personal protection

Occupational exposure limit values No exposure value assigned for this material by Occupational Safety and Health Service (OSH) of the New Zealand Department of Labour. However, the available exposure limits for ingredients are listed below:

New Zealand Occupational Safety and Health Service (OSH) Workplace Exposure Standards:

Substance	TWA		STEL		NOTICES
	ppm	mg/m ³	ppm	mg/m ³	
Dipropylene glycol, monomethyl ether	100	606	150	909	Sk
Xylene	50	217	-	-	-

TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eight-hour working day, for a five-day week.

STEL (Short Term Exposure Limit): The average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.

'Sk' Notice: Absorption through the skin may be a significant source of exposure. The exposure standard is invalidated if such contact should occur. Name: XYLENE [1330-20-7]

Biological Limit Values Determinant: Methylhippuric acids
Specimen: Creatinine in urine

Infosafe No™ LQ36D	Issue Date : April 2014	ISSUED by PARCHEMN
--------------------	-------------------------	--------------------

Product Name : **FOSROC NITOFLOL FC130 HARDENER COLOURED**

Classified as hazardous

	Value: 1.5 g/g Sampling time: End of shift
Appropriate engineering controls	Source: American Conference of Industrial Hygienists (ACGIH) Provide sufficient ventilation to keep airborne levels below the exposure limits or as low as possible. Where vapours or mists are generated, particularly in enclosed areas, and natural ventilation is inadequate, a flameproof exhaust ventilation system is required. Refer to relevant regulations for further information concerning ventilation requirements.
Respiratory Protection	If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable vapor/ mist filter should be used. Refer to relevant regulations for further information concerning respiratory protective requirements. Reference should be made to Australian Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.
Eye Protection	Safety glasses with side shields, chemical goggles or full-face shield as appropriate should be used. Final choice of appropriate eye/face protection will vary according to individual circumstances. Eye protection devices should conform to relevant regulations. Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors for Industrial Applications.
Hand Protection	Wear laminated film, nitrile, neoprene or other suitable, impervious gloves. Final choice of appropriate gloves will vary according to individual circumstances i.e. methods of handling or according to risk assessments undertaken. Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.
Body Protection	Suitable protective work wear, e.g. cotton overalls buttoned at neck and wrist is recommended. Chemical resistant apron is recommended where large quantities are handled.

9. Physical and chemical properties

Appearance	Low viscosity liquid.
Colour	Pigmented
Odour	Slight amine odour.
Decomposition Temperature	Not available
Melting Point	Not available
Boiling Point	100°C (Approximate) (water)
Solubility in Water	Completely miscible.
Specific Gravity	1.29 (23°C)
pH	Not available
Vapour Pressure	24 mmHg (25°C)
Vapour Density (Air=1)	Not available
Evaporation Rate	<1 (n-Butyl acetate=1)
Viscosity	Not available
Partition Coefficient: n-octanol/water	Not available
Flash Point	Not applicable
Flammability	Non-combustible liquid
Auto-Ignition Temperature	Not applicable

Infosafe No™ LQ36D	Issue Date : April 2014	ISSUED by PARCHEMN
--------------------	-------------------------	--------------------

Product Name : **FOSROC NITOFLOL FC130 HARDENER COLOURED**

Classified as hazardous

Flammable Limits - Lower Not applicable**Flammable Limits - Upper** Not applicable**10. Stability and reactivity****Reactivity** Reacts with incompatible materials.**Chemical Stability** Stable under normal conditions of storage and handling.**Conditions to Avoid** Extremes of temperature and direct sunlight**Incompatible Materials** Strong oxidising agents.**Hazardous Decomposition Products** Thermal decomposition may result in the release of toxic and/or irritating fumes, smoke and gases including: carbon monoxide, carbon dioxide and oxides of nitrogen.**Hazardous Polymerization** Will not occur.**11. Toxicological Information****Toxicology Information** No toxicity data available for this material.**Ingestion** Ingestion of this product may irritate the gastric tract causing nausea and vomiting.**Inhalation** Inhalation of product vapours may cause irritation of the nose, throat and respiratory system.**Skin** Causes skin irritation. Skin contact will cause redness, itching and swelling. Repeated exposure may cause skin dryness and cracking and may lead to dermatitis. May cause an allergic skin reaction.**Eye** Causes eye damage. Eye contact will cause stinging, blurring, tearing, severe pain and possible burns, necrosis, permanent damage and blindness. Not expected to be a respiratory sensitiser.**Respiratory sensitisation****Skin Sensitisation** May cause an allergic skin reaction.**Germ cell mutagenicity** Not considered to be a mutagenic hazard.**Carcinogenicity** Not considered to be a carcinogenic hazard.**Reproductive Toxicity** Xylene is listed as a Group 3: Not classifiable as to carcinogenicity to humans according to International Agency for Research on Cancer (IARC). Suspected of damaging fertility or the unborn child. Classified as a suspected human reproductive or developmental toxicant.**STOT-single exposure** Not expected to cause toxicity to a specific target organ.**STOT-repeated exposure** Not expected to cause toxicity to a specific target organ.**Aspiration Hazard** Not expected to be an aspiration hazard.**12. Ecological information****Ecotoxicity** Harmful to aquatic life with long lasting effects.**Persistence and degradability** Not available**Mobility** Not available**Bioaccumulative Potential** Not available**Environmental Protection** Prevent this material entering waterways, drains and sewers.**13. Disposal considerations**

Infosafe No™ LQ36D Issue Date : April 2014 ISSUED by PARCHEMN

Product Name : **FOSROC NITOFLOL FC130 HARDENER COLOURED**

Classified as hazardous

Disposal Considerations

Product Disposal:

Product wastes are controlled wastes and should be disposed of in accordance with all applicable local and national regulations. This product can be disposed through a licensed commercial waste collection service. In this specific case the product is water-based/water-soluble and therefore can be sent through a Waste Water Treatment Plant and after treatment can be discharged into environment through the sewerage or drainage systems as authorized.

Do not dispose directly into the sewerage system. Do not discharge into drains or watercourses or dispose where ground or surface waters may be affected. Personal protective clothing and equipment as specified in Section 8 of this SDS must be worn during handling and disposal of this product. The ventilation requirements as specified in the same section must also be followed, and the precautions given in Section 7 of this SDS regarding handling must also be followed.

In New Zealand, the disposal agency or contractor must comply with the New Zealand Hazardous Substances (Disposal) Regulations 2001. Further details regarding disposal can be obtained on the EPA New Zealand website under specific group standards.

Container Disposal:

The container or packaging must be cleaned and rendered incapable of holding any substance. It can then be disposed of in a manner consistent with that of the substance it contained. In this instance the packaging can be disposed through a commercial waste collection service.

Alternatively, the container or packaging can be recycled if the hazardous residues have been thoroughly cleaned or rendered non-hazardous.

In New Zealand, the packaging (that may or may not hold any residual substance) that is lawfully disposed of by householders or other consumers through a public or commercial waste collection service is a means of compliance with regulations.

14. Transport information

Transport Information

Australia:

Not classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)

Marine Transport (IMO/IMDG):

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

Air Transport (ICAO/IATA):

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

IMDG Marine pollutant

No

15. Regulatory information

National and or International Regulatory Information

Classified as Hazardous according to the New Zealand Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001.

Group Standard:

Additives, Process Chemicals and Raw Materials (Subsidiary Hazard) Group Standard 2006

HSNO Approval Number

HSR002503

16. Other Information

Date of preparation or last revision of SDS

SDS Created: April 2014

Literature References

Workplace Exposure Standards and Biological Exposure Indices , Department of Labour , Health & Safety.

Infosafe No™ LQ36D

Issue Date : April 2014

ISSUED by PARCHEMN

Product Name : **FOSROC NITOFLOL FC130 HARDENER COLOURED**

Classified as hazardous

Transport of Dangerous goods on land NZS 5433.

Preparation of Safety Data Sheets - Approved Code of Practice Under the HSNO Act 1996 (HSNO CoP 8-1 09-06).

Assigning a hazardous substance to a group standard.

American Conference of Industrial Hygienists (ACGIH)
Technical Support: 1800 812 864

Contact

Person/Point

...End Of MSDS...

© Copyright ACOHS Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe MSDS displayed is the intellectual property of Acohs Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe MSDS displayed is the intellectual property of Acohs Pty Ltd. The compilation of MSDS's displayed is the intellectual property of Acohs Pty Ltd.

Copying of any MSDS displayed is permitted for personal use only and otherwise is not permitted. In particular the MSDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of MSDS without the express written consent of Acohs Pty Ltd.