

Infosafe No™ LQ3DN	Issue Date : June 2014	ISSUED by PARCHEMC
--------------------	------------------------	--------------------

Product Name : **SEALER TINT PART B**

Classified as hazardous

1. Identification

GHS Product Identifier	SEALER TINT PART B
Company Name	Parchem Construction Supplies Pty Ltd (ABN 80 069 961 968)
Address	7 Lucca Road Wyong NSW 2259 Australia
Telephone/Fax Number	Tel: 02 4350 5000 Fax: 02 4351 2024
Emergency phone number	1800 638 556 (available 24/7)
Recommended use of the chemical and restrictions on use	Pigmented viscous oxide tinters for acrylic copolymer resins
Other Information	<p>This SDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since Parchem Construction Supplies Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this MSDS in the context of how the user intends to handle and use the product in the workplace.</p> <p>If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company. Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.</p> <p>www.parchem.com.au</p>

2. Hazard Identification

Classification of the substance or mixture	<p>Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia.</p> <p>Classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)</p> <p>Flammable Liquids: Category 3 Acute Toxicity - Dermal: Category 4 Acute Toxicity - Inhalation: Category 4 Skin Corrosion/Irritation: Category 2 STOT Repeated Exposure Category 2 Toxic to Reproduction: Category 1</p>
Signal Word (s)	Danger
Hazard Statement (s)	<p>H226 Flammable liquid and vapour. H312 Harmful in contact with skin. H315 Causes skin irritation. H332 Harmful if inhaled. H360 May damage fertility or the unborn child H373 May cause damage to organs through prolonged or repeated exposure</p>
General Precautionary Statement (s)	P101 If medical advice is needed, have product container or label at hand.
Pictogram (s)	P102 Keep out of reach of children. P103 Read label before use.
General Precautionary Statement (s)	Flame, Health hazard, Exclamation mark



Precautionary statement – Prevention	<p>P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.</p>
---	--

Infosafe No™ LQ3DN	Issue Date : June 2014	ISSUED by PARCHEMC
--------------------	------------------------	--------------------

Product Name : **SEALER TINT PART B**

Classified as hazardous

Precautionary statement – Response	<p>P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ventilating/lighting/equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P260 Do not breathe mist/vapours/spray. P264 Wash contaminated skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/eye protection/face protection. P308+P313 IF exposed or concerned: Get medical advice/ attention. P314 Get medical advice/attention if you feel unwell. P331 Do NOT induce vomiting. P370+P378 In case of fire: Use foam, dry chemical powder or carbon dioxide for extinction. P304+P340 IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. P332+P313 If skin irritation occurs: Get medical advice/ attention. P362 Take off contaminated clothing and wash before re-use. P403+P235 Store in a well-ventilated place. Keep cool. P405 Store locked up. P501 Dispose of contents/container to an approved waste disposal plant.</p>
Precautionary statement – Storage	
Precautionary statement – Disposal	
Supplemental information	<p>The information under this heading is not mandatory under WHS Regulations. It is provided as information on other GHS hazard classes and categories and/or environmental hazards that are outside the scope of the WHS Regulations. GHS classification: Hazardous to the Aquatic Environment - Acute Hazard: Category 2, Hazardous to the Aquatic Environment - Long-Term Hazard: Category 2. Hazard statement: H411. Precautionary statement: P273, P391. Pictogram: Environment.</p>

3. Composition/information on ingredients

Information on Composition * Total of CAS 64742-95-6 and 64742-82-1 is <10%

Ingredients	Name	CAS	Proportion
	Xylene	1330-20-7	10-30 %
	Benzyl butyl phthalate	85-68-7	0-<10 %
	Solvent naphtha (petroleum), light aromatic	64742-95-6	0-<10 %
	Naphtha, petroleum, hydrodesulfurized heavy	64742-82-1	0-<10 %
	Ethylbenzene	100-41-4	0-<10 %
	Other ingredients determined not to be hazardous		Balance

4. First-aid measures

Inhalation	If inhaled, remove affected person from contaminated area. Apply artificial respiration if not breathing. Seek medical attention.
Ingestion	Do not induce vomiting. Wash out mouth thoroughly with water. Seek immediate medical attention.
Skin	Remove all contaminated clothing immediately. Wash affected area thoroughly with soap and water. Wash contaminated clothing before reuse or discard. Seek medical attention.
Eye contact	If in eyes, hold eyelids apart and flush the eyes continuously with running water. Remove contact lenses. Continue flushing for several minutes until all contaminants are washed out completely. If symptoms develop, seek medical attention.
First Aid Facilities	Eye wash station, safety shower and normal washroom facilities.
Advice to Doctor	Treat symptomatically.

Infosafe No™ LQ3DN	Issue Date : June 2014	ISSUED by PARCHEMC
--------------------	------------------------	--------------------

Product Name : **SEALER TINT PART B**

Classified as hazardous

Other Information For advice in an emergency, contact a Poisons Information Centre (Phone 131 126 in Australia) or a doctor at once.

5. Fire-fighting measures

Suitable extinguishing media Use carbon dioxide, dry chemical or foam. Alcohol resistant foam is preferred. If not available normal foam can be used.

Unsuitable Extinguishing Media Do not use water jet.

Hazards from Combustion Products Under fire conditions this product may emit toxic and/or irritating fumes including oxides of nitrogen, carbon monoxide and carbon dioxide.

Specific hazards arising from the chemical Flammable liquid and vapour. Vapour/air mixtures may ignite explosively. Flashback along the vapour trail may occur. Runoff to sewer may create fire or explosion hazard.

Hazchem Code •3Y

Decomposition Temp. Not available

Precautions in connection with Fire Fire fighters should wear Self-Contained Breathing Apparatus (SCBA) and full protective clothing to prevent exposure to vapours, fumes or products of combustion. Water spray may be used to cool down heat-exposed material. If safe to do so, remove containers from path of fire. Do not allow run-off from fire fighting to enter drains or water courses.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Wear appropriate personal protective equipment and clothing to prevent exposure. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unprotected personnel. If possible contain the spill. Place inert absorbent, non-combustible material onto spillage. Use clean non-sparking tools to collect the material and place into suitable labelled containers for subsequent recycling or disposal. Dispose of waste according to the applicable local and national regulations. If contamination of sewers or waterways occurs inform the local water and waste management authorities in accordance with local regulations.

7. Handling and storage

Precautions for Safe Handling Wear appropriate personal protective equipment and clothing to prevent exposure. Handle and use the material in a well-ventilated area, away from sparks, flames and other ignition sources. Have emergency equipment (for fires, spills, leaks, etc.) readily available. Work from suitable, labelled, fire-resistant containers. Open containers carefully as they may be under pressure. Keep containers tightly closed. Flameproof equipment is necessary in areas where the product is being used. Take precautionary measures against static discharges. Earth or bond all equipment. Do not empty into drains. Ensure a high level of personal hygiene is maintained when using this product, that is, always wash hands before eating, drinking, smoking or using the toilet facilities. Avoid exposure. Do not handle until all safety precautions have been read and understood. It is recommended that pregnant or breastfeeding women should not handle this product unless adequate exposure protection can be assured at all times. Female personnel planning pregnancy should be made aware of the potential risks.

Conditions for safe storage, including any incompatibilities Store in a cool, dry, well-ventilated area away from sources of ignition, oxidising agents, acids, bases, foodstuffs, and out of direct sunlight. Have appropriate fire extinguishers available in and near the storage area. Take precautions against static electricity discharges. For information on the design of the storeroom, reference should be made to Australian Standard AS1940 - The storage and handling of flammable and combustible liquids. Reference should also be made to all applicable state and federal regulations.

8. Exposure controls/personal protection

Occupational exposure limit values No exposure value assigned for this material by Safe Work, Australia. However, the available exposure limits for ingredients are listed below:

Safe Work, Australia Exposure Standards:
 Substance TWA STEL NOTES

Infosafe No™ LQ3DN	Issue Date : June 2014	ISSUED by PARCHEMC
--------------------	------------------------	--------------------

Product Name : **SEALER TINT PART B**

Classified as hazardous

	ppm	mg/m ³	ppm	mg/m ³	
Xylene	80	350	150	655	-
Ethylbenzene	100	434	125	543	-

TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eight-hour working day, for a five-day week.

STEL (Short Term Exposure Limit): The average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.

Biological Limit Values

Name: Xylenes
 Determinant: Methylhippuric acids
 Specimen: Creatinine in urine.
 Value: 1.5g/g
 Sampling time: End of shift.

Name: Ethylbenzene
 Determinant: Sum of mandelic acid and phenylglyoxylic acid.
 Specimen: Creatinine in urine.
 Value: 0.7 g/g
 Sampling time: End of shift at end of work week.

Appropriate engineering controls

Source: American Conference of Industrial Hygienists (ACGIH)
 This substance is hazardous and should be used with a local exhaust ventilation system, drawing vapours away from workers' breathing zone. A flame-proof exhaust ventilation system is required. If the engineering controls are not sufficient to maintain concentrations of vapours/mists below the exposure standards, suitable respiratory protection must be worn. Refer to relevant regulations for further information concerning ventilation requirements. Refer to AS 1940 - The storage and handling of flammable and combustible liquids and AS/NZS 2430.3.1:2004: Classification of hazardous areas - Examples of area classification - General, for further information concerning ventilation requirements.

Respiratory Protection

If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable organic vapour filter should be used. Reference should be made to Australian/New Zealand Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.

Eye Protection

Safety glasses with side shields or chemical goggles should be worn. Final choice of appropriate eye/face protection will vary according to individual circumstances. Eye protection devices should conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors for Industrial Applications.

Hand Protection

Wear impervious gloves such as PVC. Final choice of appropriate gloves will vary according to individual circumstances i.e. methods of handling or according to risk assessments undertaken. Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.

Body Protection

Suitable protective workwear, e.g. cotton overalls buttoned at neck and wrist. When large quantities are handled the use of plastic aprons and rubber boots is recommended.

9. Physical and chemical properties

Appearance	Coloured viscous liquid.
Colour	Coloured
Odour	Aromatic hydrocarbon odour.
Decomposition Temperature	Not available
Melting Point	-48°C
Boiling Point	136-191°C
Solubility in Water	0.175g/l
Solubility in Organic Solvents	100% solubility in solvents
Specific Gravity	1.3-1.5

Infosafe No™ LQ3DN	Issue Date : June 2014	ISSUED by PARCHEMC
--------------------	------------------------	--------------------

 Product Name : **SEALER TINT PART B**

Classified as hazardous

pH	Not available
Vapour Pressure	4.5
Vapour Density (Air=1)	3.7
Evaporation Rate	13.5
Odour Threshold	Not available
Viscosity	Not available
Volatile Component	VOC: 40%
Partition Coefficient: n-octanol/water	Not available
Flash Point	27-31°C
Flammability	Flammable
Auto-Ignition Temperature	432-530°C
Flammable Limits - Lower	1.0%
Flammable Limits - Upper	7.1%

10. Stability and reactivity

Reactivity	Will react with incompatible materials.
Chemical Stability	Stable under normal conditions of handling and storage.
Conditions to Avoid	Heat, direct sunlight, open flames or other sources of ignition.
Incompatible Materials	Oxidising agents.
Hazardous Decomposition Products	Under fire conditions this product may emit toxic and/or irritating fumes including oxides of nitrogen, carbon monoxide and carbon dioxide.
Hazardous Polymerization	Will not occur.

11. Toxicological Information

Toxicology Information	No toxicity data available for this material. The available acute toxicity data for the ingredients are given below.
Acute Toxicity - Oral	Xylene: LD50 (rat): >200 mg/kg
Acute Toxicity - Dermal	Xylene: LD50 (rabbit): >2000 mg/kg
Acute Toxicity - Inhalation	Xylene: LC50 (rat): >20mg/1/4h
Ingestion	Ingestion of this product may irritate the gastric tract causing nausea, vomiting, abdominal pain and CNS depression with symptoms including dizziness, drowsiness, confusion and possible unconsciousness.
Inhalation	Harmful if inhaled. Inhalation of product vapours can cause irritation of the nose, throat and respiratory system. The vapours may be irritating to the respiratory system. Chronic exposure may cause headache, nausea, drowsiness, dizziness, central nervous system depression which may cause unconsciousness.
Skin	Harmful in contact with skin. Product can be absorbed through skin with resultant harmful systemic effects. Causes skin irritation. Skin contact will cause redness, itching and swelling. Prolonged or repeated skin contact may cause defatting leading to drying and cracking of skin, and dermatitis.
Eye	May be irritating to eyes. The symptoms may include redness, itching and tearing.
Respiratory sensitisation	Not expected to be a respiratory sensitiser.

Infosafe No™ LQ3DN	Issue Date : June 2014	ISSUED by PARCHEMC
--------------------	------------------------	--------------------

Product Name : **SEALER TINT PART B**

Classified as hazardous

Skin Sensitisation	Not expected to be a skin sensitiser.
Germ cell mutagenicity	Not considered to be a mutagenic hazard.
Carcinogenicity	Not considered to be a carcinogenic hazard. Ethylbenzene is listed as a Group 2B: Possibly carcinogenic to humans according to International Agency for Research on Cancer (IARC). Xylene and Benzylbutylphthalate are listed as Group 3: Not classifiable as to its carcinogenicity to humans according to International Agency for Research on Cancer (IARC).
Reproductive Toxicity	May damage fertility or the unborn child. Classified as a Known or presumed human reproductive or developmental toxicant.
STOT-single exposure	Not expected to cause toxicity to a specific target organ.
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration Hazard	Not expected to be an aspiration hazard.

12. Ecological information

Ecotoxicity	Toxic to aquatic life with long lasting effects.
Persistence and degradability	Readily biodegradable. Oxidises rapidly by photo-chemical reactions in air.
Mobility	If product enters soil, it will be highly mobile and may contaminate groundwater. Floats on water.
Bioaccumulative Potential	Does not bioaccumulate significantly.
Environmental Protection	Do not discharge this material into waterways, drains and sewers.
Acute Toxicity - Fish	LC/EC/IC50=1-10mg/l
Acute Toxicity - Algae	LC/EC/IC50=1-10mg/l
Acute Toxicity - Other Organisms	LC/EC/IC50 (aquatic invertebrates)=1-10mg/l

13. Disposal considerations

Disposal Considerations	Dispose of waste according to applicable local and national regulations. Labels should not be removed from containers until they have been cleaned. Advise flammable nature. Empty containers may contain flammable residues. Do not puncture, cut or weld on or near empty containers. Contaminated containers must not be treated as household waste. Containers should be cleaned by appropriate methods and then re-used or disposed of by landfill or incineration as appropriate. Do not incinerate closed containers. Wastes including emptied containers are controlled wastes and should be disposed of in accordance with all applicable local and national regulations. Do not allow into drains or watercourses or dispose of where ground or surface waters may be affected.
--------------------------------	---

14. Transport information

Transport Information	This material is Dangerous Goods Class 3 - Flammable Liquid according to The Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition) Class 3 - Flammable Liquids are incompatible in a placard load with any of the following: - Class 1, Explosives - Division 2.1, Flammable Gases, (Division 2.1 and Class 3 are incompatible in transport if both are in tanks or other receptacles with a capacity individually exceeding 500 L.) - Division 2.3, Toxic Gases - Division 4.2 Spontaneously Combustible Substances - Division 5.1 Oxidising substances and Division 5.2, Organic Peroxides - Class 6 Toxic or Infectious Substances (where the flammable liquid is nitromethane)
------------------------------	--

Infosafe No™ LQ3DN	Issue Date : June 2014	ISSUED by PARCHEMC
--------------------	------------------------	--------------------

Product Name : **SEALER TINT PART B**

Classified as hazardous

- Class 7 Radioactive Substances.
Marine Transport (IMO/IMDG):
Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.
UN No.: 1263
Proper Shipping Name: PAINT (Benzyl Butyl Phthalate) MARINE POLLUTANT
DG Class: 3
Packaging Group: III
EMS No.: F-E, S-E
Special provisions: 163, 223, 955

Air Transport (ICAO/IATA):
Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.
UN No: 1263
Proper Shipping Name: PAINT
Class: 3
Packing Group: III
Label: Flammable liquid
Packing Instruction: 355 (For passenger and cargo aircraft)
Packing Instruction: 366 (For cargo aircraft only)
Special provisions: A3, A72
1263

U.N. Number 1263
UN proper shipping name PAINT
Transport hazard class(es) 3
Hazchem Code •3Y
Packing Group III
EPG Number 3C1
IERG Number 14
IMDG Marine pollutant Yes

15. Regulatory information

Regulatory Information Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia
Classified as a Scheduled Poison according to the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

Poisons Schedule S5

AICS (Australia) All components of this product are listed on the Australian Inventory of Chemical Substances (AICS).

16. Other Information

Date of preparation or last revision of SDS SDS created: June 2014

Literature References Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice. Standard for the Uniform Scheduling of Medicines and Poisons. Australian Code for the Transport of Dangerous Goods by Road & Rail. Model Work Health and Safety Regulations, Schedule 10: Prohibited carcinogens, restricted carcinogens and restricted hazardous chemicals. Workplace exposure standards for airborne contaminants, Safe work Australia. American Conference of Industrial Hygienists (ACGIH). Globally Harmonised System of classification and labelling of chemicals.

Contact Person/Point Technical Support: 1800 812 864
...End Of MSDS...

Infosafe No™ LQ3DN

Issue Date : June 2014

ISSUED by PARCHEMC

Product Name : **SEALER TINT PART B**

Classified as hazardous

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe MSDS displayed is the intellectual property of Acchs Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe MSDS displayed is the intellectual property of Acchs Pty Ltd.
The compilation of MSDS's displayed is the intellectual property of Acchs Pty Ltd.

Copying of any MSDS displayed is permitted for personal use only and otherwise is not permitted. In particular the MSDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of MSDS without the express written consent of Acchs Pty Ltd.