

Infosafe No™ LPSXN	Issue Date : February 2014	ISSUED by PARCHEMC
--------------------	----------------------------	--------------------

Product Name : **FOSROC ADHESIVE A901**

Classified as hazardous

1. Identification

GHS Product Identifier	FOSROC ADHESIVE A901
Company Name	Parchem Construction Supplies Pty Ltd (ABN 80 069 961 968)
Address	7 Lucca Road Wyong NSW 2259 Australia
Telephone/Fax Number	Tel: 02 4350 5000 Fax: 02 4351 2024
Emergency phone number	1800 638 556 (available 24/7)
Recommended use of the chemical and restrictions on use	A contact adhesive for bonding laminated plastics, polyurethane foams, rubber, leather, timber and metal surfaces to a variety of substrates.
Other Information	<p>This SDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since Parchem Construction Supplies Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this MSDS in the context of how the user intends to handle and use the product in the workplace.</p> <p>If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company. Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.</p> <p>www.parchem.com.au</p>

2. Hazard Identification

Classification of the substance or mixture	<p>Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia.</p> <p>Classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)</p> <p>Flammable Liquids: Category 2 Eye Damage/Irritation: Category 2 Skin Corrosion/Irritation: Category 2 STOT Single Exposure Category 3 (narcotic) STOT Repeated Exposure Category 2 Toxic to Reproduction: Category 2 Hazardous to the Aquatic Environment - Acute Hazard: Category 2 Hazardous to the Aquatic Environment - Long-Term Hazard: Category 2</p>
Signal Word (s)	Danger
Hazard Statement (s)	<p>H225 Highly flammable liquid and vapour. H315 Causes skin irritation. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H361 Suspected of damaging fertility or the unborn child. H373 May cause damage to organs through prolonged or repeated exposure. H411 Toxic to aquatic life with long lasting effects.</p>
General Precautionary Statement (s)	<p>P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P103 Read label before use.</p>
Pictogram (s)	Flame, Health hazard, Exclamation mark, Environment



Infosafe No™ LPSXN	Issue Date : February 2014	ISSUED by PARCHEMC
--------------------	----------------------------	--------------------

 Product Name : **FOSROC ADHESIVE A901**

Classified as hazardous

Precautionary statement – Prevention	P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ventilating/lighting/equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P260 Do not breathe mist/vapours/spray. P264 Wash contaminated skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P273 Avoid release to the environment. P280 Wear protective gloves/eye protection/face protection.
Precautionary statement – Response	P308+P313 IF exposed or concerned: Get medical advice/ attention. P370+P378 In case of fire: Use foam, dry chemical powder or carbon dioxide for extinction. P304+P340 IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 If eye irritation persists: Get medical advice/attention. P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. P332+P313 If skin irritation occurs: Get medical advice/ attention. P362 Take off contaminated clothing and wash before re-use. P391 Collect spillage.
Precautionary statement – Storage	P403+P233+P235 Store in a well-ventilated place. Keep container tightly closed. Keep cool. P405 Store locked up.
Precautionary statement – Disposal	P501 Dispose of contents/container to an approved waste disposal plant.

3. Composition/information on ingredients

Ingredients	Name	CAS	Proportion
	Toluene	108-88-3	30-<50 %
	Naphtha (petroleum), hydrotreated light	64742-49-0	10-30 %
	Acetone	67-64-1	10-<25 %
	Zinc oxide	1314-13-2	1-<2.5 %
	Other ingredients determined not to be hazardous		Balance

4. First-aid measures

Inhalation	If inhaled, remove affected person from contaminated area. Apply artificial respiration if not breathing. Seek medical attention.
Ingestion	Do not induce vomiting. Wash out mouth thoroughly with water. Seek immediate medical attention.
Skin	Remove all contaminated clothing immediately. Wash affected area thoroughly with soap and water. Wash contaminated clothing before reuse or discard. Seek medical attention.
Eye contact	If in eyes, hold eyelids apart and flush the eyes continuously with running water. Remove contact lenses. Continue flushing for several minutes until all contaminants are washed out completely. Seek medical attention.
First Aid Facilities	Eye wash station, safety shower and normal washroom facilities.
Advice to Doctor	Treat symptomatically.
Other Information	For advice in an emergency, contact a Poisons Information Centre (Phone 131 126 in Australia) or a doctor at once.

5. Fire-fighting measures

Suitable extinguishing media	Use carbon dioxide, dry chemical or foam. Alcohol resistant foam is preferred. If not available normal foam can be used.
-------------------------------------	--

Infosafe No™ LPSXN	Issue Date : February 2014	ISSUED by PARCHEMC
--------------------	----------------------------	--------------------

Product Name : **FOSROC ADHESIVE A901**

Classified as hazardous

Unsuitable Extinguishing Media	Do not use water jet.
Hazards from Combustion Products	Under fire conditions this product may emit toxic and/or irritating fumes including oxides of nitrogen, carbon monoxide and carbon dioxide.
Specific hazards arising from the chemical	Highly flammable liquid and vapour. Vapour/air mixtures may ignite explosively. Flashback along the vapour trail may occur. Runoff to sewer may create fire or explosion hazard.
Hazchem Code	•3YE
Decomposition Temp.	Not available
Precautions in connection with Fire	Fire fighters should wear Self-Contained Breathing Apparatus (SCBA) and full protective clothing to prevent exposure to vapours, fumes or products of combustion. Water spray may be used to cool down heat-exposed material. If safe to do so, remove containers from path of fire. Do not allow run-off from fire fighting to enter drains or water courses.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Wear appropriate personal protective equipment and clothing to prevent exposure. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unprotected personnel. If possible contain the spill. Place inert absorbent, non-combustible material onto spillage. Use clean non-sparking tools to collect the material and place into suitable labelled containers for subsequent recycling or disposal. Dispose of waste according to the applicable local and national regulations. If contamination of sewers or waterways occurs inform the local water and waste management authorities in accordance with local regulations.
--	--

7. Handling and storage

Precautions for Safe Handling	Wear appropriate personal protective equipment and clothing to prevent exposure. Handle and use the material in a well-ventilated area, away from sparks, flames and other ignition sources. Have emergency equipment (for fires, spills, leaks, etc.) readily available. Work from suitable, labelled, fire-resistant containers. Open containers carefully as they may be under pressure. Keep containers tightly closed. Flameproof equipment is necessary in areas where the product is being used. Take precautionary measures against static discharges. Earth or bond all equipment. Do not empty into drains. Ensure a high level of personal hygiene is maintained when using this product, that is, always wash hands before eating, drinking, smoking or using the toilet facilities. Avoid exposure. Do not handle until all safety precautions have been read and understood. It is recommended that pregnant or breastfeeding women should not handle this product unless adequate exposure protection can be assured at all times. Female personnel planning pregnancy should be made aware of the potential risks.
Conditions for safe storage, including any incompatibilities	Store in a cool, dry, well-ventilated area away from sources of ignition, oxidising agents, acids, bases, foodstuffs, and out of direct sunlight. Have appropriate fire extinguishers available in and near the storage area. Take precautions against static electricity discharges. For information on the design of the storeroom, reference should be made to Australian Standard AS1940 - The storage and handling of flammable and combustible liquids. Reference should also be made to all applicable state and federal regulations.

8. Exposure controls/personal protection

Occupational exposure limit values	No exposure value assigned for this material by Safe Work, Australia. However, the available exposure limits for ingredients are listed below:
---	--

Safe Work, Australia Exposure Standards:

Substance	TWA		STEL		NOTES
	ppm	mg/m ³	ppm	mg/m ³	
Acetone	500	1185	1000	2375	-
Toluene	50	191	150	574	Sk
Zinc oxide fume	5	-	10	-	-

TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eight-hour working day, for

Infosafe No™ LPSXN	Issue Date : February 2014	ISSUED by PARCHEMC
--------------------	----------------------------	--------------------

Product Name : **FOSROC ADHESIVE A901**

Classified as hazardous

Biological Limit Values	<p>a five-day week.</p> <p>STEL (Short Term Exposure Limit): The average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.</p> <p>'Sk' Notice: Absorption through the skin may be a significant source of exposure. The exposure standard is invalidated if such contact should occur.</p> <p>Biological Exposure Indices BEI from American Conference of Industrial Hygienists (ACGIH) for ingredients are as follows:</p> <table border="1"> <thead> <tr> <th>Determinant</th> <th>Sampling Time</th> <th>Biological Exposure Indices (BEI)</th> </tr> </thead> <tbody> <tr> <td colspan="3">TOLUENE [108-88-3]</td> </tr> <tr> <td>Toluene in urine</td> <td>End of Shift</td> <td>0.03 mg/L</td> </tr> <tr> <td>Toluene in blood</td> <td>Prior to last shift of work week</td> <td>0.02 mg/L</td> </tr> <tr> <td>o-Cresol with hydrolysis</td> <td>End of Shift</td> <td>0.3 mg/g</td> </tr> <tr> <td>creatinine in urine</td> <td></td> <td></td> </tr> </tbody> </table>	Determinant	Sampling Time	Biological Exposure Indices (BEI)	TOLUENE [108-88-3]			Toluene in urine	End of Shift	0.03 mg/L	Toluene in blood	Prior to last shift of work week	0.02 mg/L	o-Cresol with hydrolysis	End of Shift	0.3 mg/g	creatinine in urine		
Determinant	Sampling Time	Biological Exposure Indices (BEI)																	
TOLUENE [108-88-3]																			
Toluene in urine	End of Shift	0.03 mg/L																	
Toluene in blood	Prior to last shift of work week	0.02 mg/L																	
o-Cresol with hydrolysis	End of Shift	0.3 mg/g																	
creatinine in urine																			
Appropriate engineering controls	<p>ACETONE [67-64-1]</p> <table border="1"> <thead> <tr> <th>Determinant</th> <th>Sampling Time</th> <th>Biological Exposure Indices (BEI)</th> </tr> </thead> <tbody> <tr> <td colspan="3">ACETONE [67-64-1]</td> </tr> <tr> <td>Acetone in urine</td> <td>End of shift</td> <td>50 mg/L</td> </tr> </tbody> </table> <p>This substance is hazardous and should be used with a local exhaust ventilation system, drawing vapours away from workers' breathing zone. A flame-proof exhaust ventilation system is required. If the engineering controls are not sufficient to maintain concentrations of vapours/mists below the exposure standards, suitable respiratory protection must be worn. Refer to relevant regulations for further information concerning ventilation requirements. Refer to AS 1940 - The storage and handling of flammable and combustible liquids and AS/NZS 2430.3.1:2004: Classification of hazardous areas - Examples of area classification - General, for further information concerning ventilation requirements.</p>	Determinant	Sampling Time	Biological Exposure Indices (BEI)	ACETONE [67-64-1]			Acetone in urine	End of shift	50 mg/L									
Determinant	Sampling Time	Biological Exposure Indices (BEI)																	
ACETONE [67-64-1]																			
Acetone in urine	End of shift	50 mg/L																	
Respiratory Protection	<p>If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable organic vapour filter should be used. Reference should be made to Australian/New Zealand Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.</p>																		
Eye Protection	<p>Safety glasses with side shields or chemical goggles should be worn. Final choice of appropriate eye/face protection will vary according to individual circumstances. Eye protection devices should conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors for Industrial Applications.</p>																		
Hand Protection	<p>Wear impervious gloves such as laminated film, nitrile or neoprene rubber. Final choice of appropriate gloves will vary according to individual circumstances i.e. methods of handling or according to risk assessments undertaken. Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.</p>																		
Body Protection	<p>Suitable protective workwear, e.g. cotton overalls buttoned at neck and wrist. When large quantities are handled the use of plastic aprons and rubber boots is recommended.</p>																		

9. Physical and chemical properties

Appearance	Pigmented translucent liquid.
Odour	Hydrocarbon solvent odour.
Decomposition Temperature	Not available
Melting Point	Not available
Boiling Point	Not available
Solubility in Water	Insoluble
Specific Gravity	0.86 (23°C)
pH	Not available
Vapour Pressure	7.3kPa (38°C) (Toluene)
Vapour Density (Air=1)	3.2 (Toluene)

Infosafe No™ LPSXN	Issue Date : February 2014	ISSUED by PARCHEMC
--------------------	----------------------------	--------------------

Product Name : **FOSROC ADHESIVE A901**

Classified as hazardous

Evaporation Rate	2.4 (n-Butyl acetate=1) (Toluene)
Odour Threshold	Not available
Viscosity	2,500 to 3,200 cP
Partition Coefficient: n-octanol/water	Not available
Flash Point	-17°C (Acetone)
Flammability	Highly flammable liquid.
Auto-Ignition Temperature	Not available
Flammable Limits - Lower	1.0% by volume (Toluene)
Flammable Limits - Upper	7.1% by volume (Toluene)

10. Stability and reactivity

Reactivity	Will react with incompatible materials.
Chemical Stability	Stable under normal conditions of handling and storage.
Conditions to Avoid	Heat, direct sunlight, open flames or other sources of ignition.
Incompatible Materials	Oxidising agents, strong acids and alkalis.
Hazardous Decomposition Products	Under fire conditions this product may emit toxic and/or irritating fumes including oxides of nitrogen, carbon monoxide and carbon dioxide.
Hazardous Polymerization	Will not occur.

11. Toxicological Information

Toxicology Information	No toxicity data are available for this specific product.
Ingestion	Ingestion of this product may irritate the gastric tract causing nausea, vomiting, abdominal pain and CNS depression with symptoms including dizziness, drowsiness, confusion and possible unconsciousness.
Inhalation	Vapours may cause drowsiness and dizziness. The vapours may be irritating to the respiratory system. The symptoms of inhalation of high concentrations of solvent vapour are pulmonary irritation, including coughing, with nausea; central nervous system depression characterised by headache and dizziness; and increased reaction time, fatigue and loss of coordination. If exposure to highly concentrated solvent vapours is prolonged this may lead to narcosis, unconsciousness, even coma and possible death.
Skin	Causes skin irritation. Skin contact will cause redness, itching and swelling. Prolonged or repeated skin contact may cause defatting leading to drying and cracking of skin, and dermatitis.
Eye	Causes serious eye irritation. On eye contact this product will cause tearing, stinging, blurred vision, and redness.
Respiratory sensitisation	Not expected to be a respiratory sensitiser.
Skin Sensitisation	Not expected to be a skin sensitiser.
Germ cell mutagenicity Carcinogenicity	Not considered to be a mutagenic hazard. Not considered to be a carcinogenic hazard. Toluene is listed as a Group 3: Not classifiable as to its carcinogenicity to humans according to International Agency for Research on Cancer (IARC).
Reproductive Toxicity STOT-single exposure	Suspected of damaging fertility or the unborn child. Classified as a suspected human reproductive or developmental toxicant. May cause drowsiness or dizziness.

Infosafe No™ LPSXN Issue Date : February 2014 ISSUED by PARCHEMC

Product Name : **FOSROC ADHESIVE A901**

Classified as hazardous

STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.
Aspiration Hazard Not expected to be an aspiration hazard.
Other Information Chronic exposure may cause damage to the central nervous system, blood organs, optic nerve, heart, liver and kidneys.

12. Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.
Persistence and degradability Not available
Mobility Not available
Bioaccumulative Potential Not available
Environmental Protection Do not discharge this material into waterways, drains and sewers.

13. Disposal considerations

Disposal Considerations Dispose of waste according to applicable local and national regulations. Labels should not be removed from containers until they have been cleaned. Do not cut, puncture or weld on or near containers. Empty containers may contain hazardous residues. Contaminated containers must not be treated as household waste. Containers should be cleaned by appropriate methods and then re-used or disposed of by landfill or incineration as appropriate. Do not incinerate closed containers. Advise flammable nature.

14. Transport information

Transport Information This material is Dangerous Goods Class 3 - Flammable Liquid according to The Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)
Class 3 - Flammable Liquids are incompatible in a placard load with any of the following:
- Class 1, Explosives
- Division 2.1, Flammable Gases, (Division 2.1 and Class 3 are incompatible in transport if both are in tanks or other receptacles with a capacity individually exceeding 500 L.)
- Division 2.3, Toxic Gases
- Division 4.2 Spontaneously Combustible Substances
- Division 5.1 Oxidising substances and Division 5.2, Organic Peroxides
- Class 6 Toxic or Infectious Substances (where the flammable liquid is nitromethane)
- Class 7 Radioactive Substances.

Marine Transport (IMO/IMDG):

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

UN No.: 1133

Proper Shipping Name: ADHESIVES containing flammable liquid

Class: 3

Packaging Group: II

EMS No.: F-E, S-D

Special Provision(s): -

Air Transport (ICAO/IATA):

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

UN No.: 1133

Proper Shipping Name: ADHESIVES containing flammable liquid

Class: 3

Packaging Group: II

Hazard Label: Flammable liquid

Packaging Instructions (passenger & cargo): 353

Packaging Instructions (cargo only): 364

Infosafe No™ LPSXN Issue Date : February 2014 ISSUED by PARCHEMC

Product Name : **FOSROC ADHESIVE A901**

Classified as hazardous

U.N. Number	Special Provision(s): A3 1133
UN proper shipping name	ADHESIVES
Transport hazard class(es)	3
Hazchem Code	•3YE
Packing Group	II
EPG Number	3A1
IERG Number	14
IMDG Marine pollutant	Yes

15. Regulatory information

Regulatory Information	Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia Classified as a Scheduled Poison according to the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).
Poisons Schedule	S5
AICS (Australia)	All components of this product are listed on the Australian Inventory of Chemical Substances (AICS).

16. Other Information

Date of preparation or last revision of SDS	SDS Reviewed: February 2014 Supersedes: May 2009
Literature References	Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice. Standard for the Uniform Scheduling of Medicines and Poisons. Australian Code for the Transport of Dangerous Goods by Road & Rail. Model Work Health and Safety Regulations, Schedule 10: Prohibited carcinogens, restricted carcinogens and restricted hazardous chemicals. Workplace exposure standards for airborne contaminants, Safe work Australia. American Conference of Industrial Hygienists (ACGIH). Globally Harmonised System of classification and labelling of chemicals.
Contact Person/Point	Technical Support: 1800 812 864 ...End Of MSDS...

© Copyright ACOHS Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe MSDS displayed is the intellectual property of Acohs Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe MSDS displayed is the intellectual property of Acohs Pty Ltd.
The compilation of MSDS's displayed is the intellectual property of Acohs Pty Ltd.

Copying of any MSDS displayed is permitted for personal use only and otherwise is not permitted. In particular the MSDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of MSDS without the express written consent of Acohs Pty Ltd.