

Safety Data Sheet



Hazardous Substance, Dangerous Goods

1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

Product name: **FOSROC CONCURE HR90**

Recommended use: Concrete curing compound. Spray applied.

Supplier: Parchem Construction Suppliers Pty Ltd Distributed in New Zealand by:
Concrete Plus

ABN: 80 069 961 968

Street Address: 7 Lucca Road
Wyong NSW 2259
Australia

23 Watts Road
Sockburn
New Zealand
(03) 343 0090

Telephone: (02) 4350 5000

Emergency telephone number: Australia – 1800 033 111 New Zealand – 0800 734 607

2. HAZARDS IDENTIFICATION

This material is hazardous according to criteria of EPA New Zealand.

EPA Group Standard: Surface Coatings and Colourants (Flammable) Group Standard 2006: HSR002662



Signal Word

Danger

HSNO Hazard Classification

3.1C - Flammable liquids

6.1D - Substances that are acutely toxic - Oral

6.1D - Substances that are acutely toxic - Dermal

6.1D - Substances that are acutely toxic - Inhalation - vapours, dusts or mists

6.1E - Substances that are acutely toxic - Aspiration hazard (H304)

6.3A - Substances that are irritating to the skin

6.4A - Substances that are irritating to the eye

6.5B - Substances that are contact sensitisers

9.1B - Substances that are ecotoxic in the aquatic environment (H411)

Hazard Statement(s)

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H411 Toxic to aquatic life with long lasting effects.

Safety Data Sheet



Prevention Precautionary Statement(s)

P102	Keep out of reach of children.
P103	Read label before use.
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical, ventilating, lighting and all other equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust, fume, gas, mist, vapours or spray.
P264	Wash hands, face and all exposed skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective clothing, gloves, eye/face protection and suitable respirator

Response Precautionary Statement(s)

P101	If medical advice is needed, have product container or label at hand.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P330	Rinse mouth.
P331	Do NOT induce vomiting.
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P362	Take off contaminated clothing and wash before reuse.
P370+P378	In case of fire: Use alcohol resistant foam, standard foam or dry agent for extinction.

Storage Precautionary Statement(s)

P405	Store locked up
P403+235	Store in a well ventilated place. Keep cool

Disposal Precautionary Statement(s)

P501	Dispose of contents/container in accordance with regional and national regulations
------	--

DANGEROUS GOODS CLASSIFICATION

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

Class: 3 Flammable Liquid

Safety Data Sheet



3. COMPOSITION INFORMATION

CHEMICAL ENTITY	CAS NO.	PROPORTION
Turpentine oil	8006-84-2	30 - 60%
Ethanol	64-17-5	1 - 10%
Ingredients determined to be non-hazardous	-	Balance
		100%

4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

Inhalation: Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. If breathing laboured and patient cyanotic (blue), ensure airways are clear and have a qualified person give oxygen through a facemask. If breathing has stopped apply artificial respiration at once. In the event of cardiac arrest, apply external cardiac massage. Seek immediate medical advice.

Skin contact: For gross contamination, immediately drench with water and remove clothing. Continue to flush skin and hair with plenty of water (and soap if material is insoluble). For skin burns, cover with a clean, dry dressing until medical help is available. If blistering occurs, do NOT break blisters. If swelling, redness, blistering, or irritation occurs seek medical assistance.

Eye contact: If in eyes, hold eyelids apart and flush the eyes continuously with running water. Continue flushing until advised to stop by the Poisons Information Centre or a Doctor; or for at least 15 minutes and transport to Doctor or Hospital.

Ingestion: Immediately rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water. Get to a doctor or hospital quickly.

PPE for First Aiders: Wear overalls, safety glasses and impervious gloves. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Notes to physician: Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Hazchem Code: •3Y

Suitable extinguishing media: If material is involved in a fire use alcohol resistant foam, standard foam or dry agent (carbon dioxide, dry chemical powder).

Specific hazards: Flammable liquid. May form flammable vapour mixtures with air. Flameproof equipment necessary in area where this chemical is being used. Nearby equipment must be earthed. Electrical requirements for work area should be assessed according to AS3000. Vapour may travel a considerable

Safety Data Sheet



distance to source of ignition and flash back. Avoid all ignition sources. All potential sources of ignition (open flames, pilot lights, furnaces, spark producing switches and electrical equipment etc) must be eliminated both in and near the work area. Do NOT smoke.

Fire fighting further advice: If safe to do so, remove containers from path of fire. Keep containers cool with water spray. On burning may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILLS

Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of vapours. Wipe up with absorbent (clean rag or paper towels). Allow absorbent to dry before disposing with normal household garbage.

LARGE SPILLS

Shut off all possible sources of ignition. Clear area of all unprotected personnel. Prevent further leakage or spillage if safe to do so. Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination and the inhalation of vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal. Use a spark-free shovel.

If contamination of sewers or waterways has occurred advise local emergency services.

Dangerous Goods – Initial Emergency Response Guide No: 14

7. HANDLING AND STORAGE

Handling: Avoid skin and eye contact and inhalation of vapour, mist or aerosols.

Storage: Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from foodstuffs. Store away from incompatible materials described in Section 10. Store away from sources of heat or ignition. Keep containers closed when not in use - check regularly for leaks. Keep containers closed when not in use - check regularly for spills.

This material is classified as a Dangerous Good Class 3 Flammable Liquid as per the criteria of the Australian Dangerous Goods Code and must be stored in accordance with the relevant regulations.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

National occupational exposure limits: No value assigned for this specific material by the Department of Labour New Zealand.

However for:

	WES - TWA		WES - STEL		CARCINOGEN	NOTICES
	ppm	mg/m ³	ppm	mg/m ³	CATEGORY	
Turpentine oil	100	556	-	-	-	Sen

As published by the Department of Labour New Zealand.

Safety Data Sheet



WES-TWA (Workplace Exposure Standard – Time-weighted Average). The time-weighted average exposure standard designed to protect the worker for the effects of long-term exposure.

No Exposure Standards assigned to other constituents.

'Sen' notice - sensitiser. The substance can cause a specific immune response in some people. An affected individual may subsequently react to exposure to minute levels of that substance.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept too as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

If the directions for use on the product label are followed, exposure of individuals using the product should not exceed the above standard. The standard was created for workers who are routinely, potentially exposed during product manufacture.

Biological Limit Values: As per the "National Model Regulations for the Control of Workplace Hazardous Substances (Safe Work Australia)" the ingredients in this material do not have a Biological Limit Allocated.

Engineering measures: Ensure ventilation is adequate to maintain air concentrations below Exposure Standards. Use only in well ventilated areas. Use with local exhaust ventilation or while wearing appropriate respirator. Vapour heavier than air - prevent concentration in hollows or sumps. DO NOT enter confined spaces where vapour may have collected. Keep containers closed when not in use.

Personal protection equipment: YELLOW: OVERALLS, SAFETY SHOES, SAFETY GLASSES, GLOVES, RESPIRATOR.

Wear overalls, safety glasses and impervious gloves. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from butyl rubber/leather/natural rubber/neoprene/nitrile rubber/polyethylene/polyvinyl alcohol (PVA)/polyvinyl chloride (PVC)/teflon should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Hygiene measures: Keep away from food, drink and animal feeding stuffs. When using do not eat, drink or smoke. Wash hands prior to eating, drinking or smoking. Avoid skin and eye contact and inhalation of vapour, mist or aerosols. Ensure that eyewash stations and safety showers are close to the workstation location.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form / Colour / Odour: Green thin liquid with a characteristic solvent odour.

Solubility:	Insoluble in water.
Specific Gravity:	0.9
Relative Vapour Density (air=1):	>1
Vapour Pressure (kPa):	25
Flash Point (°C):	38
Flammability Limits (%):	LEL – 1.0; UEL – 6.0
Autoignition Temperature (°C):	N Av
% Volatile by Volume:	65
Melting Point/Range (°C):	N Av

Safety Data Sheet



Boiling Point/Range (°C): 56
pH: N Av
Viscosity: N Av

(Typical values only - consult specification sheet)
N Av = Not available N App = Not applicable

10. STABILITY AND REACTIVITY

Reactivity: No reactivity hazards are known for the material.

Chemical stability: This material is thermally stable when stored and used as directed.

Hazardous reactions: No known hazardous reactions.

Conditions to avoid: Elevated temperatures and sources of ignition.

Incompatible materials: Oxidising agents.

Hazardous decomposition products: Oxides of carbon and nitrogen, smoke and other toxic fumes.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Acute Effects

Inhalation: Material may be an irritant to mucous membranes and respiratory tract. Where this material is used in a poorly ventilated area, at elevated temperatures or in confined spaces, vapour may cause irritation to mucous membranes and respiratory tract, headache and nausea.

Skin contact: Contact with skin will result in irritation. Will have a degreasing action on the skin. A skin sensitiser. Repeated or prolonged skin contact may lead to allergic contact dermatitis.

Ingestion: Swallowing can result in nausea, vomiting and irritation of the gastrointestinal tract. May cause lung damage if swallowed. Small amounts of liquid aspirated into the respiratory system during ingestion or vomiting may cause bronchopneumonia or pulmonary oedema.

Eye contact: An eye irritant.

Acute toxicity

Inhalation: This material has been classified as a Category 6.1D Hazard.
Acute toxicity estimate (based on ingredients): 10 - 20 mg/L

Skin contact: This material has been classified as a Category 6.1D Hazard.
Acute toxicity estimate (based on ingredients): 1,000 - 2,000 mg/Kg

Ingestion: This material has been classified as a Category 6.1D Hazard.
Acute toxicity estimate (based on ingredients): 300 - 2,000 mg/Kg

Safety Data Sheet



Corrosion/Irritancy: Eye: this material has been classified as a Category 6.4A Hazard (reversible effects to eyes).

Skin: this material has been classified as a Category 6.3A Hazard (irritant to skin).

Sensitisation: Inhalation: this material has been classified as not a respiratory sensitiser.

Skin: this material has been classified as a Category 6.5B Hazard (skin sensitiser).

Aspiration hazard: This material has been classified as a Category 6.1E Hazard.

Specific target organ toxicity (single exposure): This material has been classified as non-hazardous.

Chronic Toxicity

Mutagenicity: This material has been classified as non-hazardous.

Carcinogenicity: This material has been classified as non-hazardous.

Reproductive toxicity (including via lactation): This material has been classified as non-hazardous.

Specific target organ toxicity (repeat exposure): This material has been classified as non-hazardous.

12. ECOLOGICAL INFORMATION

Avoid contaminating waterways. No data available for the product. However, for the constituent:

Acute aquatic hazard: No information is available to complete an assessment.

Long-term aquatic hazard: This material has been classified as a Category 9.1B Hazard.

Acute toxicity estimate (based on ingredients): 1 - 10 mg/L

Ecotoxicity: No information available.

Persistence and degradability: No information available.

Bioaccumulative potential: No information available.

Mobility: No information available.

13. DISPOSAL CONSIDERATIONS

Persons conducting disposal, recycling or reclamation activities should ensure that appropriate personal protection equipment is used, see "Section 8. Exposure Controls and Personal Protection" of this SDS.

If possible material and its container should be recycled. If material or container cannot be recycled, dispose in accordance with local, regional, national and international Regulations.

14. TRANSPORT INFORMATION

ROAD AND RAIL TRANSPORT

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

Safety Data Sheet



UN No: 1866
Dangerous Goods Class: 3 Flammable liquid
Packing Group: III
Hazchem Code: •3Y
Emergency Response Guide No: 14

Proper Shipping Name: RESIN SOLUTION

Segregation Dangerous Goods: Not to be loaded with explosives (Class 1), flammable gases (Class 2.1), if both are in bulk, toxic gases (Class 2.3), spontaneously combustible substances (Class 4.2), oxidising agents (Class 5.1), organic peroxides (Class 5.2) or radioactive substances (Class 7), however exemptions may apply.

MARINE TRANSPORT

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

This material is classified as a Marine Pollutant (P) according to the International Maritime Dangerous Goods Code.

UN No: 1866
Dangerous Goods Class: 3 Flammable liquid
Packing Group: III

Proper Shipping Name: RESIN SOLUTION

AIR TRANSPORT

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

UN No: 1866
Dangerous Goods Class: 3 Flammable liquid
Packing Group: III

Proper Shipping Name: RESIN SOLUTION

15. REGULATORY INFORMATION

This material is not subject to the following international agreements:

Montreal Protocol (Ozone depleting substances)
The Stockholm Convention (Persistent Organic Pollutants)
The Rotterdam Convention (Prior Informed Consent)

This material is subject to the following international agreements:

Basel Convention (Hazardous Waste)

- Wastes from production, formulation and use of resins, latex, plasticizers, glues/adhesives

International Convention for the Prevention of Pollution from Ships (MARPOL)

- Annex III - Harmful Substances carried in Packaged Form

This material/constituent(s) is covered by the following requirements:

Safety Data Sheet



- All the constituents of this material are listed on the *Australian Inventory of Chemical Substances (AICS)*.

16. OTHER INFORMATION

Literary reference

This Safety Data Sheet has been prepared by Chemical Data Services Pty Ltd (chemdata.com.au) on behalf of its client.

Supersedes: February 2011

Reason(s) For Issue: Revised. Format change. Change in Hazardous Substance Classification.

Technical Support: Australia - 1300 737 787, New Zealand – 0800 657 156

Safety Data Sheets are updated frequently. Please ensure that you have a current copy.

This SDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since Parchem Construction Supplies Pty Ltd and Concrete Plus cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this SDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company.

Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.