



1 of 6 Page:

Infosafe No™ LPWTO Issue Date : August 2012 ISSUED by PARCHEMN

FOSROC NITOMORTAR 903 BASE Product Name

Classified as hazardous

1. Identification

GHS Product

FOSROC NITOMORTAR 903 BASE

Identifier **Company Name**

Parchem Construction Supplies Pty Ltd (ABN 80 069 961 968)

Address 7 Lucca Road Wyong

NSW 2259 Australia Tel: 02 4350 5000

Telephone/Fax Fax: 02 4351 2024 Number

0800 154 666 (available 24/7) **Emergency phone**

number

Recommended use of the chemical and restrictions on use

Other Information

Base component of epoxy repair mortar.

Distributed in New Zealand by: Concrete Plus 23 Watts Road Sockburn

New Zealand

Tel: (03) 343 0090 Fax: (03) 343 0202

This MSDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since Parchem Construction Supplies Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this MSDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company. Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.

www.parchem.co.nz

2. Hazard Identification

GHS classification of

Classified as Hazardous according to the Hazardous Substances (Minimum Degrees

of Hazard) Regulations 2001, New Zealand.

substance/mixture

the

Classified as Dangerous Goods for transport according to the New Zealand

Standard NZS 5433:2012 Transport of Dangerous Goods on Land.

6.3A - Substance that is irritating to the skin. 6.4A - Substance that is irritating to the eye. 6.5B - Substance that is a contact sensitiser.

6.9B - Substance that is harmful to human target organs or systems.

9.1B - Substance that is ecotoxic in the aquatic environment.

Signal Word (s) Warning

Hazard Statement (s)

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H371 May cause damage to organs through prolonged or repeated exposure

(dermal).

H411 Toxic to aquatic life with long lasting effects.

Pictogram (s)

Exclamation mark, Environment, Health hazard,







Print Date: 23/08/2012 CS: 1.6.21





2 of 6 Page:

Infosafe No™ LPWTO Issue Date : August 2012 ISSUED by PARCHEMN

FOSROC NITOMORTAR 903 BASE Product Name

Classified as hazardous

P103 Read label before use. -This statement applies only where the substance Precautionary is available to the general public. statement -P104 Read Safety Data Sheet before use. Prevention Do not breathe dust/fume/gas/mist/vapours/spray. P260 P264 Wash skin thoroughly after handling. P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment. -This statement does not apply where

this is the intended use.

P280 Wear protective gloves/protective clothing/eye protection/face

protection. GENERAL

Precautionary statement - Response

P314 Get medical advice/attention if you feel unwell.

P391 Collect spillage.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 If eye irritation persists: Get medical advice/attention.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P362 Take off contaminated clothing and wash before re-use.

Precautionary statement - Disposal P501 In the case of a substance that is in compliance with a HSNO approval other than a Part 6A (Group Standards) approval, a label must provide a

description of one or more appropriate and achievable methods for the disposal

of a substance in accordance with the Hazardous Substances (Disposal)

Regulations 2001. This may also include any method of disposal that must be

avoided. See Section 13 for disposal details.

3. Composition/information on ingredients

Ingredients	Name	CAS	Proportion
	Bisphenol A epoxy resin	25068-38-6	>50-100 %
	C12-C14 Glycidyl ether	68609-97-2	10-30 %
	Formaldehyde, polymer with (chloromethyl)oxirane and phenol	9003-36-5	0-<30 %
	Phenol, polymer with formaldehyde, glycidyl ether	28064-14-4	0-<30 %

4. First-aid measures

Inhalation If inhaled, remove affected person from contaminated area. Keep at rest until recovered. If symptoms persist seek medical attention. Do NOT induce vomiting. Wash out mouth with water. Seek medical attention. Ingestion Skin Wash affected area thoroughly with soap and water. Remove contaminated clothing and wash before reuse or discard. Seek medical attention. Eye contact If in eyes, hold eyelids apart and flush the eyes continuously with running water. Continue flushing for several minutes until all contaminants are washed out completely. Seek medical attention. First Aid Facilities Eye wash, safety shower and normal washroom facilities. Advice to Doctor Treat symptomatically. Other Information For advice, contact a Poisons Information Centre (Phone eq Australia 131 126; New Zealand 0800 764 766) or a doctor (at once).

5. Fire-fighting measures

Use carbon dioxide, dry chemical, foam, water fog or water spray. Suitable extinguishing media

Hazards from Combustion **Products**

Under fire conditions this product may emit toxic and/or irritating fumes including carbon monoxide and carbon dioxide.

Print Date: 23/08/2012 CS: 1.6.21





3 of 6 Page:

Infosafe No™ LPWTO Issue Date : August 2012 ISSUED by PARCHEMN

FOSROC NITOMORTAR 903 BASE Product Name

Classified as hazardous

Specific hazards arising from the chemical

Combustible liquid. This product will readily burn under fire conditions.

Hazchem Code • 37

Precautions in connection with Fire

Fire-fighters should wear full protective clothing and self contained breathing apparatus (SCBA) operated in positive pressure mode. Water spray may be used to keep fire exposed containers cool.

6. Accidental release measures

Emergency **Procedures**

Wear appropriate personal protective equipment and clothing to prevent exposure. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unprotected personnel. If possible contain the spill. Place inert absorbent, non-combustible material onto spillage. Use clean non-sparking tools to collect the material and place into suitable labelled containers for subsequent recycling or disposal. Dispose of waste according to the applicable local and national regulations. If contamination of sewers or waterways occurs inform the local water and waste management authorities in accordance with local regulations.

7. Handling and storage

Precautions for Safe Handling

Use only in a well ventilated area. Keep containers sealed when not in use. Prevent the build up of mists or vapours in the work atmosphere. Avoid inhalation of vapours and mists, and skin or eye contact. Do not use near ignition sources. Do not pressurise, cut, heat or weld containers as they may contain hazardous residues. Maintain high standards of personal hygiene i.e. Washing hands prior to eating, drinking, smoking or using toilet facilities. Store in a cool, dry well-ventilated area away from heat, sources of ignition, oxidising agents, foodstuffs, and clothing and out of direct sunlight. Keep containers closed when not in use and securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Do NOT pressurise, cut, heat or weld containers as they may contain hazardous residues. For information on the design of the storeroom, reference should be made to Australian Standard AS1940 - The storage and handling of flammable and combustible liquids. Reference should also be made to all State and Federal regulations.

storage, including any incompatabilities

Conditions for safe

8. Exposure controls/personal protection

Occupational exposure limit values No exposure standards have been established for the mixture by the Occupational Safety and Health Service (OSH) of the New Zealand Department of Labour. However, over-exposure to some industrial chemicals may result in enhancement of pre-existing adverse medical conditions and/or allergic reactions and should be kept to the least possible levels. No biological limit allocated.

Biological Limit Values

Appropriate engineering controls

Use with good general ventilation. If mists or vapours are produced local exhaust ventilation should be used.

Respiratory Protection

If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable organic vapour/mist filter should be used. Reference should be made to Australian Standards AS/NZS 1715, Selection, Use and maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes

Eye Protection

for individual circumstances. Safety glasses with side shields or chemical goggles should be worn. Final choice of appropriate eye/face protection will vary according to individual circumstances. Eye protection devices should conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors for Industrial Applications. Wear gloves of impervious material. Final choice of appropriate gloves will

Hand Protection

vary according to individual circumstances i.e. methods of handling or according to risk assessments undertaken. Reference should be made to ${\tt AS/NZS}$ 2161.1: Occupational protective gloves - Selection, use and maintenance.

Body Protection

Suitable workwear should be worn to protect personal clothing, eg cotton overalls buttoned at neck and wrist. When large quantities are handled the use of plastic aprons and rubber boots is recommended.

Print Date: 23/08/2012 CS: 1.6.21





Page: 4 of 6

Infosafe No™ LPWTO Issue Date : August 2012 ISSUED by PARCHEMN

Product Name FOSROC NITOMORTAR 903 BASE

Classified as hazardous

9. Physical and chemical properties

Appearance Clear, light yellow liquid.

Odour Mild odour Melting Point Not available

Boiling Point >200°C

Solubility in Water Insoluble

Specific Gravity 1.12 at 25°C

pH Not available

Vapour Pressure Not available

Vapour Density
(Air=1)

Not available

Odour Threshold

Not available

Viscosity 600 - 900 mPas @ 25°C

Partition Coefficient:

n-octanol/water

Not available

Flash Point

>155°C (Pensky Martens Closed Cup) (DIN 51758)

Flammability Combustible

Auto-Ignition Not available

Temperature

Flammable Limits - Not available

Lower

Flammable Limits - Not available

Upper

10. Stability and reactivity

Chemical Stability Stable under normal conditions of handling and storage.

Incompatible

Strong acids, strong bases, strong oxidisers.

Materials

Hazardous Thermal decomposition may result in the release of toxic and/or irritating

Decomposition fumes including carbon monoxide and carbon dioxide.

Products

Hazardous Will not occur.

Polymerization

11. Toxicological Information

Information

Acute Toxicity - Oral LD50 (oral, rat): >5000 mg/kg

vomiting and possible abdominal pain.

Inhalation Inhalation of product vapours may cause irritation of the nose, throat and

respiratory system. Symptoms of exposure can include sneezing and coughing. Irritating to skin resulting in redness and itching. May cause an allergic

skin reaction.

Eye Irritating to eyes. On eye contact this product will cause tearing, stinging,

blurred vision, and redness.

Respiratory

Not expected to be a respiratory sensitiser.

sensitisation

Skin

 ${\bf Skin \, Sensitisation} \qquad \qquad {\tt May \, \, cause \, \, an \, \, allergic \, \, skin \, \, reaction.}$

Germ cell Not considered to be a mutagenic hazard.

mutagenicity

Frint Date: 23/08/2012 CS: 1.6.21





Page: 5 of 6

Infosafe No^{TM} LPWTO Issue Date : August 2012 ISSUED by PARCHEMN

Product Name FOSROC NITOMORTAR 903 BASE

Classified as hazardous

Carcinogenicity Not considered to be a carcinogenic hazard.

Reproductive Not considered to be toxic to reproduction.

Toxicity

STOT-single Not expected to cause damage to organs.

exposure

STOT-repeated May cause damage to organs through prolonged or repeated exposure by skin

exposure contact.

Aspiration Hazard Not expected to be an aspiration hazard.

12. Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

Persistence and

Not available

degradability Mobility

Not available

Bioaccumulative

Not available

Potential Environmental

Do not discharge the product into drains, waterways or sewers.

Protection

13. Disposal considerations

Disposal Considerations

Product Disposal:

Product wastes are controlled wastes and should be disposed of in accordance with all applicable local and national regulations. This product can be disposed through a licensed commercial waste collection service. It can be disposed by burning in an approved high temperature incineration facility; or alternatively, it can be reacted with the catalyst/hardener component to enable it to cure to an inert solid that can be disposed in a licensed landfill facility.

Personal protective clothing and equipment as specified in Section 8 of this SDS must be worn during handling and disposal of this product. The ventilation requirements as specified in the same section must also be followed, and the precautions given in Section 7 of this SDS regarding handling must also be followed.

Do not dispose into the sewerage system. Do not discharge into drains or watercourses or dispose where ground or surface waters may be affected. In New Zealand, the disposal agency or contractor must comply with the New Zealand Hazardous Substances (Disposal) Regulations 2001. Further details regarding disposal can be obtained on the ERMA New Zealand website under specific group standards.

Container Disposal:

The container or packaging must be cleaned and rendered incapable of holding any substance. It can then be disposed of in a manner consistent with that of the substance it contained. In this instance the packaging can be disposed through a commercial waste collection service.

Alternatively, the container or packaging can be recycled if the hazardous residues have been thoroughly cleaned or rendered non-hazardous. In New Zealand, the packaging (that may or may not hold any residual substance) that is lawfully disposed of by householders or other consumers through a public or commercial waste collection service is a means of compliance with regulations.

14. Transport information

Transport Information

Road and Rail Transport:

This material is classified as a Class 9 - Miscellaneous Substances according to NZS 5433:2012 Transport of Dangerous Goods on Land.

Must not be loaded in the same freight container or on the same vehicle with: - Class 1, Explosives

Class 9 dangerous goods that contain organic matter must not be loaded in the same bulk container or tankwagon with dangerous goods of Division 5.1 unless the Class 9 and Division 5.1 dangerous goods are in separate compartments of a bulk container or tankwagon.

Print Date: 23/08/2012 CS: 1.6.21





Page: 6 of 6

Infosafe No™ LPWTO Issue Date : August 2012 ISSUED by PARCHEMN

Product Name FOSROC NITOMORTAR 903 BASE

Classified as hazardous

Goods of packing group II or III may be loaded in the same freight container or on the same vehicle if transported in segregation devices. Segregation devices may be used to segregate Dangerous goods of Class 9 when the nature of those dangerous goods requires them to be segregated from dangerous goods of Class 3, 4, 5, 6 or 8 or from food items.

Marine Transport (IMO/IMDG):

Classified as Dangerous Goods by the criteria of the International Maritime

Dangerous Goods Code (IMDG Code) for transport by sea.

UN No.: 3082

Proper Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(CONTAINS BISPHENOL A EPOXY RESIN)

DG Class: 9

Packaging Group: III EMS No.: F-A, S-F

Air Transport (ICAO/IATA):

Classified as Dangerous Goods by the criteria of the International Air

Transport Association (IATA) Dangerous Goods Regulations for transport by air.

UN No: 3082

Proper Shipping Name: : Environmentally hazardous substance, liquid, n.o.s.

(Contains Bisphenol A Epoxy Resin)

Class: 9

Packing Group: III Label: Miscellaneous

Packing Instruction: 964 (For passenger and cargo aircraft)

Packing Instruction: 964 (For cargo aircraft only)

U.N. Number 3082

UN proper shipping

nama

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. - (CONTAINS BISPHENOL A

EPOXY RESIN)

Transport hazard

class(es) Hazchem Code

•3z

Packing Group III EPG Number 9C1 IERG Number 47

IMDG Marine pollutant

Yes

15. Regulatory information

Regulatory Information Classified as Hazardous according to the Hazardous Substances (Minimum degrees

of hazard) Regulations 2001.

Group Standard:

Construction Products (Subsidiary Hazard) Group Standard 2006

HSNO Approval

Number

HSR002544

16. Other Information

Date of preparation or last revision of

SDS Reviewed: August 2012, Supersedes: September 2007

SDS

Contact Person/Point Technical Support

Technical Support: 1800 812 864

...End Of MSDS...

© Copyright ACOHS Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe MSDS displayed is the intellectual property of Acohs Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe MSDS displayed is the intellectual property of Acohs Pty Ltd. The compilation of MSDS's displayed is the intellectual property of Acohs Pty Ltd.

Copying of any MSDS displayed is permitted for personal use only and otherwise is not permitted. In particular the MSDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of MSDS without the express written consent of Acohs Pty Ltd.

Print Date: 23/08/2012 CS: 1.6.21