

Infosafe No™ LPWHT	Issue Date : June 2012	ISSUED by PARCHEMC
--------------------	------------------------	--------------------

Product Name : **LUSTRESEAL ACRYLIC MATT SEALER**

Classified as hazardous

1. Identification

GHS Product Identifier	LUSTRESEAL ACRYLIC MATT SEALER
Company Name	Parchem Construction Supplies Pty Ltd (ABN 80 069 961 968)
Address	7 Lucca Road Wyong NSW 2259 Australia
Telephone/Fax Number	Tel: 02 4350 5000 Fax: 02 4351 2024
Emergency phone number	1800 638 556 (available 24/7)
Recommended use of the chemical and restrictions on use	Concrete and masonry coatings.
Other Information	<p>This SDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since Parchem Construction Supplies Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this MSDS in the context of how the user intends to handle and use the product in the workplace.</p> <p>If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company. Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.</p> <p>www.parchem.com.au</p>

2. Hazard Identification

Classification of the substance or mixture	<p>Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia.</p> <p>Classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)</p> <p>Flammable Liquids: Category 3 Acute Toxicity - Dermal: Category 4 Acute Toxicity - Inhalation: Category 4 Skin Corrosion/Irritation: Category 2 Eye Damage/Irritation: Category 2A STOT Single Exposure Category 3 (respiratory tract irritation) Aspiration Hazard: Category 1 Hazardous to the Aquatic Environment - Acute Hazard: Category 2 Hazardous to the Aquatic Environment - Long-Term Hazard: Category 2</p>
Signal Word (s)	Danger
Hazard Statement (s)	H226: Flammable liquid and vapour. H312: Harmful in contact with skin. H332: Harmful if inhaled. H315: Causes skin irritation. H319: Causes serious eye irritation. H335: May cause respiratory irritation. H304: May be fatal if swallowed and enters airways. H411: Toxic to aquatic life with long lasting effects.
Pictogram (s)	Flame, Exclamation mark, Health hazard, Environment



Infosafe No™ LPWHT	Issue Date : June 2012	ISSUED by PARCHEMC
--------------------	------------------------	--------------------

Product Name : **LUSTRESEAL ACRYLIC MATT SEALER**

Classified as hazardous

Precautionary statement – Prevention	<p>P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.</p> <p>P233: Keep container tightly closed.</p> <p>P240: Ground/bond container and receiving equipment.</p> <p>P241: Use explosion-proof electrical/ventilating/lighting/.../equipment.</p> <p>P242: Use only non-sparking tools.</p> <p>P243: Take precautionary measures against static discharge.</p> <p>P261: Avoid breathing dust/fume/gas/mist/vapours/spray.</p> <p>P264: Wash skin thoroughly after handling.</p> <p>P271: Use only outdoors or in a well-ventilated area.</p> <p>P273: Avoid release to the environment.</p> <p>P280b: Wear protective gloves/eye protection/face protection.</p>
Precautionary statement – Response	<p>GENERAL:</p> <p>P370+P378: In case of fire: Use foam, carbon dioxide or dry chemical powder to extinguish.</p> <p>P312: Call a POISON CENTER/doctor if you feel unwell.</p> <p>P391: Collect spillage.</p> <p>SKIN:</p> <p>P302+P352: IF ON SKIN: Wash with plenty of water.</p> <p>P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.</p> <p>P362+P364: Take off contaminated clothing and wash it before reuse.</p> <p>P332+P313: If skin irritation occurs: Get medical advice/attention.</p> <p>INHALATION:</p> <p>P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.</p> <p>EYES:</p> <p>P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing.</p> <p>P337+P313: If eye irritation persists: Get medical advice/attention.</p> <p>INGESTION:</p> <p>P301+P310: IF SWALLOWED: Immediately call a POISON CENTER/doctor.</p> <p>P331: Do NOT induce vomiting.</p>
Precautionary statement – Storage	<p>P403+P235: Store in a well-ventilated place. Keep cool.</p> <p>P403+P233: Store in a well-ventilated place. Keep container tightly closed.</p> <p>P405: Store locked up.</p>
Precautionary statement – Disposal	<p>P501 Dispose of contents/container to an approved waste disposal plant.</p>

3. Composition/information on ingredients

Ingredients	Name	CAS	Proportion
	Solvent naphtha (petroleum), light aromatic	64742-95-6	35-50 %
	Xylene	1330-20-7	35-50 %
	Ingredients determined not to be hazardous.		Balance

4. First-aid measures

Inhalation	If inhaled, remove affected person from contaminated area. Apply artificial respiration if not breathing. Seek medical attention.
Ingestion	Do NOT induce vomiting. Wash out mouth and lips with water. Where vomiting occurs naturally have affected person place head below hip level in order to reduce risk of aspiration. Seek immediate medical attention.
Skin	Wash affected area thoroughly with soap and water. Remove contaminated clothing and wash before reuse or discard. Seek medical attention.
Eye contact	If in eyes, hold eyelids apart and flush the eyes continuously with running water. Continue flushing for several minutes until all contaminants are washed out completely. Seek medical attention.
First Aid Facilities	Eye wash, safety shower and normal washroom facilities.
Advice to Doctor	Treat symptomatically.
Other Information	For advice in an emergency, contact a Poisons Information Centre (Phone Australia 13 1126) or a doctor at once.

Infosafe No™ LPWHT Issue Date : June 2012 ISSUED by PARCHEMC

Product Name : **LUSTRESEAL ACRYLIC MATT SEALER**

Classified as hazardous

5. Fire-fighting measures

Suitable extinguishing media Use carbon dioxide, dry chemical, foam or water mist.

Unsuitable Extinguishing Media DO NOT USE water jets.

Hazards from Combustion Products Under fire conditions this product may emit toxic and/or irritating fumes including carbon monoxide and carbon dioxide.

Specific hazards arising from the chemical Flammable liquid and vapour. Vapour/air mixtures may ignite explosively. Flashback along the vapour trail may occur. Runoff to sewer may create fire or explosion hazard.

Hazchem Code •3Y

Precautions in connection with Fire Fire fighters should wear Self-Contained Breathing Apparatus (SCBA) operated in positive pressure mode and full protective clothing to prevent exposure to vapours or fumes. Water spray may be used to cool down heat-exposed containers. Fight fire from safe location. This product should be prevented from entering drains and watercourses.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Wear appropriate personal protective equipment and clothing to prevent exposure. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unprotected personnel. If possible contain the spill. Place inert absorbent, non-combustible material onto spillage. Use clean non-sparking tools to collect the material and place into suitable labelled containers for subsequent recycling or disposal. Dispose of waste according to the applicable local and national regulations. If contamination of sewers or waterways occurs inform the local water and waste management authorities in accordance with local regulations.

7. Handling and storage

Precautions for Safe Handling Avoid contact with skin and eyes. Wear overalls, impervious gloves and safety glasses. Use in designated areas with adequate ventilation. Use approved flammable liquid storage containers in the work area. Prevent release of vapours and mists into workplace air. Keep containers closed when not in use. Take precautionary measures against static discharges. Keep material away from sparks, flames and other ignition sources. Do not empty into drains. Ensure a high level of personal hygiene is maintained when using this product, that is, always wash hands before eating, drinking, smoking or using the toilet facilities.

Conditions for safe storage, including any incompatibilities Store in a cool, dry, well-ventilated area away from sources of ignition, oxidising agents, strong acids, foodstuffs, and clothing. Keep containers closed when not in use and securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Have appropriate fire extinguishers available in and near the storage area. Take precautions against static electricity discharges. Use proper grounding procedures. For information on the design of the storeroom, reference should be made to Australian Standard AS1940 - The storage and handling of flammable and combustible liquids. Reference should also be made to all applicable local and national regulations.

8. Exposure controls/personal protection

Occupational exposure limit values No exposure value assigned for this specific material by the Safe Work, Australia. However, the available exposure limits for ingredients are listed below:

Substance	TWA		STEL		NOTICES
	ppm	mg/m ³	ppm	mg/m ³	
Xylene	80	350	150	655	-

TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eight-hour working day, for a five-day week.

Infosafe No™ LPWHT	Issue Date : June 2012	ISSUED by PARCHEMC
--------------------	------------------------	--------------------

Product Name : **LUSTRESEAL ACRYLIC MATT SEALER**

Classified as hazardous

Biological Limit Values	<p>STEL (Short Term Exposure Limit): The average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.</p> <p>Biological Exposure Indice (BEI) from American Conference of Industrial Hygienists (ACGIH) for ingredients are as follows:</p> <table border="1"> <thead> <tr> <th>Determinant</th> <th>Sampling Time</th> <th>Biological Exposure Indice (BEI)</th> </tr> </thead> <tbody> <tr> <td>XYLENE [1330-20-7]</td> <td></td> <td></td> </tr> <tr> <td>Methylhippuric acids in urine</td> <td>End of shift</td> <td>1.5mg/g creatinine</td> </tr> <tr> <td></td> <td>shift of work week</td> <td></td> </tr> </tbody> </table>	Determinant	Sampling Time	Biological Exposure Indice (BEI)	XYLENE [1330-20-7]			Methylhippuric acids in urine	End of shift	1.5mg/g creatinine		shift of work week	
Determinant	Sampling Time	Biological Exposure Indice (BEI)											
XYLENE [1330-20-7]													
Methylhippuric acids in urine	End of shift	1.5mg/g creatinine											
	shift of work week												
Appropriate engineering controls	<p>Provide sufficient ventilation to keep airborne levels below the exposure limits. Where vapours or mists are generated, particularly in enclosed areas, and natural ventilation is inadequate, a flameproof exhaust ventilation system is required. Refer to AS 1940 - The storage and handling of flammable and combustible liquids and AS/NZS 60079.10.1:2009 Explosive atmospheres - Classification of areas - Explosive gas atmospheres, for further information concerning ventilation requirements.</p>												
Respiratory Protection	<p>If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable organic vapour filter should be used. Reference should be made to Australian/New Zealand Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.</p>												
Eye Protection	<p>Safety glasses with side shields or chemical goggles should be worn. Final choice of appropriate eye/face protection will vary according to individual circumstances. Eye protection devices should conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors for Industrial Applications.</p>												
Hand Protection	<p>Wear gloves of impervious material, such as laminated film or nitrile. Final choice of appropriate gloves will vary according to individual circumstances i.e. methods of handling or according to risk assessments undertaken. Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.</p>												
Body Protection	<p>Suitable protective work wear, e.g. cotton overalls buttoned at neck and wrist is recommended. Chemical resistant apron is recommended where large quantities are handled.</p>												

9. Physical and chemical properties

Appearance	Clear, colourless viscous liquid
Odour	Aromatic solvent odour
Melting Point	Not available
Boiling Point	136°C-182°C
Solubility in Water	Immiscible
pH	Not available
Vapour Pressure	8-12 hPa at 20°C (xylene)
Vapour Density (Air=1)	Not available
Odour Threshold	Not available
Partition Coefficient: n-octanol/water	Not available
Density	0.91
Flash Point	24°C
Flammability	Flammable
Auto-Ignition Temperature	Not available
Flammable Limits - Lower	0.01%

Infosafe No™ LPWHT	Issue Date : June 2012	ISSUED by PARCHEMC
--------------------	------------------------	--------------------

Product Name : **LUSTRESEAL ACRYLIC MATT SEALER**

Classified as hazardous

Flammable Limits - Upper 7.1%
Dynamic Viscosity 10-30 mPas at 25°C

10. Stability and reactivity

Chemical Stability Stable under normal conditions of storage and handling.
Conditions to Avoid Heat, flames and other ignition sources.
Incompatible Materials Strong oxidising agents.
Hazardous Decomposition Products Thermal decomposition may result in the release of toxic and/or irritating fumes including carbon monoxide and carbon dioxide.
Hazardous Polymerization Will not occur.

11. Toxicological Information

Toxicology Information No toxicology data available for this product.
Ingestion Harmful-may cause lung damage if swallowed. Small amounts of liquid aspirated into the respiratory system during ingestion or from vomiting may cause severe pulmonary injury that may lead to death. May cause irritation to the mouth, throat, esophagus and stomach with symptoms of nausea, abdominal discomfort, vomiting and diarrhoea.
Inhalation Harmful by inhalation. Inhalation of product vapours can cause irritation of the nose, throat and respiratory system.
Skin Irritating to skin. Skin contact will cause redness, itching and swelling. Repeated exposure may cause skin dryness and cracking and may lead to dermatitis.
Eye Harmful in contact with skin. Product can be absorbed through skin with resultant harmful systemic effects. Irritating to eyes. On eye contact this product will cause tearing, stinging, blurred vision, and redness.
Respiratory sensitisation Not expected to be a respiratory sensitiser.
Skin Sensitisation Not expected to be a skin sensitiser.
Germ cell mutagenicity Not considered to be a mutagenic hazard.
Carcinogenicity Not considered to be a carcinogenic hazard.
Reproductive Toxicity Not considered to be toxic to reproduction.
STOT-single exposure May cause respiratory irritation.
STOT-repeated exposure Not expected to cause damage to organs.
Aspiration Hazard May be fatal if swallowed and enters airways.

12. Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.
Persistence and degradability Not available
Mobility Not available
Bioaccumulative Potential Not available
Environmental Protection Do not discharge this material into waterways, drains and sewers.
Acute Toxicity - Fish Xylene (mixed isomers):
LC50 (Fathead minnow): 13.4 mg/L/96h

Infosafe No™ LPWHT	Issue Date : June 2012	ISSUED by PARCHEMC
--------------------	------------------------	--------------------

Product Name : **LUSTRESEAL ACRYLIC MATT SEALER**

Classified as hazardous

13. Disposal considerations

Disposal Considerations Do not allow into drains or watercourses or dispose of where ground or surface waters may be affected. Wastes including emptied containers are controlled wastes and should be disposed of in accordance with all applicable local and national regulations.

14. Transport information

Transport Information This material is a Class 3 - Flammable Liquid according to The Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)
 Class 3 - Flammable Liquids are incompatible in a placard load with any of the following:
 - Class 1, Explosives
 - Division 2.1, Flammable Gases, (Division 2.1 and Class 3 are incompatible in transport if both are in tanks or other receptacles with a capacity individually exceeding 500 L.)
 - Division 2.3, Toxic Gases
 - Division 4.2 Spontaneously Combustible Substances
 - Division 5.1 Oxidising Agents and Division 5.2, Organic Peroxides
 - Class 6 Toxic or Infectious Substances (where the flammable liquid is nitromethane)
 - Class 7 Radioactive Substances.

Marine Transport (IMO/IMDG):
 Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

UN No.: 1866
 Proper Shipping Name: RESIN SOLUTION (Solvent naphtha (petroleum), light aromatic) MARINE POLLUTANT
 DG Class: 3
 Packaging Group: III
 EMS No.: F-E, S-E
 Special provisions: 223, 955

Air Transport (ICAO/IATA):
 Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

UN No: 1866
 Proper Shipping Name: : Resin solution
 Class: 3
 Packing Group: III
 Label: Miscellaneous
 Packing Instruction: 355 (For passenger and cargo aircraft)
 Packing Instruction: 366 (For cargo aircraft only)
 Special provisions: A3

U.N. Number	1866
UN proper shipping name	RESIN SOLUTION
Transport hazard class(es)	3
Hazchem Code	•3Y
Packing Group	III
EPG Number	3A1
IERG Number	14
IMDG Marine pollutant	Yes

15. Regulatory information

Regulatory Information Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia

Infosafe No™ LPWHT	Issue Date : June 2012	ISSUED by PARCHEMC
--------------------	------------------------	--------------------

Product Name : **LUSTRESEAL ACRYLIC MATT SEALER**

Classified as hazardous

Poisons Schedule

Classified as a Scheduled Poison according to the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).
S5

16. Other Information

Date of preparation MSDS amendment: June 2014, SECTION 14
or last revision of MSDS Reviewed: June 2012
SDS Supersedes: July 2007
Contact Person/Point Technical Support: 1800 812 864

...End Of MSDS...

© Copyright ACOHS Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe MSDS displayed is the intellectual property of Acohs Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe MSDS displayed is the intellectual property of Acohs Pty Ltd.
The compilation of MSDS's displayed is the intellectual property of Acohs Pty Ltd.

Copying of any MSDS displayed is permitted for personal use only and otherwise is not permitted. In particular the MSDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of MSDS without the express written consent of Acohs Pty Ltd.