

Liquid Nails Direct Stick Remover

Adhesive remover

Description

Liquid Nails Direct Stick Remover is a special, slightly gelled, solvent to aid removal of Polyurethane adhesives. It is available in a 500mL tin.

Uses

- For removing *Selleys Liquid Nails Direct Stick* timber flooring adhesives from suitable hard UV or heat cured pre-finished wooden flooring, steel trowels and other tools.
- Suitable for wiping over pre-finished flooring during installation so that any surface contamination by these adhesives can be more easily removed at a later time with this remover.
- An effective stripper for removing cured *Selleys Liquid Nails Direct Stick* timber flooring adhesives from metal application tools and woodcutting tools.

Features/Advantages

- Light gel consistency
- Supplied ready to use
- Powerful softening of one-part room temperature cured polyurethane adhesives.
- Does not damage most hardwearing UV and heat cured coatings on pre-finished timber flooring
- Slow evaporating

Instructions for Use/Application Instructions

- Shake can before opening to ensure the contents are uniform. Wear solvent resistant gloves.
- Spread out a tissue trimmed to a size larger than the adhesive smeared area.
- Pour or spoon remover onto the centre of the tissue until it is completely soaked and flattened down to be in contact all over the surface. Allow to soak up to 4 hours or overnight.
- If possible, cover with an up-turned bowl or similar, to reduce evaporation.
- After soaking, lift off the still soaking tissue, and use only the special plastic scraper provided to scrape off the adhesive. Start scraping from an area where there is no adhesive to ensure the scraper edge is flat on the pre-finished timber surface.
- Holding scraper hard to the surface, scrape the softened adhesive to lift it off the surface.
- Thick films of adhesive may require longer soaking or more than one treatment.
- Once all the cured adhesive is scraped off, clean residues of Remover from the surface with a dilute solution of suitable detergent and wipe dry.

Technical Data/Properties

Contact Selleys before using this data for the setting of specifications.

Property	Typical Result
Shelf Life	24 months
Technology	Hydrocarbon solvent
VOC	

Important Notes/Limitations

- Remover will damage the ability of *Selleys Liquid Nails Direct Stick* timber flooring adhesives to cure and adhere properly.
- Do not contaminate surfaces that will require adhesive to be bonded to it.
- Do not allow *Remover* to run down board joints and damage the adhesive beneath.
- Pre-test on surfaces first. This product is only suitable for use on hard UV or heat cured urethane pre-finishes. It may damage other finishes.
- Remover will damage 1k and 2k urethane timber furniture and flooring finishes.

- Timber soaked or wet with *Remover* will not be suitable for bonding with Selleys Liquid Nails Direct Stick timber flooring adhesives.
- Use only the special plastic scraper provided. Use of metal scrapers may cause irreparable damage to the underlying finish.

Storage

Store unopened tin below 30°C in a cool dry place away from direct sunlight. Unopened tin can be stored for 24 months from the date of manufacture.

Safety

No special personal protective equipment required. Wash hands after use. Rubber gloves are recommended if handling often.

Not classified as Dangerous Goods.

Not classified as Hazardous.

Refer to Safety Data Sheet for more detailed information.

Clean up

Liquid Nails Direct Stick Remover is slow evaporating and leaves an oily film which can remain on surfaces for some days. This residue can be very slippery and may soften the surface and hence allow it to be damaged before the Remover has totally evaporated. Wipe up spills immediately with dry cloth or paper towels and then clean the surface with a dilute solution of suitable detergent and wipe dry.

Disclaimer

All information contained in this Product Information Sheet is as accurate and up-to-date as possible. Products can be expected to perform as indicated in this Sheet, so long as application procedures are followed as recommended. Notwithstanding the above, any recommendations made by Selleys or its distributors in relation to this or other products is to be taken as advice only. Selleys makes no representations or warranties that this product will be suitable for use. Subject to any applicable legislation which cannot be excluded (such as the Australian Consumer Law), Selleys takes no responsibility and will not be liable for any failure in performance of this product or any losses, damages, or injuries (consequential or otherwise) arising from the storage, mixing, application or other use of this product or for any representations made by you about the product which have not been approved in writing by Selleys. The buyer assumes all risk and responsibility for the use of this product.

© 2013 **Selleys** Pty Limited

Selleys – a division of DuluxGroup Australia Pty Ltd

1 Gow Street, Padstow, NSW 2211

1300 555 205 (Australia)

0800 735 539 (New Zealand)