

Colour tint for LustreSeal Acrylic, Matt Finish and Extended Wear Plus sealers

Application

- Applicable ONLY to 20L sealers
- Replace 1L of LustreSeal sealer with selected 1L LustreSeal Tint
- Mix thoroughly with a hand paddle for 3-4 minutes
- When applying coloured sealer, a paint tray and solvent resistant lambswool roller must be used
- For application of sealer, refer to relative LustreSeal Sealer TDS.

Specifications

Solids:	30 – 60% by weight depending on colour.
UV Resistance:	Very Good
Solubility:	Not dispersible in water (dispersible in most paint type solvents).

Uses

When mixed with the LustreSeal range:

- Re-colour plain or decorative concrete surfaces.
- Re-fresh coloured concrete

Features

- Affordable alternative to concrete/paver paint
- Mask blemished concrete

Colour

Available in all colours to match Parchem's decorative concrete colour range.

Usage Rate

1 Litre LustreSeal tint per 20L LustreSeal solvent based sealer.

Supply

1 litre can.

Limitations

- Where possible, matching batch numbers to be used.
- Not for use with Waterbased sealers.

Storage

Store in cool, dry conditions.

Shelf Life

18 months, if kept unopened and stored in cool, dry conditions. After this time, product should be checked to ensure its suitability for use.

LustreSeal®

Coloured Sealer Tints

Important notice

A Safety Data Sheet (SDS) and Technical Data Sheet (TDS) are available from the Parchem website or upon request from the nearest Parchem sales office. Read the SDS and TDS carefully prior to use as application or performance data may change from time to time. In emergency, contact any Poisons Information Centre (phone 13 11 26 within Australia) or a doctor for advice.

Product disclaimer

This Technical Data Sheet (TDS) summarises our best knowledge of the product, including how to use and apply the product based on the information available at the time. You should read this TDS carefully and consider the information in the context of how the product will be used, including in conjunction with any other product and the type of surfaces to, and the manner in which, the product will be applied. Our responsibility for products sold is subject to our standard terms and conditions of sale. Parchem does not accept any liability either directly or indirectly for any losses suffered in connection with the use or application of the product whether or not in accordance with any advice, specification, recommendation or information given by it.

LUSTRESEAL



Parchem Construction Supplies Pty Ltd
7 Lucca Road, Wyong NSW 2259
Phone: 1300 737 787
www.parchem.com.au
ABN 80 069 961 968

Distributed in New Zealand by: Concrete Plus Ltd
23 Watts Rd, Sockburn 8042 Ph: 03 343 0090