

Infosafe No™ LPXJM Issue Date : February 2012 ISSUED by PARCHEMN

Product Name : **MASTERSHIELD UA20 PART A**

Classified as hazardous

1. Identification

GHS Product Identifier MASTERSHIELD UA20 PART A
Company Name Parchem Construction Supplies Pty Ltd (ABN 80 069 961 968)
Address 7 Lucca Road Wyong
NSW 2259 Australia
Telephone/Fax Number Tel: 02 4350 5000
Fax: 02 4351 2024
Emergency phone number 0800 154 666 (available 24/7)
Recommended use of the chemical and restrictions on use Part of a two pack urethane coating.
Other Information Distributed in New Zealand by:
Concrete Plus
23 Watts Road
Sockburn
New Zealand
Tel: (03) 343 0090
Fax: (03) 343 0202

This MSDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since Parchem Construction Supplies Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this MSDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company. Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.

www.parchem.co.nz

2. Hazard Identification

GHS classification of the substance/mixture Classified as Hazardous according to the New Zealand Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001.
Classified as Dangerous Goods for transport according to the New Zealand Standard NZS 5433:2007 Transport of Dangerous Goods on Land.
3.1C - Flammable liquids: medium hazard
6.1D (Dermal) - Substance that is acutely toxic
6.1D (Inhalation - vapours, dusts or mists) - Substance that is acutely toxic
6.1E (Oral) - Substance that is acutely toxic
6.3A - Substance that is irritating to the skin
6.4A - Substance that is irritating to the eyes
6.5B - Substance that is a contact sensitiser
6.7B - Substance that is a suspected human carcinogen
6.8B - Substance that is suspected to be a human reproductive or developmental toxicant
6.9B (Repeated exposure) - Substance that is harmful to human target organs or systems (ingestion and inhalation)
9.1D - Substance that is slightly harmful to the aquatic environment or is otherwise designed for biocidal action
9.3C - Substance that is harmful to terrestrial vertebrates

Signal Word (s) Warning

Hazard Statement (s) H226 Flammable liquid and vapour.
H303 May be harmful if swallowed.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.

Infosafe No™ LPXJM Issue Date : February 2012 ISSUED by PARCHEMN

Product Name : **MASTERSHIELD UA20 PART A**

Classified as hazardous

H319 Causes serious eye irritation.
 H332 Harmful if inhaled.
 H351 Suspected of causing cancer
 H361 Suspected of damaging fertility or the unborn child
 H373 May cause damage to organs through prolonged or repeated exposure
 H402 Harmful to aquatic life.
 H433 Harmful to terrestrial vertebrates.
 Flame, Health hazard, Exclamation mark,

Pictogram (s)



Precautionary statement – Prevention

P102 Keep out of reach of children.
 P103 Read label before use.
 P104 Read Safety Data Sheet before use.
 P201 Obtain special instructions before use.
 P202 Do not handle until all safety precautions have been read and understood.
 P210 Keep away from heat/sparks/open flames/hot surfaces
 P233 Keep container tightly closed.
 P240 Ground/bond container and receiving equipment.
 P241 Use explosion-proof electrical/ventilating/lighting/equipment.
 P242 Use only non-sparking tools.
 P243 Take precautionary measures against static discharge.
 P260 Do not breathe dust/fume/gas/mist/vapours/spray.
 P264 Wash skin thoroughly after handling.
 P271 Use only outdoors or in a well-ventilated area.
 P272 Contaminated work clothing should not be allowed out of the workplace.
 P273 Avoid release to the environment.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statement – Response

P101 If medical advice is needed, have product container or label at hand.
 P308+P313 IF exposed or concerned: Get medical advice/ attention.
 P314 Get medical advice/attention if you feel unwell.
 P370+P378 In case of fire: Use Foam, carbon dioxide or dry chemical powder.
 INGESTION
 P331 Do NOT induce vomiting.

INHALATION

P304+P340 IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

EYES

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

SKIN

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P362 Take off contaminated clothing and wash before re-use.

P405 Store locked up.

P403+P235 Store in a well-ventilated place. Keep cool.

Precautionary statement – Storage

Precautionary statement – Disposal

P501 In the case of a substance that is in compliance with a HSN0 approval other than a Part 6A (Group Standards) approval, a label must provide a description of one or more appropriate and achievable methods for the disposal of a substance in accordance with the Hazardous Substances (Disposal) Regulations 2001. This may also include any method of disposal that must be avoided. See Section 13 for disposal details.

3. Composition/information on ingredients

Ingredients	Name	CAS	Proportion
	Xylene	1330-20-7	30-<70 %

Infosafe No™ LPXJM Issue Date : February 2012 ISSUED by PARCHEMN

Product Name : **MASTERSHIELD UA20 PART A**

Classified as hazardous

Ingredients	Name	CAS	Proportion
	Ethyl benzene	100-41-4	10-<30 %
	2-methoxy-1-methylethyl acetate	108-65-6	0-<10 %
	Mixture of alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-hydroxypoly(oxyethylene) and alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)		0-<1 %
	Bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate		0-<1 %
	Ingredients determined not to be hazardous		Balance

4. First-aid measures

Inhalation	If inhaled, remove from contaminated area. Apply artificial respiration if not breathing. Seek medical attention.
Ingestion	If swallowed, do NOT induce vomiting. Wash mouth thoroughly with water. Seek medical attention.
Skin	If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Ensure contaminated clothing is washed before re-use or discard. Seek medical attention.
Eye contact	If in eyes, hold eyelids apart and flush the eyes continuously with running water. Continue flushing for several minutes until all contaminants are washed off completely. Seek medical attention.
First Aid Facilities	Eye wash station, safety shower and normal washroom facilities.
Advice to Doctor	Treat symptomatically.
Other Information	For advice, contact a Poisons Information Centre (Phone eg Australia 131 126; New Zealand 0800 764 766) or a doctor at once.

5. Fire-fighting measures

Suitable extinguishing media	Foam, carbon dioxide or dry chemical powder.
Hazards from Combustion Products	Under fire conditions this product may emit toxic and/or irritating fumes and gases including carbon monoxide, carbon dioxide.
Specific hazards arising from the chemical	Flammable liquid. Keep storage tanks, pipelines, fire exposed surfaces etc cool with water spray. Shut off any leak if safe to do so and remove sources of re-ignition. Vapour/air mixtures may ignite explosively. Flashback along the vapour trail may occur. Runoff to sewer may create a fire hazard. Heating can cause expansion or decomposition leading to violent rupture of containers.
Hazchem Code	•3Y
Precautions in connection with Fire	Fire-fighters should wear full protective clothing and self contained breathing apparatus (SCBA) operated in positive pressure mode. Use water spray to cool storage containers and tanks, pipelines and fire-exposed surfaces.

6. Accidental release measures

Emergency Procedures	Wear appropriate personal protective equipment and clothing to prevent exposure. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unprotected personnel. If
-----------------------------	--

Infosafe No™ LPXJM Issue Date : February 2012 ISSUED by PARCHEMN

Product Name : **MASTERSHIELD UA20 PART A**

Classified as hazardous

possible contain the spill. Spillage is slippery. Place inert absorbent, non-combustible material onto spillage. Use clean non-sparking tools to collect the material and place into suitable labelled containers for subsequent recycling or disposal. Dispose of waste according to the applicable local and national regulations. If contamination of sewers or waterways occurs inform the local water and waste management authorities in accordance with local regulations.

7. Handling and storage

Precautions for Safe Handling

Wear appropriate protective clothing and equipment to prevent inhalation, skin and eye contact. Handle and use the material in a well-ventilated area, away from sparks, flames and other ignition sources. Have emergency equipment (for fires, spills, leaks, etc.) readily available. Work from suitable, labelled, fire-resistant containers. Keep containers closed when not in use. Flameproof equipment is necessary in areas where the product is being used. Take precautionary measures against static discharges. Earth or bond all equipment. Do not empty into drains. Maintain a high level of personal hygiene when using the product, that is, always wash hands after handling, and before eating, drinking, smoking or using the toilet facilities.

Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well ventilated area away from sources of ignition, oxidising agents, foodstuffs, clothing and out of direct sunlight. Keep containers closed when not in use and securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Have appropriate fire extinguishers available in and near the storage area. For information on the design of the storeroom, reference should be made to Australian Standard AS1940 - The storage and handling of flammable and combustible liquids. Reference should also be made to all Local, State and Federal regulations.

8. Exposure controls/personal protection

Occupational exposure limit values

No exposure standards have been established for this material by the Occupational Safety and Health Service (OSH) of the New Zealand Department of Labour. However, exposure standards for ingredients are stated below:

New Zealand Occupational Safety and Health Service (OSH) Workplace Exposure Standards:

Substance	TWA		STEL		NOTICES
	ppm	mg/m ³	ppm	mg/m ³	
Xylene	50	217	-	-	-
Ethyl benzene	100	434	125	543	-

TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eight-hour working day, for a five-day week.

STEL (Short Term Exposure Limit): The average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.

Biological Limit Values

Biological Exposure Indices BEI from American Conference of Industrial Hygienists (ACGIH) for ingredients are as follows

Name: Xylenes
Determinant: Methylhippuric acids
Specimen: Creatinine in urine.
Value: 1.5 g/g
Sampling time: end of shift.

Name: Ethyl benzene
Determinant: Sum of mandelic acid and phenyl glyoxylic acid.
Specimen: Creatinine in urine.
Value: 0.7 g/g
Sampling time: End of shift at end of work week.

Appropriate engineering controls

Provide sufficient ventilation to keep airborne levels below the exposure limits. Where vapours or mists are generated, particularly in enclosed areas, and natural ventilation is inadequate, a flameproof exhaust ventilation system is required. Refer to AS 1940 - The storage and handling of flammable and combustible liquids and AS/NZS 60079.10.1:2009 Explosive atmospheres -

Infosafe No™ LPXJM	Issue Date : February 2012	ISSUED by PARCHEMN
--------------------	----------------------------	--------------------

Product Name : **MASTERSHIELD UA20 PART A**

Classified as hazardous

Respiratory Protection	Classification of areas - Explosive gas atmospheres, for further information concerning ventilation requirements. If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable organic vapour filter should be used. Reference should be made to Australian/New Zealand Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.
Eye Protection	Safety glasses with side shields or chemical goggles should be worn. Final choice of appropriate eye/face protection will vary according to individual circumstances. Eye protection devices should conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors for Industrial Applications.
Hand Protection	Impervious gloves recommended. Final choice of appropriate gloves will vary according to individual circumstances ie. methods of handling or according to risk assessments undertaken. Reference should be made to AS/NZS 2161 Occupational protective gloves- Selection, use and maintenance.
Body Protection	Suitable workwear should be worn to protect personal clothing, eg cotton overalls buttoned at neck and wrist. When large quantities are handled the use of plastic aprons and rubber boots is recommended.

9. Physical and chemical properties

Appearance	Clear liquid
Odour	Aromatic solvent odour
Melting Point	Not available
Boiling Point	138-142°C (xylene)
Solubility in Water	Negligible
Specific Gravity	0.97 at 23°C
pH	Not available
Vapour Pressure	0.8 kPa @20°C
Vapour Density (Air=1)	3.66 @15°C(xylene)
Evaporation Rate	0.76 (xylene)
Odour Threshold	Not available
Viscosity	Not available
Partition Coefficient: n-octanol/water	Not available
Flash Point	26°C (xylene)
Flammability	Flammable liquid.
Auto-Ignition Temperature	495°C (xylene)
Flammable Limits - Lower	1.1% (xylene)
Flammable Limits - Upper	7.7% (xylene)

10. Stability and reactivity

Chemical Stability	Stable under normal conditions of storage and handling.
Conditions to Avoid	Heat, direct sunlight, open flames or other sources of ignition.
Incompatible Materials	Strong acids, strong bases and strong oxidising agents
Hazardous Decomposition Products	Thermal decomposition may result in the release of toxic and/or irritating fumes including carbon monoxide, carbon dioxide.

Infosafe No™ LPXJM	Issue Date : February 2012	ISSUED by PARCHEMN
--------------------	----------------------------	--------------------

Product Name : **MASTERSHIELD UA20 PART A**

Classified as hazardous

Hazardous Polymerization Will not occur.

11. Toxicological Information

Toxicology Information	No toxicity data are available for this specific product.
Inhalation	Harmful by inhalation. Inhalation will cause irritation of the respiratory system.
Ingestion	Ingestion of this product may irritate the gastric tract causing nausea and vomiting.
Skin	Harmful in contact with skin. Irritating to skin. Symptoms may include redness and itchiness. Repeated exposure may cause skin dryness and cracking, and may lead to dermatitis.
Eye	Irritating to eyes. Symptoms can include redness, tearing, stinging and swelling.
Reproductive Toxicity	Suspected of damaging fertility or the unborn child
Carcinogenicity	Suspected of causing cancer
Skin Sensitisation	May cause an allergic skin reaction.
Aspiration Hazard	Not expected to be an aspiration hazard.
STOT-single exposure	Not expected to cause damage to organs.
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure by ingestion and inhalation.
Germ cell mutagenicity	Not considered to be a mutagenic hazard.
Respiratory sensitisation	Not expected to be a respiratory sensitiser.

12. Ecological information

Ecotoxicity	Harmful to aquatic life. Harmful to terrestrial vertebrates.
Persistence and degradability	Not available
Mobility	2-Methoxy-1-methylethyl acetate: Ultimate destination of the product: Water Xylene: Ultimate destination of the product: Air
Bioaccumulative Potential	2-Methoxy-1-methylethyl acetate: Not potentially bioaccumulable. (Unpublished reports) Xylene: Not bioaccumulable. (Published data)
Environmental Protection	Do not allow product to enter drains, waterways or sewers.
Acute Toxicity - Fish	2-Methoxy-1-methylethyl acetate: LC50(Pimephales promelas)/96h: >100 mg/l (Unpublished reports) Xylene: LC50(Pimephales promelas)/96h: 13.4 mg/l (Published reports)

13. Disposal considerations

Disposal Considerations	<p>Product Disposal:</p> <p>Product wastes are controlled wastes and should be disposed of in accordance with all applicable local and national regulations. This product can be disposed through a licensed commercial waste collection service. It can be disposed by burning in an approved high temperature incineration facility; or alternatively, it can be reacted with the base component to enable it to cure to an inert solid that can be disposed in a licensed landfill facility. Personal protective clothing and equipment as specified in Section 8 of this SDS must be worn during handling and disposal of this product. The ventilation requirements as specified in the same section must also be followed, and the precautions given in Section 7 of this SDS regarding handling must also be followed.</p>
--------------------------------	---

Infosafe No™ LPXJM Issue Date : February 2012 ISSUED by PARCHEMN

Product Name : **MASTERSHIELD UA20 PART A**

Classified as hazardous

Do not dispose into the sewerage system. Do not discharge into drains or watercourses or dispose where ground or surface waters may be affected. In New Zealand, the disposal agency or contractor must comply with the New Zealand Hazardous Substances (Disposal) Regulations 2001. Further details regarding disposal can be obtained on the ERMA New Zealand website under specific group standards.

Container Disposal:

The container or packaging must be cleaned and rendered incapable of holding any substance. It can then be disposed of in a manner consistent with that of the substance it contained. In this instance the packaging can be disposed through a commercial waste collection service.

Alternatively, the container or packaging can be recycled if the hazardous residues have been thoroughly cleaned or rendered non-hazardous.

In New Zealand, the packaging (that may or may not hold any residual substance) that is lawfully disposed of by householders or other consumers through a public or commercial waste collection service is a means of compliance with regulations.

14. Transport information

Transport Information

Road and Rail Transport:

This material is classified as a Class 3 - Flammable Liquid according to NZS 5433:2007 Transport of Dangerous Goods on Land.

Must not be loaded in the same freight container or on the same vehicle with:

- Class 1, Explosives
- Division 2.1, Flammable gases
- Division 2.3, Toxic gases
- Division 4.2, Spontaneously combustible substances
- Division 5.1, Oxidising substances
- Division 5.2, Organic peroxides or
- Class 7, Radioactive materials unless specifically exempted.

Must not be loaded with in the same freight container; and on the same vehicle must be separated horizontally by at least 3 metres unless all but one are packed in separate freight containers with:

- Division 4.3, Dangerous when wet substances
- Goods of packing group II or III may be loaded in the same freight container or on the same vehicle if transported in segregation devices with:
- Division 4.2, Spontaneously combustible substances
 - Division 4.3, Dangerous when wet substances
 - Division 5.1, Oxidising substances
 - Division 5.2, Organic peroxides

Marine Transport (IMO/IMDG):

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

UN-No: 1866

Proper Shipping Name: RESIN SOLUTION

Class: 3

Packaging Group: III

EMS No.: F-E, S-E

Air Transport (ICAO/IATA):

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

UN-No: 1866

Proper Shipping Name: Resin solution

Class: 3

Packaging Group: III

Label: Flammable liquid

Packaging Instructions (passenger & cargo): 355

Packaging Instructions (cargo only): 366

1866

U.N. Number

UN proper shipping name

RESIN SOLUTION

Infosafe No™ LPXJM Issue Date : February 2012 ISSUED by PARCHEMN

Product Name : **MASTERSHIELD UA20 PART A**

Classified as hazardous

Transport hazard class(es) 3
Hazchem Code •3Y
Packing Group III
EPG Number 3A1
IERG Number 14
IMDG Marine pollutant No

15. Regulatory information

Regulatory Information Classified as Hazardous according to the New Zealand Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001.
Group Standard:
Surface Coatings and Colourants (Flammable, Toxic [6.7]) Group Standard 2006
HSNO Approval Number HSR002669

16. Other Information

Date of preparation or last revision of SDS SDS Reviewed: February 2012, Supersedes: August 2008
Contact Person/Point Technical Support: 1800 812 864
...End Of MSDS...

© Copyright ACOHS Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe MSDS displayed is the intellectual property of Acohs Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe MSDS displayed is the intellectual property of Acohs Pty Ltd. The compilation of MSDS's displayed is the intellectual property of Acohs Pty Ltd.

Copying of any MSDS displayed is permitted for personal use only and otherwise is not permitted. In particular the MSDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of MSDS without the express written consent of Acohs Pty Ltd.