

Infosafe No™ LPWTX Issue Date : August 2012 ISSUED by PARCHEMN

Product Name : **FOSROC NITOFLOOR FC100 COLOURED**

Classified as hazardous

## 1. Identification

**GHS Product Identifier** FOSROC NITOFLOOR FC100 COLOURED

**Company Name** Parchem Construction Supplies Pty Ltd (ABN 80 069 961 968)

**Address** 7 Lucca Road Wyong  
NSW 2259 Australia

**Telephone/Fax Number** Tel: 02 4350 5000  
Fax: 02 4351 2024

**Emergency phone number** 0800 154 666 (available 24/7)

**Recommended use of the chemical and restrictions on use** Sealer for cementitious floors

**Other Information** Distributed in New Zealand by:  
Concrete Plus  
23 Watts Road  
Sockburn  
New Zealand  
Tel: (03) 343 0090  
Fax: (03) 343 0202

This MSDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since Parchem Construction Supplies Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this MSDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company. Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.

[www.parchem.co.nz](http://www.parchem.co.nz)

## 2. Hazard Identification

**GHS classification of the substance/mixture** Classified as Hazardous according to the New Zealand Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001.  
Classified as Dangerous Goods for transport according to the New Zealand Standard NZS 5433:2012 Transport of Dangerous Goods on Land.  
3.1C - Flammable liquids: medium hazard  
6.1E (Aspiration hazard 1) - Substance that is acutely toxic  
6.1E (Inhalation - vapours, dusts or mists) - Substance that is acutely toxic  
6.3B - Substance that is mildly irritating to the skin  
9.1B - Substance that is ecotoxic in the aquatic environment

**Signal Word (s)** Danger

**Hazard Statement (s)** H226 Flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H316 Causes mild skin irritation.  
H333 May be harmful if inhaled.  
H411 Toxic to aquatic life with long lasting effects.

**Pictogram (s)** Flame, Health hazard, Environment



Infosafe No™ LPWTX Issue Date : August 2012 ISSUED by PARCHEMN

Product Name : **FOSROC NITOFLOOR FC100 COLOURED**

Classified as hazardous

<b>Precautionary statement – Prevention</b>	<p>P102 Keep out of reach of children</p> <p>P103 Read label before use</p> <p>P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.</p> <p>P233 Keep container tightly closed.</p> <p>P240 Ground/bond container and receiving equipment.</p> <p>P241 Use explosion-proof electrical/ventilating/lighting/.../equipment.</p> <p>P242 Use only non-sparking tools.</p> <p>P243 Take precautionary measures against static discharge.</p> <p>P273 Avoid release to the environment.</p> <p>P280 Wear protective gloves/eye protection/face protection.</p>
<b>Precautionary statement – Response</b>	<p>GENERAL:</p> <p>P101 If medical advice is needed, have product container or label at hand</p> <p>P312 Call a POISON CENTER or doctor/physician if you feel unwell.</p> <p>P370+P378: In case of fire: Use foam, carbon dioxide or dry chemical powder to extinguish.</p> <p>P391 Collect spillage.</p> <p>SKIN:</p> <p>P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.</p> <p>P332+P313 If skin irritation occurs: Get medical advice/ attention.</p> <p>INHALATION</p> <p>P304+P312 IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell.</p> <p>INGESTION</p> <p>P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.</p> <p>P331 Do NOT induce vomiting.</p>
<b>Precautionary statement – Storage</b>	<p>P403+P235: Store in a well-ventilated place. Keep cool.</p> <p>P405 Store locked up.</p>
<b>Precautionary statement – Disposal</b>	<p>P501 In the case of a substance that is in compliance with a HSN0 approval other than a Part 6A (Group Standards) approval, a label must provide a description of one or more appropriate and achievable methods for the disposal of a substance in accordance with the Hazardous Substances (Disposal) Regulations 2001. This may also include any method of disposal that must be avoided. See Section 13 for disposal details.</p>

### 3. Composition/information on ingredients

Ingredients	Name	CAS	Proportion
	Solvent naphtha, petroleum, light aromatic	64742-95-6	30-60 %
	Crystalline Silica (Quartz)	14808-60-7	0-<1 %
	Ingredients determined not to be hazardous.		Balance

### 4. First-aid measures

<b>Inhalation</b>	If inhaled, remove from contaminated area. Apply artificial respiration if not breathing. Seek medical attention.
<b>Ingestion</b>	Do NOT induce vomiting. Wash out mouth and lips with water. Where vomiting occurs naturally have affected person place head below hip level in order to reduce risk of aspiration. Seek immediate medical attention.
<b>Skin</b>	Wash affected area thoroughly with soap and water. Remove contaminated clothing and wash before reuse or discard. Seek medical attention.
<b>Eye contact</b>	If in eyes, hold eyelids apart and flush the eyes continuously with running water. Continue flushing for several minutes until all contaminants are washed out completely. Seek medical attention.
<b>First Aid Facilities</b>	Eye wash, safety shower and normal washroom facilities.
<b>Advice to Doctor</b>	Treat symptomatically.
<b>Other Information</b>	For advice, contact a Poisons Information Centre (Phone eg Australia 131 126; New Zealand 0800 764 766) or a doctor (at once).

### 5. Fire-fighting measures

Infosafe No™ LPWTX	Issue Date : August 2012	ISSUED by PARCHEMN
--------------------	--------------------------	--------------------

Product Name : **FOSROC NITOFLOOR FC100 COLOURED**

Classified as hazardous

<b>Suitable extinguishing media</b>	Use carbon dioxide, dry chemical, foam or water mist.
<b>Unsuitable Extinguishing Media</b>	DO NOT USE water jets.
<b>Hazards from Combustion</b>	Under fire conditions this product may emit toxic and/or irritating fumes including carbon monoxide and carbon dioxide.
<b>Specific hazards arising from the chemical</b>	Flammable liquid and vapour. Vapour/air mixtures may ignite explosively. Flashback along the vapour trail may occur. Runoff to sewer may create fire or explosion hazard.
<b>Hazchem Code</b>	•3Y
<b>Precautions in connection with Fire</b>	Fire fighters should wear Self-Contained Breathing Apparatus (SCBA) operated in positive pressure mode and full protective clothing to prevent exposure to vapours or fumes. Water spray may be used to cool down heat-exposed containers. Fight fire from safe location. This product should be prevented from entering drains and watercourses.

## 6. Accidental release measures

<b>Emergency Procedures</b>	Wear appropriate personal protective equipment and clothing to prevent exposure. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unprotected personnel. If possible contain the spill. Place inert absorbent, non-combustible material onto spillage. Use clean non-sparking tools to collect the material and place into suitable labelled containers for subsequent recycling or disposal. Dispose of waste according to the applicable local and national regulations. If contamination of sewers or waterways occurs inform the local water and waste management authorities in accordance with local regulations.
-----------------------------	--

## 7. Handling and storage

<b>Precautions for Safe Handling</b>	Avoid contact with skin and eyes. Wear overalls, impervious gloves and safety glasses. Use in designated areas with adequate ventilation. Use approved flammable liquid storage containers in the work area. Prevent release of vapours and mists into workplace air. Keep containers closed when not in use. Take precautionary measures against static discharges. Keep material away from sparks, flames and other ignition sources. Do not empty into drains. Ensure a high level of personal hygiene is maintained when using this product, that is, always wash hands before eating, drinking, smoking or using the toilet facilities.
<b>Conditions for safe storage, including any incompatibilities</b>	Store in a cool, dry, well-ventilated area away from sources of ignition, oxidising agents, strong acids, foodstuffs, and clothing. Keep containers closed when not in use and securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Have appropriate fire extinguishers available in and near the storage area. Take precautions against static electricity discharges. Use proper grounding procedures. For information on the design of the storeroom, reference should be made to Australian Standard AS1940 - The storage and handling of flammable and combustible liquids. Reference should also be made to all applicable local and national regulations.

## 8. Exposure controls/personal protection

<b>Occupational exposure limit values</b>	No exposure value assigned for this specific material by the New Zealand Occupational Safety and Health Service (OSH). However, over-exposure to any chemical may result in enhancement of pre-existing adverse medical conditions and/or allergic reactions and should be kept to the least possible levels. The available exposure limits for ingredients are listed below:				
	Substance	TWA		STEL	NOTICES
		ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
	Oil mist, mineral	-	5	-	10
	Quartz	-	0.1	-	-
					Inhalable dust
	TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eight-hour working day, for a five-day week.				

Infosafe No™ LPWTX

Issue Date : August 2012

ISSUED by PARCHEMN

Product Name : **FOSROC NITOFLOOR FC100 COLOURED**

Classified as hazardous

<b>Biological Limit Values</b>	STEL (Short Term Exposure Limit): The average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday. No biological limit allocated.
<b>Appropriate engineering controls</b>	Provide sufficient ventilation to keep airborne levels below the exposure limits. Where vapours or mists are generated, particularly in enclosed areas, and natural ventilation is inadequate, a flameproof exhaust ventilation system is required. Refer to AS 1940 - The storage and handling of flammable and combustible liquids and AS/NZS 60079.10.1:2009 Explosive atmospheres - Classification of areas - Explosive gas atmospheres, for further information concerning ventilation requirements.
<b>Respiratory Protection</b>	If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable organic vapour filter should be used. Reference should be made to Australian/New Zealand Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.
<b>Eye Protection</b>	Safety glasses with side shields or chemical goggles should be worn. Final choice of appropriate eye/face protection will vary according to individual circumstances. Eye protection devices should conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors for Industrial Applications.
<b>Hand Protection</b>	Wear gloves of impervious material. Final choice of appropriate gloves will vary according to individual circumstances i.e. methods of handling or according to risk assessments undertaken. Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.
<b>Body Protection</b>	Suitable protective work wear, e.g. cotton overalls buttoned at neck and wrist is recommended. Chemical resistant apron is recommended where large quantities are handled.

## 9. Physical and chemical properties

<b>Appearance</b>	Coloured, opaque liquid
<b>Odour</b>	Aromatic
<b>Melting Point</b>	Not available
<b>Boiling Point</b>	150 - 185°C
<b>Solubility in Water</b>	Not available
<b>Specific Gravity</b>	1.23 @ 25°C
<b>pH</b>	Not available
<b>Vapour Pressure</b>	Not available
<b>Vapour Density (Air=1)</b>	Not available
<b>Evaporation Rate</b>	Not available
<b>Odour Threshold</b>	Not available
<b>Viscosity</b>	Not available
<b>Partition Coefficient: n-octanol/water</b>	Not available
<b>Flash Point</b>	34°C
<b>Flammability</b>	Flammable
<b>Auto-Ignition Temperature</b>	Not available
<b>Flammable Limits - Lower</b>	Not available
<b>Flammable Limits - Upper</b>	Not available

## 10. Stability and reactivity

Infosafe No™ LPWTX

Issue Date : August 2012

ISSUED by PARCHEMN

Product Name : **FOSROC NITOFLOOR FC100 COLOURED**

Classified as hazardous

<b>Reactivity</b>	Reacts with incompatibles
<b>Chemical Stability</b>	Stable under normal conditions of storage and handling.
<b>Conditions to Avoid</b>	Heat, flames and other ignition sources.
<b>Incompatible Materials</b>	Strong oxidising agents.
<b>Hazardous Decomposition Products</b>	Thermal decomposition may result in the release of toxic and/or irritating fumes including carbon monoxide and carbon dioxide.
<b>Hazardous Polymerization</b>	Will not occur.

## 11. Toxicological Information

<b>Toxicology Information</b>	No toxicology data available for this product.
<b>Ingestion</b>	Harmful-may cause lung damage if swallowed. Small amounts of liquid aspirated into the respiratory system during ingestion or from vomiting may cause severe pulmonary injury that may lead to death. May cause irritation to the mouth, throat, esophagus and stomach with symptoms of nausea, abdominal discomfort, vomiting and diarrhoea.
<b>Inhalation</b>	May be harmful if inhaled. May cause respiratory irritation. Symptoms include sneezing, coughing, wheezing, shortness of breath, headache, drowsiness, dizziness, nausea and vomiting.
<b>Skin</b>	Causes mild skin irritation. Skin contact may cause redness, itching and swelling. Repeated exposure may cause skin dryness and cracking and may lead to dermatitis.
<b>Eye</b>	May be irritating to eyes. On eye contact this product may cause tearing, stinging, blurred vision, and redness.
<b>Respiratory sensitisation</b>	Not expected to be a respiratory sensitiser.
<b>Skin Sensitisation</b>	Not expected to be a skin sensitiser.
<b>Germ cell mutagenicity</b>	Not considered to be a mutagenic hazard.
<b>Carcinogenicity</b>	Not considered to be a carcinogenic hazard. However, crystalline silica has been classified by International Agency for Research on Cancer (IARC) as carcinogenic to humans by inhalation (Group 1).
<b>Reproductive Toxicity</b>	Not considered to be toxic to reproduction.
<b>STOT-single exposure</b>	Not expected to cause toxicity to a specific target organ.
<b>STOT-repeated exposure</b>	Prolonged inhalation may cause central nervous system depression with symptoms including dizziness, drowsiness, nausea and headaches.
<b>Aspiration Hazard</b>	May be fatal if swallowed and enters airways.
<b>Other Information</b>	This product contains crystalline silica (quartz). No exposure to free respirable crystalline silica is anticipated during normal use of this product as silica is bound in the liquid. It should be noted, however, that respirable crystalline silica has been listed as a Group 1 human carcinogen by the IARC. Inhalation of respirable silica may cause cancer, silicosis or other serious delayed lung injury. Grinding or machining of coated materials may release silica. Use approved dust respirator when grinding, sanding or machining the dried items.

## 12. Ecological information

<b>Ecotoxicity</b>	Toxic to aquatic life with long lasting effects.
<b>Persistence and degradability</b>	Not available
<b>Mobility</b>	Not available
<b>Bioaccumulative Potential</b>	Not available

Infosafe No™ LPWTX

Issue Date : August 2012

ISSUED by PARCHEMN

Product Name : **FOSROC NITOFLOOR FC100 COLOURED**

Classified as hazardous

**Environmental Protection** Do not discharge this material into waterways, drains and sewers.

### 13. Disposal considerations

**Disposal Considerations** Product Disposal:  
Product wastes are controlled wastes and should be disposed of in accordance with all applicable local and national regulations. This product can be disposed through a licensed commercial waste collection service. In this specific case the product is a combustible substance and therefore can be sent to an approved high temperature incineration plant for disposal. Do not dispose directly into the sewerage system. Do not discharge into drains or watercourses or dispose where ground or surface waters may be affected. The disposal agency or contractor must comply with the New Zealand Hazardous Substances (Disposal) Regulations 2001. Further details regarding disposal can be obtained on the EPA New Zealand website under specific group standards. Personal protective clothing and equipment as specified in Section 8 of this SDS must be worn during handling and disposal of this product. The ventilation requirements as specified in the same section must also be followed, and the precautions given in Section 7 of this SDS regarding handling must also be followed.

Container Disposal:  
The container or packaging must be cleaned and rendered incapable of holding any substance. It can then be disposed of in a manner consistent with that of the substance it contained. In this instance the packaging can be disposed through a commercial waste collection service. Alternatively, the container or packaging can be recycled if the hazardous residues have been thoroughly cleaned or rendered non-hazardous. In New Zealand, the packaging (that may or may not hold any residual substance) that is lawfully disposed of by householders or other consumers through a public or commercial waste collection service is a means of compliance with regulations.

### 14. Transport information

**Transport Information** Road & Rail:  
This material is classified as Dangerous Goods Class 3 - Flammable Liquid according to NZS 5433:2012 Transport of Dangerous Goods on Land. Must not be loaded in the same freight container or on the same vehicle with:  
- Class 1, Explosives  
- Division 2.1, Flammable gases  
- Division 2.3, Toxic gases  
- Division 4.2, Spontaneously combustible substances  
- Division 5.1, Oxidising substances  
- Division 5.2, Organic peroxides or  
- Class 7, Radioactive materials unless specifically exempted.  
Must not be loaded with in the same freight container; and on the same vehicle must be separated horizontally by at least 3 metres unless all but one are packed in separate freight containers with:  
- Division 4.3, Dangerous when wet substances  
Goods of packing group II or III may be loaded in the same freight container or on the same vehicle if transported in segregation devices with:  
- Division 4.2, Spontaneously combustible substances  
- Division 4.3, Dangerous when wet substances  
- Division 5.1, Oxidising substances  
- Division 5.2, Organic peroxides

Marine Transport (IMO/IMDG):  
Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.  
UN No.: 1866  
Proper Shipping Name: RESIN SOLUTION  
DG Class: 3  
Packaging Group: III  
EMS No.: F-E, S-E  
Special provisions: 223, 955

Infosafe No™ LPWTX	Issue Date : August 2012	ISSUED by PARCHEMN
--------------------	--------------------------	--------------------

Product Name : **FOSROC NITOFLOOR FC100 COLOURED**

Classified as hazardous

Air Transport (ICAO/IATA):  
 Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.  
 UN No: 1866  
 Proper Shipping Name: : Resin solution  
 Class: 3  
 Packing Group: III  
 Label: Miscellaneous  
 Packing Instruction: 355 (For passenger and cargo aircraft)  
 Packing Instruction: 366 (For cargo aircraft only)  
 Special provisions: A3  
 1866

**U.N. Number**

**UN proper shipping name**

**Transport hazard class(es)**

**Hazchem Code**

**Packing Group**

**EPG Number**

**IERG Number**

**IMDG Marine pollutant**

RESIN SOLUTION

3

•3Y

III

3A1

14

Yes

## 15. Regulatory information

**Regulatory Information**

Classified as Hazardous according to the New Zealand Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001.  
 Group Standard:  
 Surface Coatings and Colourants (Flammable) Group Standard 2006

**HSNO Approval Number**

HSR002662

## 16. Other Information

**Date of preparation or last revision of SDS**

SDS Reviewed: August 2012, Supersedes: September 2007

**Contact Person/Point**

Technical Support: 1800 812 864

...End Of MSDS...

© Copyright ACOHS Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe MSDS displayed is the intellectual property of Acohs Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe MSDS displayed is the intellectual property of Acohs Pty Ltd. The compilation of MSDS's displayed is the intellectual property of Acohs Pty Ltd.

Copying of any MSDS displayed is permitted for personal use only and otherwise is not permitted. In particular the MSDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of MSDS without the express written consent of Acohs Pty Ltd.