

Infosafe No™ LPTCG	Issue Date : September 2013	ISSUED by PARCHEMC
Product Name : FOSROC PRIMER 21		

1. Identification

GHS Product Identifier	FOSROC PRIMER 21
Company Name	Parchem Construction Supplies Pty Ltd (ABN 80 069 961 968)
Address	7 Lucca Road Wyong NSW 2259 Australia
Telephone/Fax Number	Tel: 02 4350 5000 Fax: 02 4351 2024
Emergency phone number	1800 638 556 (available 24/7)
Recommended use of the chemical and restrictions on use	A primer to promote adhesion of polyurethane sealants to porous surfaces.
Other Information	<p>This SDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since Parchem Construction Supplies Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this MSDS in the context of how the user intends to handle and use the product in the workplace.</p> <p>If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company. Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.</p> <p>www.parchem.com.au</p>

2. Hazard Identification

GHS classification of the substance/mixture	<p>Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia.</p> <p>Classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)</p>
Signal Word (s)	<p>Carcinogenicity: Category 2 Flammable Liquids: Category 3 Acute Toxicity - Inhalation: Category 5 Sensitization - Respiratory: Category 1 Skin Corrosion/Irritation: Category 2 STOT Single Exposure Category 3 (narcotic) Sensitization - Skin: Category 1</p> <p>Danger</p>
Hazard Statement (s)	<p>H226 Flammable liquid and vapour. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H333 May be harmful if inhaled H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H336 May cause drowsiness or dizziness. H351 Suspected of causing cancer.</p>
Pictogram (s)	Exclamation mark, Flame, Health hazard



Precautionary statement – Prevention	<p>P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.</p>
---	--

Infosafe No™ LPTCG Issue Date : September 2013 ISSUED by PARCHEMC

Product Name : **FOSROC PRIMER 21**

P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ventilating/lighting/equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P261 Avoid breathing fume/gas/mist/vapours/spray.
P264 Wash hands and skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P281 Use personal protective equipment as required.
P285 In case of inadequate ventilation wear respiratory protection.

Precautionary statement – Response

GENERAL
P308+P313 IF exposed or concerned: Get medical advice/attention.

INHALATION
P304+P312 IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell.
P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.
P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

SKIN
P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P362 Take off contaminated clothing and wash before reuse.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

OTHER
P370+P378 In case of fire: Use foam, water fog, water spray, carbon dioxide or dry chemical powder for extinction.

Precautionary statement – Storage

P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P403+P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Precautionary statement – Disposal

P501 Dispose of contents/container to an approved waste disposal plant.

3. Composition/information on ingredients

Ingredients	Name	CAS	Proportion
	Butyl Acetate	123-86-4	30-60 %
	Benzene,	26426-91-5	30-60 %
	2,4-diisocyanato-1-meth yl-, polymer with 1,6-diisocyanatohexane		
	Ethylbenzene	100-41-4	<5 %
	Xylene	1330-20-7	<10 %
	Toluene-2,4-diisocyanat e	584-84-9	<1 %
	1,6-Hexamethylene Diisocyanate	822-06-0	<1 %
	Ingredients determined not to be hazardous		To 100%

4. First-aid measures

Inhalation If inhaled, remove affected person from contaminated area. Apply artificial respiration if not breathing. Seek medical attention.

Ingestion Rinse mouth and lips thoroughly with water. Do not induce vomiting. Seek immediate medical attention.

Skin Remove all contaminated clothing immediately. Wash affected area thoroughly with soap and water. Wash contaminated clothing before reuse or discard. Seek medical attention.

Eye contact If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre (e.g. phone Australia 13 11 26; New Zealand 0800 764 766) or a doctor, or for at least 15 minutes.

Infosafe No™ LPTCG	Issue Date : September 2013	ISSUED by PARCHEMC
--------------------	-----------------------------	--------------------

Product Name : **FOSROC PRIMER 21**

First Aid Facilities	Eye wash station and normal washroom facilities.
Advice to Doctor	Treat symptomatically.
Other Information	For advice in an emergency, contact a Poisons Information Centre (Phone Australia 13 1126; New Zealand 0800 POISON / 0800 764 766) or a doctor at once.

5. Fire-fighting measures

Suitable extinguishing media	Foam, water fog, water spray, carbon dioxide or dry chemical powder.
Hazards from Combustion Products	Under fire conditions this product may emit toxic and/or irritating fumes, smoke and gases including carbon monoxide, carbon dioxide and nitrogen oxides.
Specific hazards arising from the chemical	Flammable liquid and vapour. Vapour/air mixtures may ignite explosively. Flashback along the vapour trail may occur. Runoff to sewer may create fire or explosion hazard.
Hazchem Code	•3Y
Decomposition Temp.	Not available
Precautions in connection with Fire	Fire fighters should wear Self-Contained Breathing Apparatus (SCBA) and full protective clothing to prevent exposure to vapours, fumes or products of combustion. Prevent spillage from entering drains or water courses. Keep containers cool with water spray.

6. Accidental release measures

Emergency Procedures	Wear appropriate personal protective equipment and clothing to prevent exposure. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unprotected personnel. If possible contain the spill. Place inert absorbent, non-combustible material onto spillage. Use clean non-sparking tools to collect the material and place into suitable labelled containers for subsequent recycling or disposal. Dispose of waste according to the applicable local and national regulations. If contamination of sewers or waterways occurs inform the local water and waste management authorities in accordance with local regulations.
-----------------------------	--

7. Handling and storage

Precautions for Safe Handling	Avoid skin and eye contact, and inhalation of vapours when mixing and handling. Wear overalls, impervious gloves and approved respirator. Use in designated areas with adequate ventilation. Use approved flammable liquid storage containers in the work area. Electrical equipment must be protected to the appropriate standard. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear antistatic footwear and clothing and floors should be of the conducting type. Isolate from sources of heat, sparks and open flame. No sparking tools should be used. Prevent release of vapours and mists into workplace air. Keep containers closed when not in use. Take precautionary measures against static discharges. Keep material away from sparks, flames and other ignition sources. Do not empty into drains. Ensure a high level of personal hygiene is maintained when using this product, that is, always wash hands before eating, drinking, smoking or using the toilet facilities. The accumulation of contaminated rags may result in spontaneous combustion. Good housekeeping standards, regular safe removal of waste materials and regular maintenance of spray booth filters will minimise the risks of spontaneous combustion and other fire hazards.
Conditions for safe storage, including any incompatibilities	Store in a cool, dry, well-ventilated area away from sources of heat and ignition. Store away from strong oxidising agents, amines and alcohols. Containers which are opened must be carefully resealed and kept upright to prevent leakage and reaction with moisture. Keep containers closed at all times - check regularly for leaks. For information on the design of the storeroom reference should be made to Australian Standard AS1940, The storage and handling of flammable and combustible liquids. Reference should also be made to any applicable national and local regulations.

Infosafe No™ LPTCG	Issue Date : September 2013	ISSUED by PARCHEMC
Product Name : FOSROC PRIMER 21		

8. Exposure controls/personal protection

Occupational exposure limit values No exposure value assigned for this material by Safe Work, Australia. However, the available exposure limits for ingredients are listed below:

Safe Work, Australia Exposure Standards:

	TWA		STEL		NOTICES
	ppm	mg/m3	ppm	mg/m3	
Isocyanates (as -NCO)	-	0.02	-	0.07	Sen
Xylene	80	350	150	655	-
n-Butyl acetate	150	713	200	950	-
Ethylbenzene	100	434	125	543	-

Note: The values for isocyanates apply to all isocyanates, including prepolymers, present in the workplace air as vapours, mist or dust.

TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eight-hour working day, for a five-day week.

STEL (Short Term Exposure Limit): The average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.

'Sen' Notice: The substance may cause sensitization by skin contact or by inhalation.

Biological Limit Values Biological Exposure Indices (BEI) from American Conference of Industrial Hygienists (ACGIH) for ingredients are as follows:

Determinant Indices (BEI)	Sampling Time	Biological Exposure
XYLENES [1330-20-7) Methylhippuric acids in urine	End of shift	1.5 g/g creatinine
ETHYL BENZENE [100-41-4] Sum of mandelic acid and phenylglyoxylic acid in urine	End of shift at end of workweek	0.7 g/g creatinine

Appropriate engineering controls Provide sufficient ventilation to keep airborne levels below the exposure limits. Where vapours or mists are generated, particularly in enclosed areas, and natural ventilation is inadequate, a flameproof exhaust ventilation system is required. Refer to AS 1940 - The storage and handling of flammable and combustible liquids and AS/NZS 60079.10.1:2009 Explosive atmospheres - Classification of areas - Explosive gas atmospheres, for further information concerning ventilation requirements.

Respiratory Protection Positive pressure air supplied full face respirator is preferred for long term use. Cartridge filter mask complying with AS1716 for organic vapours is acceptable for short periods depending on risk assessment. The final choice of appropriate personal protection will vary according to individual circumstances. This can include methods of handling and engineering controls as determined by appropriate applicator risk assessment. Reference should be made to Australian/New Zealand Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.

Eye Protection Safety glasses with side shields, goggles or full-face shield as appropriate recommended. Final choice of appropriate eye/face protection will vary according to individual circumstances i.e. methods of handling or engineering controls and according to risk assessments undertaken. Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors for Industrial Applications.

Hand Protection Wear laminated film, Viton, nitrile or other suitable gloves conforming to AS/NZS 2161: Occupational protective gloves. Final choice of appropriate gloves will vary according to individual circumstances i.e. methods of handling or according to risk assessments undertaken. Reference should be made

Infosafe No™ LPTCG Issue Date : September 2013 ISSUED by PARCHEMC

Product Name : FOSROC PRIMER 21

Footwear	to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance. Antistatic footwear.
Body Protection	Suitable protective workwear, e.g. cotton overalls buttoned at neck and wrist. Final choice of appropriate clothing will vary according to individual circumstances i.e. methods of handling or according to risk assessments undertaken.

9. Physical and chemical properties

Appearance	Clear liquid
Colour	Slightly coloured
Odour	Aromatic
Decomposition Temperature	Not available
Melting Point	Not available
Boiling Point	125°C (initial)
Solubility in Water	Insoluble; reacts with water.
Solubility in Organic Solvents	Not available
Specific Gravity	1.07 at 23°C
pH	Not available
Vapour Pressure	Not available
Vapour Density (Air=1)	>1
Evaporation Rate	1.0 (Butyl acetate)
Odour Threshold	Not available
Viscosity	2200 mPa.s at 23°C
Partition Coefficient: n-octanol/water	Not available
Flash Point	28°C (Closed Cup) (approximate)
Flammability	Flammable liquid
Auto-Ignition Temperature	440°C (approximate)
Flammable Limits - Lower	1.7% v/v (Butyl acetate)
Flammable Limits - Upper	7.6% v/v (Butyl acetate)

10. Stability and reactivity

Reactivity	Will react with incompatibles.
Chemical Stability	Stable under normal conditions of use and storage.
Conditions to Avoid	Heat, direct sunlight, open flames and other sources of ignition.
Incompatible Materials	Reacts with oxidizing agents. Exothermic reaction with amines and alcohols; reacts slowly with water liberating carbon dioxide.
Hazardous Decomposition Products	Under fire conditions this product may emit toxic and/or irritating fumes, smoke and gases including carbon monoxide, carbon dioxide and oxides of nitrogen.
Hazardous Polymerization	Will not occur.

11. Toxicological Information

Infosafe No™ LPTCG	Issue Date : September 2013	ISSUED by PARCHEMC
--------------------	-----------------------------	--------------------

Product Name : **FOSROC PRIMER 21**

Toxicology Information	No toxicity data are available for this specific product. The available data for the ingredients are given below.
Acute Toxicity - Oral	For n-Butyl acetate: LD50 (Oral, Rat): 14,000 mg/kg LD50 (Oral, Rat): 10,770 mg/kg
Acute Toxicity - Dermal	For Polymeric isocyanate: LD50 (Oral, Rat): 5,000 mg/kg For n-Butyl acetate: LD50 (Dermal, Rabbit): 17,600 mg/kg
Acute Toxicity - Inhalation	For n-Butyl acetate: LC50 (Inhalation, Rat): 2,000 ppm/4h For Polymeric isocyanate: LC50 (Inhalation, Rat): >3,003 mg/m3/4h
Ingestion	Ingestion of this product may irritate the gastric tract causing nausea and vomiting.
Inhalation	May be harmful if inhaled. Inhalation of product vapours can cause irritation of the nose, throat and respiratory system. Symptoms include sneezing, coughing, wheezing, shortness of breath, headache, dizziness, drowsiness, nausea and vomiting. May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin	Irritating to skin. Skin contact will cause redness, itching and swelling. Repeated exposure may cause skin dryness and cracking and may lead to dermatitis. Repeated exposure may cause skin dryness and cracking. May cause sensitisation by skin contact.
Eye	May be irritating to eyes. The symptoms may include redness, itching and tearing.
Respiratory sensitisation	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin Sensitisation	May cause an allergic skin reaction.
Germ cell mutagenicity	Not considered to be a mutagenic hazard.
Carcinogenicity	Suspected of causing cancer. Xylene is listed as a Group 3: Not classifiable as to its carcinogenicity to humans according to International Agency for Research on Cancer (IARC). Ethylbenzene is listed as a Group 2B: Possibly carcinogenic to humans according to International Agency for Research on Cancer (IARC).
Reproductive Toxicity	Not considered to be toxic to reproduction.
STOT-single exposure	May cause drowsiness or dizziness by inhalation.
STOT-repeated exposure	Not available
Aspiration Hazard	Not expected to be an aspiration hazard.
Chronic Effects	Prolonged and repeated exposure through skin contact or inhalation of this material may result in harmful effects on the central nervous system. Chronic exposure can also cause damage to kidneys and liver. Repeated exposure may cause skin dryness and dermatitis.

12. Ecological information

Ecotoxicity	The monomeric isocyanates, which form a very small part of this product, may be harmful to aquatic organisms with long term adverse effects. The resin (polymeric isocyanate) reacts with water forming polyurea, an insoluble solid.
Persistence and degradability	Not available
Mobility	Not available
Bioaccumulative Potential	Not available

Infosafe No™ LPTCG	Issue Date : September 2013	ISSUED by PARCHEMC
--------------------	-----------------------------	--------------------

Product Name : **FOSROC PRIMER 21**

Environmental Protection Do not allow product to enter drains, waterways or sewers.

13. Disposal considerations

Disposal Considerations Disposal of spilled or waste material must be carried out in accordance with the applicable local, state and federal government regulations. Advise flammable nature. Empty containers may contain flammable residues. Do not puncture, cut or weld empty containers.

14. Transport information

Transport Information This material is Dangerous Goods Class 3 - Flammable Liquid according to The Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)
 Class 3 - Flammable Liquids are incompatible in a placard load with any of the following:
 - Class 1, Explosives
 - Division 2.1, Flammable Gases, (Division 2.1 and Class 3 are incompatible in transport if both are in tanks or other receptacles with a capacity individually exceeding 500 L.)
 - Division 2.3, Toxic Gases
 - Division 4.2 Spontaneously Combustible Substances
 - Division 5.1 Oxidising substances and Division 5.2, Organic Peroxides
 - Class 6 Toxic or Infectious Substances (where the flammable liquid is nitromethane)
 - Class 7 Radioactive Substances.

Marine Transport (IMO/IMDG):
 Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.
 UN-No: 1866
 Proper Shipping Name: RESIN SOLUTION
 Class: 3
 Packaging Group: III
 EmS: F-E, S-E
 Label: 3 (Flammable liquid)
 Marine Pollutant: No
 Special provisions: 223, 955

Air Transport (ICAO/IATA):
 Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.
 UN-No: 1866
 Proper Shipping Name: RESIN SOLUTION
 Class: 3
 Packaging Group: III
 Label: 3 (Flammable liquid)
 Packaging Instructions (passenger & cargo): 355
 Packaging Instructions (cargo): 366
 Special provisions: A3

U.N. Number	1866
UN proper shipping name	RESIN SOLUTION
Transport hazard class(es)	3
Hazchem Code	•3Y
Packing Group	III
EPG Number	3A1
IERG Number	14
IMDG Marine pollutant	No

Infosafe No™ LPTCG Issue Date : September 2013 ISSUED by PARCHEMC

Product Name : FOSROC PRIMER 21

15. Regulatory information

Regulatory Information	Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia
Poisons Schedule	Classified as a Scheduled Poisons according to the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP). S6
AICS (Australia)	All components of this product are listed on the Australian Inventory of Chemical Substances (AICS).

16. Other Information

Date of preparation or last revision of SDS	SDS Reviewed: September 2013 Supersedes: August 2004, July 2009
Literature References	Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice. Standard for the Uniform Scheduling of Medicines and Poisons. Australian Code for the Transport of Dangerous Goods by Road & Rail. Model Work Health and Safety Regulations, Schedule 10: Prohibited carcinogens, restricted carcinogens and restricted hazardous chemicals. Workplace exposure standards for airborne contaminants, Safe work Australia. American Conference of Industrial Hygienists (ACGIH). Globally Harmonised System of classification and labelling of chemicals.
Contact Person/Point	Technical Support: 1800 812 864 ...End Of MSDS...

© Copyright ACOHS Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe MSDS displayed is the intellectual property of Acohs Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe MSDS displayed is the intellectual property of Acohs Pty Ltd.
The compilation of MSDS's displayed is the intellectual property of Acohs Pty Ltd.

Copying of any MSDS displayed is permitted for personal use only and otherwise is not permitted. In particular the MSDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of MSDS without the express written consent of Acohs Pty Ltd.