

Infosafe No™ LPWBO	Issue Date : March 2012	ISSUED by PARCHEMC
--------------------	-------------------------	--------------------

 Product Name **SEALER PREP (TYRE MARK REMOVER)**

Classified as hazardous

## 1. Identification

<b>GHS Product Identifier</b>	SEALER PREP (TYRE MARK REMOVER)
<b>Company Name</b>	Parchem Construction Supplies Pty Ltd (ABN 80 069 961 968)
<b>Address</b>	7 Lucca Road Wyong NSW 2259 Australia
<b>Telephone/Fax Number</b>	Tel: 02 4350 5000 Fax: 02 4351 2024
<b>Emergency phone number</b>	1800 638 556 (available 24/7)
<b>Recommended use of the chemical and restrictions on use</b>	Sealant preparation solvent
<b>Other Information</b>	<p>This MSDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since Parchem Construction Supplies Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this MSDS in the context of how the user intends to handle and use the product in the workplace.</p> <p>If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company. Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.</p> <p>www.parchem.com.au</p>

## 2. Hazard Identification

<b>GHS classification of the substance/mixture</b>	Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia Classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition) Flammable liquid, Category 2 Acute toxicity - Inhalation, Category 4 Acute toxicity - Dermal, Category 4 Skin Corrosion/irritation, Category 2 Serious Eye damage/irritation, Category 2 Specific Target Organ Toxicity, Single exposure, Category 3 (narcotic)
<b>Signal Word (s)</b>	Danger
<b>Hazard Statement (s)</b>	H225 Highly Flammable liquid and vapour. H312 Harmful in contact with skin. H315 Causes skin irritation. H319 Causes serious eye irritation H332 Harmful if inhaled H336 May cause drowsiness or dizziness
<b>Pictogram (s)</b>	Flame, Exclamation mark,



<b>Precautionary statement – Prevention</b>	P102 Keep out of reach of children. P103 Read label before use. P104 Read Safety Data Sheet before use. P210 Keep away from heat/sparks/open flames/hot surfaces P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ventilating/lighting/equipment.
---	--

Infosafe No™ LPWBO	Issue Date : March 2012	ISSUED by PARCHEMC
--------------------	-------------------------	--------------------

 Product Name **SEALER PREP (TYRE MARK REMOVER)**

Classified as hazardous

<b>Precautionary statement – Response</b>	P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P261 Avoid breathing mist/vapours/spray. P264 Wash skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area P280 Wear protective gloves/protective clothing/eye protection/face protection. P101 If medical advice is needed, have product container or label at hand. P312 Call a POISON CENTER or doctor/physician if you feel unwell. P370+P378 In case of fire: use dry chemical powder, carbon dioxide or foam. SKIN P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. P332+P313 If skin irritation occurs: Get medical advice/ attention P362+P364 Take off contaminated clothing and wash before re-use. INHALATION P304+P340 IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. EYES P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 If eye irritation persists: Get medical advice/attention.
<b>Precautionary statement – Storage</b>	P403+P233 Store in a well-ventilated place. Keep container tightly closed. P403+P235 Store in a well-ventilated place. Keep cool. P405 Store locked up.
<b>Precautionary statement – Disposal</b>	P501 Dispose of contents/container to an approved waste disposal plant

### 3. Composition/information on ingredients

Ingredients	Name	CAS	Proportion
	Xylene	1330-20-7	30-60 %
	Acetone	67-64-1	30-60 %

### 4. First-aid measures

<b>Inhalation</b>	If inhaled, remove from contaminated area. Apply artificial respiration if not breathing. Seek medical attention.
<b>Ingestion</b>	If swallowed, do NOT induce vomiting. Wash out mouth with water. Seek medical attention.
<b>Skin</b>	Wash affected area thoroughly with soap and water. Remove contaminated clothing and wash before reuse or discard. Seek medical attention.
<b>Eye contact</b>	If in eyes, hold eyelids apart and flush the eyes continuously with running water. Continue flushing for several minutes until all contaminants are washed out completely. Seek medical attention.
<b>First Aid Facilities</b>	Eye wash, safety shower and normal washroom facilities.
<b>Advice to Doctor</b>	Treat symptomatically.
<b>Other Information</b>	For advice, contact a Poisons Information Centre (Phone eg Australia 131 126; New Zealand 0800 764 766) or a doctor (at once).

### 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Use dry chemical powder, carbon dioxide or foam.
<b>Unsuitable Extinguishing Media</b>	DO NOT USE water jets.
<b>Hazards from Combustion Products</b>	Under fire conditions this product may emit toxic and/or irritating fumes and gases including carbon monoxide and carbon dioxide.
<b>Specific hazards arising from the chemical</b>	This product is flammable. Keep storage tanks, pipelines, fire-exposed surfaces etc cool with water spray. Shut off any leak if safe to do so and remove sources of re-ignition. Vapour/air mixtures may ignite explosively. Flashback along the vapour trail may occur. Runoff to sewer may create fire or explosion hazard.
<b>Hazchem Code</b>	•3YE

Infosafe No™ LPWBO	Issue Date : March 2012	ISSUED by PARCHEMC
--------------------	-------------------------	--------------------

Product Name **SEALER PREP (TYRE MARK REMOVER)**

Classified as hazardous

**Precautions in connection with Fire** Fire-fighters should wear full protective clothing and self contained breathing apparatus (SCBA) operated in positive pressure mode. Water spray may be used to keep fire exposed containers cool.

## 6. Accidental release measures

**Emergency Procedures** Wear appropriate personal protective equipment and clothing to prevent exposure. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unprotected personnel. If possible contain the spill. Place inert absorbent, non-combustible material onto spillage. Use clean non-sparking tools to collect the material and place into suitable labelled containers for subsequent recycling or disposal. Dispose of waste according to the applicable local and national regulations. If contamination of sewers or waterways occurs inform the local water and waste management authorities in accordance with local regulations.

## 7. Handling and storage

**Precautions for Safe Handling** Open containers cautiously as contents may be under pressure. Use only in a well ventilated area. DO NOT store or use in confined spaces. Keep tank covered and containers sealed when not in use. Build up of mists or vapours in the atmosphere must be prevented. Avoid inhalation of sprays, vapour and mists. Do not use near welding or other ignition sources and avoid sparks. Do NOT pressurise, cut, heat or weld containers as they may contain hazardous residues. Do not smoke. Wear appropriate protection. It is essential that all who come into contact with this material maintain high standards of personal hygiene ie. Washing hands prior to eating, drinking, smoking or using toilet facilities.

**Conditions for safe storage, including any incompatibilities** Store in a cool, dry, well-ventilated area away from sources of ignition, oxidising agents, foodstuffs, and clothing and out of direct sunlight. Keep containers closed when not in use and securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Always keep in containers made of the same material as the supply container. Have appropriate fire extinguishers available in and near the storage area. Take precautions against static electricity discharges. Use proper grounding procedures. For information on the design of the storeroom, reference should be made to Australian Standard AS1940 - The storage and handling of flammable and combustible liquids. Reference should also be made to all State and Federal regulations.

## 8. Exposure controls/personal protection

**Occupational exposure limit values** No exposure value assigned for this specific material by Safework, Australia. However, the available exposure limits for ingredients are listed below:

Substance	TWA		STEL		NOTICES
	ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>	
Xylene	80	350	150	655	-
Acetone	500	1185	1000	2375	-

TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eight-hour working day, for a five-day week.

STEL (Short Term Exposure Limit): The average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.

**Biological Limit Values** Biological Exposure Indices BEI from American Conference of Industrial Hygienists (ACGIH) for ingredients are as follows

Name: Xylenes  
 Determinant: Methylhippuric acids  
 Specimen: Creatinine in urine.  
 Value: 1.5 g/g  
 Sampling time: end of shift.

Name: Acetone  
 Determinant: Acetone in urine  
 Value: 50 mg/L  
 Sampling time: End of shift.

Infosafe No™ LPWBO	Issue Date : March 2012	ISSUED by PARCHEMC
--------------------	-------------------------	--------------------

 Product Name **SEALER PREP (TYRE MARK REMOVER)**

Classified as hazardous

<b>Appropriate engineering controls</b>	Provide sufficient ventilation to keep airborne levels below the exposure limits. Where vapours or mists are generated, particularly in enclosed areas, and natural ventilation is inadequate, a flameproof exhaust ventilation system is required. Refer to AS 1940 - The storage and handling of flammable and combustible liquids and AS/NZS 60079.10.1:2009 Explosive atmospheres - Classification of areas - Explosive gas atmospheres, for further information concerning ventilation requirements.
<b>Respiratory Protection</b>	If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable vapour/mist filter should be used. Reference should be made to Australian/New Zealand Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.
<b>Eye Protection</b>	Safety glasses with side shields or face shield as appropriate recommended. Final choice of appropriate eye/face protection will vary according to individual circumstances ie. methods of handling or engineering controls and according to risk assessments undertaken. Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337- Eye Protectors for Industrial Applications.
<b>Hand Protection</b>	Impervious gloves recommended. Final choice of appropriate gloves will vary according to individual circumstances ie. methods of handling or according to risk assessments undertaken. Reference should be made to AS/NZS 2161 Occupational protective gloves- Selection, use and maintenance.
<b>Body Protection</b>	Suitable workwear should be worn to protect personal clothing, eg cotton overalls buttoned at neck and wrist. When large quantities are handled the use of plastic aprons and rubber boots is recommended.

## 9. Physical and chemical properties

<b>Appearance</b>	Clear, colourless liquid
<b>Odour</b>	Characteristic
<b>Melting Point</b>	-94°C
<b>Boiling Point</b>	56°C
<b>Solubility in Water</b>	Partly soluble
<b>Specific Gravity</b>	0.83 @23°C
<b>pH</b>	Not available
<b>Vapour Pressure</b>	Not available
<b>Vapour Density (Air=1)</b>	Not available
<b>Evaporation Rate</b>	Not available
<b>Odour Threshold</b>	Not available
<b>Viscosity</b>	Not available
<b>Partition Coefficient: n-octanol/water</b>	Not available
<b>Flash Point</b>	-17°C (Closed cup)
<b>Flammability</b>	Highly Flammable
<b>Auto-Ignition Temperature</b>	Not available
<b>Flammable Limits - Lower</b>	2.15%
<b>Flammable Limits - Upper</b>	13%

## 10. Stability and reactivity

<b>Chemical Stability</b>	Stable under normal conditions.
<b>Conditions to Avoid</b>	Heat, flames and other ignition sources.

Infosafe No™ LPWBO	Issue Date : March 2012	ISSUED by PARCHEMC
--------------------	-------------------------	--------------------

 Product Name **SEALER PREP (TYRE MARK REMOVER)**

Classified as hazardous

<b>Incompatible Materials</b>	Strong acids, strong bases and strong oxidising agents. Amines, aldehydes, ammonia, chlorinated compounds, natural rubber, amine epoxy coatings, neoprene rubber, vinyl coatings, PVC.
<b>Hazardous Decomposition Products</b>	Thermal decomposition may result in the release of toxic and/or irritating fumes and gases including carbon monoxide, carbon dioxide.
<b>Hazardous Polymerization</b>	Will not occur.

## 11. Toxicological Information

<b>Toxicology Information</b>	No toxicology data available for this product.
<b>Inhalation</b>	Harmful by inhalation. Inhalation will cause irritation of the respiratory system.
<b>Ingestion</b>	Ingestion of this product may irritate the gastric tract causing nausea and vomiting.
<b>Skin</b>	Harmful in contact with skin. Irritating to skin resulting in redness and itching. Prolonged or repeated skin contact may cause dermatitis due to defatting effect.
<b>Eye</b>	Irritating to eyes. On eye contact this product will cause tearing, stinging, blurred vision, and redness.
<b>Reproductive Toxicity</b>	Not considered to be toxic to reproduction.
<b>Carcinogenicity</b>	Not considered to be a carcinogenic hazard.
<b>Skin Sensitisation</b>	Not expected to be a skin sensitiser
<b>Aspiration Hazard</b>	Not expected to be an aspiration hazard.
<b>STOT-single exposure</b>	May cause drowsiness or dizziness.
<b>STOT-repeated exposure</b>	Not expected to cause damage to organs.
<b>Germ cell mutagenicity</b>	Not considered to be a mutagenic hazard.
<b>Respiratory sensitisation</b>	Not expected to be a respiratory sensitiser.

## 12. Ecological information

<b>Ecotoxicity</b>	No data available for this specific material.
<b>Persistence and degradability</b>	Biodegradable
<b>Mobility</b>	Not available
<b>Bioaccumulative Potential</b>	Acetone has negligible potential to bioaccumulate.
<b>Environmental Protection</b>	Prevent this material entering waterways, drains and sewers.

## 13. Disposal considerations

<b>Disposal Considerations</b>	Disposal of spilled or waste material must be carried out in accordance with the relevant local and national government regulations. Advise flammable nature. Empty containers may contain flammable residues. Do not puncture, cut or weld empty containers.
--------------------------------	---

## 14. Transport information

<b>Transport Information</b>	Road and Rail Transport: This material is a Class 3 - Flammable Liquid according to The Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition) Class 3 - Flammable Liquids are incompatible in a placard load with any of the following: - Class 1, Explosives - Division 2.1, Flammable Gases, (Division 2.1 and Class 3 are incompatible in transport if both are in tanks or other receptacles with a capacity
------------------------------	---

Infosafe No™ LPWBO	Issue Date : March 2012	ISSUED by PARCHEMC
--------------------	-------------------------	--------------------

Product Name **SEALER PREP (TYRE MARK REMOVER)**

Classified as hazardous

- individually exceeding 500 L.)
- Division 2.3, Toxic Gases
- Division 4.2 Spontaneously Combustible Substances
- Division 5.1 Oxidising Agents and Division 5.2, Organic Peroxides
- Class 6 Toxic or Infectious Substances (where the flammable liquid is nitromethane)
- Class 7 Radioactive Substances.

Marine Transport (IMO/IMDG):  
Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

UN No.: 1993  
Proper Shipping Name: FLAMMABLE LIQUID, N.O.S. (Contains Acetone & Xylene)  
Class: 3  
Packaging Group: II  
EMS No.: F-E, S-E  
Special Provision: 274

Air Transport (ICAO/IATA):  
Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

UN No.: 1993  
Proper Shipping Name: FLAMMABLE LIQUID, N.O.S. (Contains Acetone & Xylene)  
Class: 3  
Packaging Group: II  
Label: Flammable Liquid  
Packaging Instructions (passenger & cargo): 353  
Packaging Instructions (cargo only): 364  
1993

<b>U.N. Number</b>	
<b>UN proper shipping name</b>	FLAMMABLE LIQUID, N.O.S. - (Contains Acetone & Xylene)
<b>Transport hazard class(es)</b>	3
<b>Hazchem Code</b>	•3YE
<b>Packing Group</b>	II
<b>EPG Number</b>	3A1
<b>IERG Number</b>	14
<b>IMDG Marine pollutant</b>	No

## 15. Regulatory information

**Regulatory Information** Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia  
Classified as a Scheduled Poison according to the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

**Poisons Schedule** S6

**AICS (Australia)** All components of this product are listed on the Australian Inventory of Chemical Substances (AICS) or exempted.

## 16. Other Information

**Date of preparation or last revision of SDS** SDS Reviewed: March 2012, Supersedes: April 2007

**Contact Person/Point** Technical Support: 1800 812 864

...End Of MSDS...

Infosafe No™ LPWBO

Issue Date : March 2012

ISSUED by PARCHEMC

Product Name **SEALER PREP (TYRE MARK REMOVER)**

Classified as hazardous

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe MSDS displayed is the intellectual property of Acohs Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe MSDS displayed is the intellectual property of Acohs Pty Ltd.  
The compilation of MSDS's displayed is the intellectual property of Acohs Pty Ltd.

Copying of any MSDS displayed is permitted for personal use only and otherwise is not permitted. In particular the MSDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of MSDS without the express written consent of Acohs Pty Ltd.